THE JOURNAL

OF THE

AMERICAN CERAMIC SOCIETY

DECEMBER 1, 1942

MONTHLY PUBLICATION DEVOTED TO THE ARTS AND SCIENCES RELATED TO THE SILICATE INDUSTRIES

OFFICIAL PERSONNEL OF DIVISIONS, 1942–1943

	Art	Enamel	Glass	Materials and Equipment	Refractories	Structural Clay Products	White Wares
Trustee	L. E. Barringer	J. E. Hansen	G. W. Morey	J. E. Eagle	J. D. Sullivan	Frederick Heath, Jr.	F. P. Hall
Chairman	J. A. Foster	Karl Kautz	W. C. Taylor	J. F. McMahon	R. S. Bradley	R. A. Shipley	F. C. Henderson
Vice-Chairman	A. E. Baggs	D. G. Bennett	J. F. Greene	E. M. Rupp	C. L. Thompson	R. L. Stone	
2d Vice-Chairman	H. S. Nash		K. C. Lyon				
Secretary	Marion L. Fosdick	D. G. Moore	S. R. Scholes	J. R. Kauffman	W. R. Kerr	E. F. Theobald	J. R. Beam
Division Nominations	A. A. Ayars	W. G. Martin R. J. Whitesell W. W. Higgins	F. C. Flint J. C. Hostetter E. W. Tillotson	B. T. Bonnot S. S. Cole	Gilbert Solér C. A. Freeman	H. G. Schurecbt Chester R. Austin	J. W. Hepplewhite Harry Thiemecke
Papers and Program	H. S. Nash	D. G. Bennett	J. F. Greene	E. W. Koenig N. B. Davis	S. M. Swain P. G. Herold C. L. Norton E. E. Callinan	R. L. Stone J. H. Isenhour V. W. Boeker	J. W. Whittemore H. L. Latimer C. M. Lambe, Jr.
Membership	Carlton Atherton	O. E. Mulvane	W. R. Lester	H. B. Foster, Jr.	E. C. Petrie	L. R. Whitaker	W. E. Welliver
Standards	F. R. Matson	R. L. Cook	A. E. Badger F. W. Adams H. P. Hood	C. C. Treischel O. A. Kantner	E. E. Callinan	Frederick Heath, Jr. Clarence P. Austin	F. P. Hall
Research	H. E. Marley	M. J. Bahnsen	J. S. Gregorius H. R. Lillie A. Silverman	G. M. Hutt	D. W. Ross	Chester R. Austin	Ralston Russell, Jr.
Data	M. L. Fosdick	H. L. Cook		F. E. Lobaugh	Grant Diamond	E. B. Merry, Jr.	R. M. Campbell
Rules	Theodore Lenchner	E. E. Howe	D. E. Sharp	W. R. Malkin	S. F. Walton	Frederick Heath, Jr. J. W. Whittemore D. F. Stevens	W. E. Palmer
Councillors	A. E. Baggs C. M. Harder	J. D. Tetrick R. L. Fellows	A. K. Lyle U. E. Bowes	V. V. Kelsey		J. L. Child J. W. Whittemore	Ralston Russell, Jr. Edward Schramm
Exhibitions	W. A. Weldon		J. E. Frazier	F. T. Buzard			
Industrial Management			L. C. Roche	E. W. Knapp	O. L. Jones		
Bibliography		J. E. Rosenberg					

JOURNAL

of

The American Ceramic Society

A Monthly Journal Devoted to the
Arts and Sciences Related to
the Silicate Industries

Volume 25, 1942

Ross C. Purdy, *Editor*
Emily C. Van Schoick, *Assistant Editor*

Committee on Publications: D. E. Sharp, *Chairman;* E. E. Marbaker, J. B. Austin,
G. H. Spencer-Strong, and Ross C. Purdy

Editorial and Advertising Offices: 2525 North High Street, Columbus, Ohio
Publication Office: Easton, Pennsylvania

THE AMERICAN CERAMIC SOCIETY TRUSTEES AND OFFICERS FOR 1942–1943

President: Louis J. Trostel, General Refractories Co., Baltimore, Md.
Vice-President: M. E. Holmes, N. Y. State College of Ceramics, Alfred, N. Y.
Treasurer: C. Forrest Tefft, The Claycraft Co., Columbus, Ohio
Secretary-Editor: R. C. Purdy, 2525 North High St., Columbus, Ohio
Past-President: J. T. Littleton, Corning Glass Works, Corning, N. Y.
Past-President: J. L. Carruthers, Ohio State University, Columbus, Ohio

TRUSTEES FROM INDUSTRIAL DIVISIONS*

Art: L. E. Barringer, General Electric Co., Schenectady, N. Y. (1943)
Enamel: J. E. Hansen, Ferro Enamel Corp., Cleveland, Ohio (1943)
Glass: G. W. Morey, Corning Glass Works, Parkersburg, W. Va. (1944)
Materials and Equipment: J. E. Eagle, Vitro Mfg. Co., Pittsburgh, Pa. (1945)
Refractories: J. D. Sullivan, Battelle Memorial Institute, Columbus, Ohio (1943)
Structural Clay Products: Frederick Heath, Jr., Owens-Corning Fiberglas Corp., Toledo, Ohio (1945)
White Wares: F. P. Hall, Onondaga Pottery Co., Syracuse, N. Y. (1944)
Institute of Ceramic Engineers: H. G. Wolfram, Porcelain Enamel & Mfg. Co., Baltimore, Md. (1944)
Ceramic Educational Council: J. W. Whittemore, Virginia Polytechnic Institute, Blacksburg, Va. (1944)

* Date of expiration of term of office in parentheses.

DIVISION OFFICERS

Art
Chairman: J. A. Foster, 9591 Sorrento Ave., Detroit, Mich.
Secretary: Marion L. Fosdick, N. Y. State College of Ceramics, Alfred, N. Y.

Enamel
Chairman: Karl Kautz, Climax Molybdenum Co., First National Bank Bldg., Canton, Ohio
Secretary: D. G. Moore, National Bureau of Standards, Washington, D. C.

Glass
Chairman: W. C. Taylor, Corning Glass Works, Corning, N. Y.
Secretary: S. R. Scholes, N. Y. State College of Ceramics, Alfred, N. Y.

Materials and Equipment
Chairman: J. F. McMahon, N. Y. State College of Ceramics, Alfred, N. Y.
Secretary: J. R. Kauffman, Allied Engineering Co., 29 Highland Drive, Milltown, N. J.

Refractories
Chairman: R. S. Bradley, A. P. Green Fire Brick Co., Mexico, Mo.
Secretary: W. R. Kerr, Armstrong Cork Co., Beaver Falls, Pa.

Structural Clay Products
Chairman: R. A. Shipley, National Fireproofing Corp., Pittsburgh, Pa.
Secretary: E. F. Theobald, Metropolitan Paving Brick Co., Canton, Ohio

White Wares
Chairman: F. C. Henderson, Royal China Co., Sebring, Ohio
Secretary: J. R. Beam, Universal Sanitary Mfg. Co., New Castle, Pa.

OFFICERS OF THE FELLOWS

Dean: R. B. Sosman, U. S. Steel Corp., Kearny, N. J.
Associate Dean: T. N. McVay, University of Alabama, University, Ala.
Secretary-Treasurer: R. M. King, Ohio State University, Columbus, Ohio

INSTITUTE OF CERAMIC ENGINEERS

President: H. M. Kraner, Bethlehem Steel Co., Bethlehem, Pa.
Vice-President: H. B. DuBois, Consolidated Feldspar Corp., Trenton, N. J.
Secretary: H. G. Schurecht, New York State College of Ceramics, Alfred, N. Y.

CERAMIC EDUCATIONAL COUNCIL

President: N. W. Taylor, Pennsylvania State College, State College, Pa.
Vice-President: R. M. Campbell, N. Y. State College of Ceramics, Alfred, N. Y.
Secretary: C. M. Dodd, Iowa State College, Ames, Iowa

LOCAL SECTIONS

Baltimore-Washington
Chairman: Kenneth M. Smith, Severn Clay Co., Baltimore, Md.
Secretary: W. R. Lester, Maryland Glass Corp., Baltimore, Md.

Central Ohio
Chairman: H. J. Orlowski, O.S.U. Engr. Expt. Sta., Columbus, Ohio
Secretary: A. C. Jackson, The Claycraft Co., Columbus, Ohio

Chicago
Chairman: H. G. Fisk, Armour Research Foundation, Inc., Chicago, Ill.
Secretary: C. R. Filippi, Illinois Brick Co., Chicago, Ill.

Michigan-Northwestern Ohio
Chairman: J. F. Quirk, AC Spark Plug Co., Flint, Mich.
Secretary: W. V. Blake, Macklin Co., Jackson, Mich.

Northern California
Chairman: G. A. Page, Stockton Fire Brick Co., Pittsburg, Calif.
Secretary: B. W. Wyatt, N. Clark & Sons, Alameda, Calif.

Pacific-Northwest
President: M. D. Saindon, Chehalis Brick & Tile Co., Chehalis, Wash.
Secretary: W. P. Keith, Univ. of Washington, Seattle, Wash.

Pittsburgh
Chairman: E. E. Marbaker, Mellon Institute, Pittsburgh, Pa.
Secretary: H. E. Simpson, Mellon Institute, Pittsburgh, Pa.

Southern California
Chairman: J. E. Stevens, Emsco Refractories Co., South Gate, Calif.
Secretary: R. F. Evans, Gladding, McBean & Co., Los Angeles, Calif.

St. Louis
Chairman: H. H. Hanna, Pittsburgh Plate Glass Co., Crystal City, Mo.
Secretary: J. H. Ivery, Hydraulic Press Brick Co., St. Louis, Mo.

TABLE OF CONTENTS

for

Volume 25, 1942

January 1 [1], pp. 1–32

1. C. W. Parmelee and A. R. Rodriguez: Catalytic Mullitization of Kaolinite by Metallic Oxide..... 1
2. C. W. Parmelee and P. E. Buckles: Study of Glaze and Body Interface..... 11
3. Ralston Russell, Jr., and C. F. Hanks, Jr.: Stress-Strain Characteristics of Plastic Clay Masses..... 16
4. A. M. Johnsen and J. J. Canfield: Effect of Iron Oxide on Tensile Strength of Porcelain Enamel..... 29

January 15 [2], pp. 33–59

5. J. H. Koenig: Properties of Ware versus Thermal History: I, Tests on Vitreous China Bodies and Ware 33
6. J. H. Koenig: Properties of Ware versus Thermal History: II, Tests on Semivitreous China Bodies and Ware..... 41
7. P. C. McCollom and R. R. Danielson: Effect of Firing Treatment on Physical Properties of Dry-Process Enamels..... 48
8. H. L. Cook and C. H. Wolff: Effect of Set of Enamels on Hydrometer Readings of the Slip..... 51
9. L. G. Ghering and F. W. Preston: Decrepitude of Old Bottles, Aging, Weathering, and Solarization Compared with Use and Abuse..... 53
10. W. E. Brownell and S. R. Scholes: Glass-Batch Mixing..... 56

February 1 [3], pp. 61–96

11. Owens-Illinois Glass Company Research Laboratory: Effect of Barium Oxide and Zinc Oxide on Properties of Soda-Dolomite Lime-Silica Glass..... 61
12. H. A. Shadduck and Arthur Van Zee: Analysis of Gases Dissolved in Glass and Gases Present in Seeds... 69
13. R. L. Green: X-Ray Diffraction and Physical Properties of Potassium Borate Glasses..... 83
14. C. J. Koenig: Nepheline Syenite in Hotel Chinaware Bodies..... 90
15. R. F. Mather: Zirconia–Magnesia Spinel System..... 93

February 15 [4], pp. 97–122

16. K.-H. Sun and Alexander Silverman: Glassforming Nature of Oxides with Special Reference to Tantala, Titania, and Beryllia..... 97
17. K.-H. Sun and Alexander Silverman: Can Silicon Take a Six-Fold Coordination in Glass?..... 101
18. A. E. Badger and A. C. Ottoson: Effect of Light on Color of Glass..... 104
19. C. W. Parmelee and V. D. Fréchette: Heat-of-Wetting Values of Unfired and Fired Clays..... 108
20. M. S. Nelson and R. R. Ralston: Design and Operation of Electric Load-Test Furnace..... 112
21. F. C. Arrance: Use of the Photronic Cell and Spectrophotometer for Measuring Translucency of Whiteware 116

March 1 [5], pp. 123–49

22. J. D. Sullivan and C. R. Austin: Selenium Ruby Glass..... 123
23. C. R. Austin and J. D. Sullivan: Selenium Black Glass..... 128
24. N. J. Kreidl: Zirconium and Thorium Oxides in Ceramics..... 129
25. N. J. Kreidl: Rare Earths..... 141
26. J. S. Owens and E. C. Emanuel: Variable Factors in Accelerated Autoclave Chemical Durability Tests.... 143

March 15 [6], pp. 151–74

27. R. B. Snow and W. J. McCaughey: Equilibrium Studies in System FeO–Al_2O_3–SiO_2..... 151
28. Karl Kautz: Molybdenum in Enamels: II, Adherence Produced with Soluble and Insoluble Molybdates 160
29. D. R. Goetchius: Porcelain Enamel as Protective Coating for Hot-Water Tanks..... 164
30. W. B. Silverman: Surface Tension of Glass and Its Effect on Cords..... 168

April 1 [7], pp. 175–216

31. C. A. Zapffe: I, Cause of Defects in Enamel Fired on Cast Iron at Temperatures above 725°C..... 175
32. C. A. Zapffe and J. L. Yarne: II, Scratch Blisters..... 180
33. C. A. Zapffe and J. L. Yarne: III, Relation of Surface Oxidation to Certain Defects in Enamel Coatings on Steel..... 191
34. C. A. Zapffe and J. L. Yarne: IV, Chips, Fish Scales, and Shiners..... 194
    Karl Kautz Discussion; Zapffe and Yarne Reply..... 203
35. C. A. Zapffe and C. E. Sims: V, Further Considerations of Hydrogen as Cause of Enamel Defects..... 205

April 15 [8] (No Journal papers)

Program issue for Forty-Fourth Annual Meeting

May 1 [9], pp. 217–40

36. A. I. Andrews and H. R. Swift: Iron Oxide in Enamel Glass as Dissolved from the Metal Base..... 217
37. E. A. Hauser and A. L. Johnson: Plasticity of Clays..... 223
38. J. M. Sharf: Conditions Encountered in Filling Pressure Ware..... 228
39. C. J. Koenig: Low-Temperature Vitreous Bodies..... 230
40. M. S. Nelson and Hewitt Wilson: Commercial Firing Survey of Car-Tunnel Kilns..... 237

June 1 [10], pp. 241–82

41. J. F. Schairer: System CaO–FeO–Al_2O_3–SiO_2: I, Results of Quenching Experiments on Five Joins..... 241
42. Sidney Speil and Hewitt Wilson: Improved Mercury Balance Volumeter..... 275
43. Edward Forst, Jr., and N. J. Kreidl: Red Silver Glasses..... 278
44. F. M. Veazie and W. A. Weyl: Effect of Tin in Gold Ruby Glass..... 280
45. R. J. Smith: Preparation of Refractory and Coal-Ash Test Cones..... 282

July 1 [11], pp. 283–326

46. T. L. Hurst and E. B. Read: Survey of Literature on Slag Tests for Refractory Materials..... 283
47. R. R. Ralston and G. T. Faust: Electric Furnace Study of MgO–SiO_2 System..... 294
48 H. M. Kraner: Refractories Service Conditions in the Blast Furnace..... 311
49. H. G. Schurecht, J. K. Shapiro, and Z. Zabawsky: Influence of Fluxes of Spodumene and Feldspar Mixtures on Properties of Chinaware Bodies..... 321

August 1 [12], pp. 327–58

50. M. D. Burdick, W. W. Meyer, and T. A. Klinefelter: Effect of Exchangeable Bases on Properties of Ball Clays..... 327
51. A. J. Johnson and F. H. Norton: Fundamental Study of Clay: III, Casting as Base-Exchange Phenomenon..... 336
52. A. L. Johnson and W. G. Lawrence: Fundamental Study of Clay: IV, Surface Area and Its Effect on Exchange Capacity of Kaolinite..... 344
53. H. G. Schurecht, J. F. McMahon, and C. M. Lampman: Effect of Steam and Hot Water with Soda Ash and Wetting Agent on Properties of Clay..... 346
54. R. K. Hursh and M. K. Blanchard: Expansion, Contraction, and Strength Changes of Clays During Firing 351
55. R. L. Shute and A. E. Badger: Effect of Iron Oxide on Melting of Glass..... 355

September 1 [13], pp. 359–90

56. J. S. Owens and E. C. Emanuel: Effect of Storage Conditions on Weathering of Commercial Glass Containers..... 359
57. Frank Day, Jr., and Alexander Silverman: Oxidation-Reduction Equilibria in Glass Between Iron and Selenium in Several Furnace Atmospheres..... 371
58. W. H. Bruckner and H. Czyzewski: Metallurgical Study of Cast Iron for Glass Molds..... 381
59. J. C. McMullen: Transverse Testing Furnace..... 389

October 1 [14], pp. 391–424

60. H. N. Baumann, Jr., and C. H. Moore, Jr.: Electric Furnace Boroaluminate..... 391
61. A. E. Badger, H. C. Johnson, and J. O. Kraehenbuehl: Structure of Sodium Borate Glasses as Affected by Temperature..... 395
62. Owens-Illinois Glass Company Research Laboratory: Effect of Iron Oxide on Properties of Soda-Dolomite Lime-Silica Glass..... 401
63. J. G. McCann: Decay of Vibration Phenomena of Glass Bars..... 409
64. W. E. Palmer: Influence of Flint Particle Size on Permanent Moisture and Thermal Expansion in Porous Earthenware Bodies..... 413
65. I. J. W. MacHattie and A. E. R. Westman: Effect of Sulfur and Reducing Gases on Semivitreous Dinnerware Glaze and Decalcomania Decoration..... 416
66. E. W. Koenig: Calculation of Mineralogical Composition of Feldspar by Chemical Analysis..... 420
67. H. G. Schurecht and J. F. McMahon: Testing and Improving Drying Behavior of Clays..... 422

November 1 [15], pp. 427–66

68. F. W. Preston: Strength of Bottles as Affected by Limitations of Manufacturing Processes..... 427
69. A. Herman and H. M. Kindsvater: Studies Correlating Bottling Line with Pressure Test Breakage..... 434
70. M. D. Rigterink, R. O. Grisdale, and S. O. Morgan: Relation Between Chemical Composition and Dielectric Properties of Ceramic Materials with Low Dielectric Losses..... 439
71. Hans Thurnauer and A. R. Rodriguez: Notes on Constitution of Steatite..... 443
72. C. J. Norton, Jr.: Apparatus for Measuring Thermal Conductivity of Refractories..... 451
73. E. C. Petrie and D. W. Kocher: Control Testing for Consistency of Refractory Mortars..... 459
74. E. E. Howe and E. P. Bolin: Resistance of Enamels to Thermal Shock..... 463

December 1 [16], pp. 467–486

Author Index to *The Journal*..... 467
Subject Index to *The Journal*..... 468
Citations Index to *The Journal*..... 479

INDEXES TO THE JOURNAL

Compiled by

THE AMERICAN CERAMIC SOCIETY

ROSS C. PURDY, *Editor*
EMILY C. VAN SCHOICK, *Assistant Editor*

Volume 25 December, 1942 No. 16

AUTHOR INDEX

The reference number in parentheses refers to the *monthly* issue of the *Journal;* the numbers following are the *page* numbers.

Because of temporary publication changes in the order of issuance of the *Journal* during the year 1942, the reader is requested to note the following issue numbers and their respective publication dates: (1) January 1; (2) January 15; (3) February 1; (4) February 15; (5) March 1; (6) March 15; (7) April 1; (8) Forty-Fourth Annual Meeting Program (no *Journal* papers); (9) May 1; (10) June 1; (11) July 1; (12) August 1; (13) September 1; (14) October 1; (15) November 1; (16) December 1.

Andrews, A. I., and Swift, H. R. Iron oxide in enamel glass as dissolved from metal base (9) 217–22.
Arrance, F. C. Use of photronic cell and spectrophotometer for measuring translucency of whiteware, (4) 116–22.
Austin, C. R., and Sullivan, J. D. Selenium black glass, (5) 128–29.
Austin, C. R. See Sullivan, J. D.

Badger, A. E., Johnson, H. C., and Kraehenbuehl, J. O. Structure of sodium borate glasses as affected by temperature, (14) 395–401.
Badger, A. E., and Ottoson, A. C. Effect of light on color of glass, (4) 104–108.
Badger, A. E. See Shute, R. L.
Baumann, H. N., Jr., and Moore, C. H., Jr. Electric furnace boroaluminate, (14) 391–94.
Blanchard, M. K. See Hursh, R. K.
Bolin, E. P. See Howe, E. E.
Brownell, W. E., and Scholes, S. R. Glass-batch mixing, (2) 56–59.
Bruckner, W. H., and Czyzewski, H. Metallurgical study of cast iron for glass molds, (13) 381–88.
Buckles, P. E. See Parmelee, C. W.
Burdick, M. D., Meyer, W. W., and Klinefelter, T. A. Effect of exchangeable bases on some properties of ball clays, (12) 327–36.

Canfield, J. J. See Johnsen, A. M.
Cook, H. L., and Wolff, C. F. Effect of set of enamels on hydrometer readings of slip, (2) 51–52.
Czyzewski, H. See Bruckner, W. H.

Danielson, R. R. See McCollom, P. C.
Day, Frank, Jr., and Silverman, Alexander. Oxidation-reduction equilibria in glass between iron and selenium in several furnace atmospheres, (13) 371–81.

Emmanuel, E. C. See Owens, J. S.

Faust, G. T. See Ralston, R. R.
Forst, Edward, Jr., and Kreidl, N. J. Red silver glasses, (10) 278–80.
Fréchette, V. D. See Parmelee, C. W.

Gehring, L. G., and Preston, F. W. Decrepitude of old bottles: Aging, weathering, and solarization compared with use and abuse, (2) 53–55.
Goetchius, D. R. Porcelain enamel as protective coating for hot-water tanks, (6) 164–68.
Green, R. L. X-ray diffraction and physical properties of potassium borate glasses, (3) 83–89.
Grisdale, R. O. See Rigterink, M. D.

Hanks, C. F., Jr. See Russell, Ralston, Jr.
Hauser, E. A., and Johnson, A. L. Plasticity of clays, (9) 223–27.
Herman, A., and Kindsvater, H. M. Studies correlating bottling line with pressure test breakage, (15) 434–38.
Howe, E. E., and Bolin, E. P. Resistance of enamels to thermal shock, (15) 463–66.
Hursh, R. K., and Blanchard, M. K. Expansion, contraction, and strength changes of some clays during firing, (12) 351–54.
Hurst, T. L., and Read, E. B. Survey of literature on slag tests for refractory materials, (11) 283–94.

Johnsen, A. M., and Canfield, J. J. Effect of iron oxide on tensile strength of porcelain enamel, (1) 29–32.
Johnson, A. L. See Hauser, E. A.
Johnson, A. L., and Lawrence, W. G. Fundamental study of clay: IV, Surface area and its effect on exchange capacity of kaolinite, (12) 344–46.
Johnson, A. L., and Norton, F. H. Fundamental study of clay: III, Casting as base-exchange phenomenon, (12) 336–44.
Johnson, H. C. See Badger, A. E.

Kautz, Karl. Discussion of "Chips, fish scales, and shiners," (7) 203–204; reply by C. A. Zapffe and J. L. Yarne, (7) 204–205; Molybdenum in enamels: II, Adherence produced with soluble and insoluble molybdates, (6) 160–63.
Kindsvater, H. M. See Herman, A.
Klinefelter, T. A. See Burdick, M. D.
Kocher, D. W. See Petrie, E. C.
Koenig, C. J. Low-temperature vitreous bodies, (9) 230–36; Nepheline syenite in hotel chinaware bodies, (3) 90–93.
Koenig, E. W., Calculation of mineralogical composition of feldspar by chemical analysis, (14) 420–22.
Koenig, J. H. Properties of ware vs. thermal history: I, Tests on vitreous china bodies and ware, (2) 33–40; II, Tests on semivitreous china bodies and ware, (2) 41–48.
Kraehenbuehl, J. O. See Badger, A. E.
Kraner, H. M. Refractories service conditions in blast furnace, (11) 311–20.
Kreidl, N. J. Rare earths, (5) 141–43; Zirconium oxide and thorium oxide in ceramics, (5) 129–41.
Kreidl, N. J. See Forst, Edward, Jr.

Lampman, C. M. See Schurecht, H. G.
Lawrence, W. G. See Johnson, A. L.

MacHattie, I. J. W., and Westman, A. E. R. Effect of sulfur and reducing gases on semivitreous dinnerware glaze and decalcomania decoration, (14) 416–20.
Mather, R. F. Zirconia–magnesia spinel system, (3) 93–96.
McCann, J. G. Decay of vibration phenomena of glass bars, (14) 409–13.
McCaughey, W. J. See Snow, R. B.
McCollom, P. C., and Danielson, R. R. Effect of firing treatment on physical properties of dry-process enamels, (2) 48–50.
McMahon, J. F. See Schurecht, H. G.
McMullen, J. C. Transverse testing furnace, (13) 389–90.
Meyer, W. W. See Burdick, M. D.
Moore, C. H., Jr. See Baumann, H. N., Jr
Morgan, S. O. See Rigterink, M. D.

Nelson, M. S., and Ralston, R. R. Design and operation of electric load-test furnace, (4) 112–16.
Nelson, M. S., and Wilson, Hewitt. Commercial firing survey of car-tunnel kilns, (9) 237–40.
Norton, C. L., Jr. Apparatus for measuring thermal conductivity of refractories, (15) 451–59.
Norton, F. H. See Johnson, A. L.

Ottoson, A. C. See Badger, A. E.
Owens-Illinois Glass Company Research Laboratory. Effect of barium and zinc oxides on properties of soda-dolomite lime-silica glass, (3) 61–69; Effect of iron oxide on properties of soda-dolomite lime-silica glass, (14) 401–408.
Owens, J. S., and Emanuel, E. C. Effect of storage conditions on weathering of commercial glass containers, (13) 359–71; Variable factors in accelerated autoclave chemical durability tests, (5) 143–49.

Palmer, W. E. Influence of flint particle size on permanent moisture and thermal expansion in porous earthenware bodies, (14) 413–16.
Parmelee, C. W., and Buckles, P. E. Study of glaze and body interface, (1) 11–15.
Parmelee, C. W., and Fréchette, V. D. Heat-of-wetting values of unfired and fired clays, (4) 108–12.
Parmelee, C. W., and Rodriguez, A. R. Catalytic mullitization of kaolinite by metallic oxide, (1) 1–10.
Petrie, E. C., and Kocher, D. W. Control testing for consistency of refractory mortars, (15) 459–63.
Preston, F. W. Strength of bottles as affected by limitations of manufacturing processes, (15) 427–34.
Preston, F. W. See Gehring, L. G.

Ralston, R. R., and Faust, G. T. Electric furnace study of the MgO–SiO_2 system, (11) 294–310.
Ralston, R. R. See Nelson, M. S.
Read, E. B. See Hurst, T. L.
Rigterink, M. D., Grisdale, R. O., and Morgan, S. O. Relation between chemical composition and dielectric properties of ceramic materials with low dielectric losses, (15) 439–43.
Rodriguez, A. R. See Parmelee, C. W.; Thurnauer, Hans.
Russell, Ralston, Jr., and Hanks, C. F., Jr. Stress-strain characteristics of plastic clay masses, (1) 16–28.

Schairer, J. F. System CaO–FeO–Al_2O_3–SiO_2: I, Results of quenching experiments on five joins, (10) 241–74.
Scholes, S. R. See Brownell, W. E.
Schurecht, H. G., and McMahon, J. F. Testing and improving drying behavior of clays, (14) 422–24.
Schurecht, H. G., McMahon, J. F., and Lampman, C. M. Effect of steam and hot water with soda ash and a wetting agent on properties of clay, (12) 346–51.
Schurecht, H. G., Shapiro, J. K., and Zabawsky, Z. Influence of fluxes of spodumene and feldspar mixtures on properties of chinaware bodies, (11) 321–26.
Shadduck, H. A., and Van Zee, Arthur. Analysis of gases dissolved in glass and gases present in seeds, (3) 69–83.
Shapiro, J. K. See Schurecht, H. G.
Sharf, J. M. Conditions encountered in filling pressure ware, (9) 228–30.
Shute, R. L., and Badger, A. E. Effect of iron oxide on melting of glass, (12) 355–58.
Silverman, Alexander. See Day, Frank, Jr.; Sun, K.-H.
Silverman, W. B. Surface tension of glass and its effect on cords, (6) 168–73.
Smith, R. J. Preparation of refractory and of coal-ash test cones, (10) 282.
Snow, R. B., and McCaughey, W. J. Equilibrium studies in system FeO–Al_2O_3–SiO_2, (6) 151–60.
Spell, Sidney, and Wilson, Hewitt. Improved mercury balance volumeter, (10) 275–77.
Sullivan, J. D., and Austin, C. R. Selenium ruby glass, (5) 123–27.
Sullivan, J. D. See Austin, C. R.
Sun, K.-H., and Silverman, Alexander. Can silicon take a six-fold coordination in glass?, (4) 101–103; Glassforming nature of oxides with special reference to Ta, Ti, and Be, (4) 97–100.
Swift, H. R. See Andrews, A. I.

Thurnauer, Hans, and Rodriguez, A. R. Notes on constitution of steatite, (15) 443–50.

Van Zee, Arthur. See Shadduck, H. A.
Veazie, F. M., and Weyl, W. A. Effect of tin in gold ruby glass, (10) 280–81.

Westman, A. E. R. See MacHattie, I. J. W.
Weyl, W. A. See Veazie, F. M.
Wilson, Hewitt. See Nelson, M. S.; Spell, Sidney.
Wolff, C. H. See Cook, H. L.

Zabawsky, Z. See Schurecht, H. G.
Zapffe, C. A. Cause of defects in enamel fired on cast iron at temperatures above 725°C., I, (7) 175–80.
Zapffe, C. A., and Sims, C. E. Further considerations of hydrogen as cause of enamel defects, V, (7) 205–15.
Zapffe, C. A., and Yarne, J. L. Scratch blisters, II, (7) 180–90; Relation of surface oxidation to certain defects in enamel coatings on steel, III, (7) 191–94; Chips, fish scales, and shiners, IV, (7) 194–203; Kautz discussion, (7) 203–204; Zapffe and Yarne reply, (7) 204–205.

SUBJECT INDEX TO THE JOURNAL
Vol. 25, 1942

The reference number in parentheses refers to the *monthly* issue of the *Journal;* the number following is the *page* number; (the issue numbers for Vol. 25, 1942, are (1) through (16)).

Abrasion of blast-furnace refractories, (11) 315–16; references, (11) 320.
of ground-coat enamels: surface resistance, (2) 49; dye-stain method of measurement, (2) 50.
surface, of wet-process enamels, effect of firing treatment, Hutchison cited, (2) 48.
Abrasives, zirconium carbides, characteristics and uses, (5) 133.
Acid resistance of enamels. See *Enamels, acid-resistant.*
Aging of glass bottles and jars in warehouse, (2) 54.
of plastic clay bodies, (1) 23.
Ajax-Northrup furnace, electric induction, for glassmelting, diagram, (13) 373.
Alkali extraction in glass bottles, accelerated autoclave chemical durability test, (5) 143.
in glass bottles, weathering tests, method and tables, (13) 361–64.
Alkaline earth oxides and alkaline earth carbonates as feldspar substitute in steatite bodies, dielectric properties, tables and curves, (15) 441–42.
as fluxes in talc-kaolin mixture, effect on dielectric properties of low-loss ceramics, (15) 443.
Alloy irons. See *Molds for glassforming.*
Alumina–anorthite–FeO join, (10) 253; compositions, primary phases, and liquidus temperatures, equilibrium diagram and table, (10) 254–55.
–boric oxide system, properties, cone fusion, and pouring and blistering temperature, curves, (14) 393–94.
–CaO–FeO–SiO_2, quenching experiments on five joins, (10) 241–74.
–FeO–SiO_2 system, equilibrium studies, (6) 151.
–MgO–SiO_2 system, portion of phase equilibrium diagram, chemical composition and dielectric properties, (15) 440–41.
Aluminum chloride for bisque-mold treatment, effect on casting slips, yield value vs. water content, (12) 341.
Aluminum hydroxide for ball-clay treatment, effect on physical properties, (12) 329, (12) 335.
Amber glass. See *Glass, bottle.*
American Society for Testing Materials, C24–36 and D271–40, for test cone preparation, (10) 282.
hydrostatic pressure and thermal shock tests on bottles, (15) 434–35.
Ammonium molybdate, properties and behavior in enamels, (6) 161.
Amsler tensile testing machine for fiber breaking tests for enamels, photo, (1) 30.
Analyses, chemical, for mineralogical composition of feldspar, (14) 420.
Annealing, disannealing of glass bars, effect on sonic properties, (14) 412.
of sand-cast and chill-cast irons for glassforming molds vs. spheroidizing treatment, microstructure and hardness gradients, photomicrograph and curves, (13) 381–88.
Annealing rack for enamel threads in tensile strength tests, (1) 30.
Anorthite–Al_2O_3–SiO_2 join, compositions, primary phases, and liquidus temperatures: equilibrium diagram and table, (10) 253–55; for anorthite–$CaSiO_3$–FeO join, (10) 255, (10) 257–59, (10) 266; for anorthite–gehlenite–FeO join, (10) 260–62; for anorthite–SiO_2–FeO join, (10) 250–53.
Antimony, cerium oxide as substitute for bleaching cobalt ground coats, (5) 143.
in dry-process enamels, firing treatment, effect on properties, (2) 48–50.
in glass, effect on fading, curves and discussion, (4) 106–107.
Apparatus, Amsler tensile testing machine for enamel-thread tests, photo, (1) 30.
annealing rack for enamel threads in tensile strength tests, (1) 30.
Brock creep-test, for speed-effect tests on vitreous electrical porcelain, (1) 25.
Apparatus (*Continued*)
camera for decay patterns of vibrating glass bars, (14) 411–12.
for cast-iron specimens, accelerated cracking test, photo, (13) 383.
clay-compression, photo and diagram, (1) 17.
clay, for heat-of-wetting measurements, (4) 111.
clay, for hot transverse strength measurements, photo, (12) 352.
clay, for thermal expansion and contraction tests, diagram, (12) 351.
electrometer and spectrophotometer, Coleman, for spectral transmission measurements in glass, (13) 374.
furnaces. See *Furnaces.*
for gas analyses in glass: furnace assembly, description and photo, (3) 69–70; Hyvac and metal diffusion (shell) pump (3) 71; Toepler automatic pump, circuit for operation, (3) 71; complete setup, photo, (3) 73.
for gas analysis of seeds in glass, (3) 78.
glassmaking, for bottle production, Owens suction, Hartford-Empire, I.S., and Lynch types, (15) 431–32.
hydrometer for specific gravity tests on enamel slips, (2) 51.
Hyvac and metal diffusion (shell) pump, photo, (3) 71.
Lyons scratch-hardness tester, scratch resistance of glazes vs. glost temperature, (2) 47.
mixers for glass batches, types, photos, (2) 56.
mixers, Read, for pugging clays, photo, (12) 347.
photronic cell vs. spectrophotometer for translucency measurements on hotel chinaware body, photo and description, (4) 118–19.
plastometer, Bingham-Green, (1) 16.
plungers, hemispherical-end and flat-end types, Vicat consistency results, (15) 462.
pressure-temperature, for weight-loss tests on enamel surfaces, (6) 166.

Apparatus (*continued*)
Preston hydrostatic pressure machine for strength test on bottles, (15) 434.
Q meter for dielectric loss determination, (15) 440.
reflectometer, Hunter multipurpose, for opacity and gloss tests, (2) 49.
Soxhlet extractor, modified, for porcelain-enamel coatings, (6) 166.
spectrophotometer, Coleman direct-reading, for translucency measurements on hotel chinaware body, (4) 118–19.
spectrophotometer, General Electric automatic recording photoelectric, for spectral transmission measurements, (4) 104, (13) 374, (14) 395.
for thermal conductivity measurements on refractories, photos and diagrams (15), 451–53; power supply and heating unit circuit, water-circulating system, and calorimeter and guard-ring construction, (15) 454; calorimeter, multiple couple assemblies, and drilling jig, specimens, (15) 455; for lateral flow loss, diagram, (15) 456.
Toepler pump, circuit for operation, photo, (3) 71.
vacuum: for gas analyses in glass, photos and use, (3) 69–76; for analysis of blisters in flint glass, (3) 77–78.
Vicat needle, modified, for refractory mortar consistency tests, (15) 460–61.
viscometer, Hommel type, (15) 459–60.
volumeters, Goodner, Wheeler, McMahon, Kuechler, and Spiers types, review, (10) 275.
volumeters, kerosene-overflow type for volume measurements of plastic bars, (12) 329; mercury type, for dried and heated bars, (12) 329.
volumeters, mercury balance, photo and diagram of submersion arm, (10) 276.
volumeters, Westman mercury balance, description and formula, (10) 275.
Arsem furnace for electric load test, modification, (10) 113.
Arsenic and manganese in soda-lime-silica glass, effect on fading, data and curves, (4) 106–107.
Autoclave tests, crazing tests over water and steam pressure and thermal expansion effect, method and tables, (14) 414–15.
for glass, chemical durability, variable factors in, (5) 143; rinsing process vs. volume of water in bottle, (5) 146–47; volume of water vs. time and temperature of heating, test, and cooling periods, (5) 147–49.

Baddeleyite, ZrO_2, history and use, (5) 130.
Ball clays. See *Clays*.
Ball deformation test, Mellor cited, (1) 16.
Barium carbonate as flux in steatite bodies, dielectric properties, composition and data on specific resistance and ratio of reactance to resistance or susceptance to conductance, tables and curves, (15) 442.
for treating casting slips, effect on yield value and water content, (12) 342–43.
Barium hydroxide for ball-clay treatment, effect on physical properties, (12) 335.
Barium molybdate, properties and behavior in enamels, (6) 162.
Barium oxide in glass. See *Glass, barium oxide*.
Base exchange, exchangeable bases in ball clays, effect on properties, (12) 327.
exchange capacity of kaolinite fractions linear relation with surface area, (12) 344.
process and dewatering of casting slips, (12) 336; effect on stress-strain values, (12) 340–41; mechanical dewatering effect, (12) 342.
slip-casting phenomenon, (12) 336.
treatment for electrodialyzed ball clays, process, (12) 327–28.
Batch mixers for glass, types, (2) 56; effect of fineness, time, and r.p.m., on degree of mixing, (2) 57–58.
Beryllia in glass, glassforming nature, (4) 97; role of, properties, (4) 99.
Bibliographies and footnote references (listed according to subject and title of *Journal* papers); see also Footnote Citations Index, pp. 479–86, this issue).
blast furnaces, refractories service conditions, review, tests, 75 ref., (11) 311–30.
boroaluminate, electric furnace, 5 ref., (14) 391.
catalytic mullitization of kaolinite by metallic oxide, 34 ref., (1) 1–10.
ceramic materials, chemical composition and dielectric properties, relation to low dielectric losses, 12 ref., (14) 439–41.
chinaware and bodies, properties vs. thermal history: of vitreous bodies, 16 ref., (2) 38–40; of semivitreous ware, 1 ref., (2) 46.
chinaware, hotel, nepheline syenite in, 7 ref., (3) 90–92.
chinaware, properties, effect of spodumene and feldspar mixtures as fluxes, 3 ref., (11) 321.
clays, ball, effect of exchangeable bases on properties, 7 ref., (12) 327–35.
casting as base-exchange phenomenon, 21 ref., (12) 326–41.
clay masses, plastic, stress-strain characteristics, 12 ref., (1) 16–28.
drying behavior, testing and improving, 4 ref., (14) 422.
firing of, expansion, contraction, and strength changes, 2 ref., (12) 351.
plasticity, 9 ref., (9) 223–37.
properties, effect of steam and hot water with soda ash and wetting agent, 3 ref., (12) 346–49.
surface area, effect on exchange capacity of kaolinite, 8 ref., (12) 344–45.
unfired and fired, heat-of-wetting values, 13 ref., (4) 109–10.
decoration, decalcomania, firing recommendations, 7 ref., (14) 419–20.
dinnerware, semivitreous, glaze and decalcomania decoration, effect of sulfur and reducing gases, 11 ref., (14) 417–20.
earthenware, porous, effect of flint particle size on permanent moisture and thermal expansion, 8 ref., (14) 413–15.
enamels, adherence, with soluble and insoluble molybdates, 1 ref., (6) 160.
defects: fired on cast iron above 725°C., I, (7) 175–80; scratch blisters, II, (7) 180–90; surface oxidation vs. defects in coatings on steel, III, (7) 191–94; chips, fish scales, and shiners, IV, (7) 194–205; hydrogen as cause, V, (7) 205–15; 35 inclusive ref., (7) 215.
glass, iron oxide in, as dissolved from metal base, 4 ref., (9) 217–19.
porcelain, as protective coating for hot-water tanks, 7 ref., (6) 164–67.
porcelain, tensile strength, effect of iron oxide, 7 ref., (1) 29.
slip, effect of set on hydrometer readings, 1 ref., (2) 51.
thermal-shock resistance, 12 ref., (14) 463–64.
equilibrium studies in system FeO–Al_2O_3–SiO_2, 14 ref., (6) 151–55.
feldspar, mineralogical composition, calculation by chemical analysis, 8 ref., (14) 420–21.
furnace, electric load-test, design and operation, 10 ref., (4) 112–13.
furnace, transverse-test, 1 ref., (13) 389.
glass, accelerated autoclave durability tests, 4 ref., (5) 144–48.
bottles decrepitude of old types, aging, weathering, and solarization vs. use and abuse, 6 ref., (2) 54–55.
bottles, strength, effect of limitations of manufacturing processes, 4 ref., (14) 427–33.
bottling line, correlation with pressure-breakage test, 4 ref., (14) 434–37.
color, effect of light, 15 ref., (4) 104–108.
commercial containers, weathering, effect of storage containers, 6 ref., (13) 359–63.
gases dissolved in, analysis, and gases in seeds, 23 ref., (3) 69–83.
glass bars, vibration decay, 4 ref., (14) 408–11.
iron oxide in, effect on melting, 13 ref., (12) 355.
molds, cast iron for, 1 ref., (13) 382.
oxidation-reduction equilibria, between iron and selenium in furnace atmospheres, 13 ref., (13) 371–80.
potassium borate, X-ray diffraction and physical properties, 11 ref., (3) 83–89.
red silver, 5 ref., (10) 278–79.
selenium black, 1 ref., (5) 128–29.
selenium ruby, 1 ref., (5) 127.
silicon in, partial formation theory, 13 ref., (4) 101–103.
soda-dolomite lime-silica, effect of BaO and ZnO and properties, 8 ref., (3) 62–63; effect of iron oxide, 1 ref., (14) 401.
sodium borate, structure as affected by temperature, 7 ref., (14) 395–99.
surface tension, effect on cords, 5 ref., (6) 168–72.
glaze and body interface, 13 ref., (1) 11.
kilns, car-tunnel, commercial firing survey, 3 ref., (9) 239–40.
mullite catalysis, (1) 1.
oxides, glassforming nature, Ta_2O_5, TiO_2, and BeO, 24 ref., (4) 97–100.
plasticity of clays, 9 ref., (9) 223–27.
rare earths, 27 ref., (5) 141–43.
refractories service conditions in blast furnace, 75 ref., (11) 318–20.
refractories, thermal conductivity, apparatus for measuring, 11 ref., (14) 451–58.
refractory materials, slag-test literature survey, 166 ref., (11) 290–94.
steatite, constitution, 12 ref., (14) 443–44.
system CaO–FeO–Al_2O_3–SiO_2, results of quenching experiments on five joins, I, 60 ref., (10) 241–74.
system FeO–Al_2O_3–SiO_2, equilibrium studies, 14 ref., (6) 151–55.
system MgO–SiO_2, electric furnace study, 12 ref., (11) 294–310.
system zirconia–spinel, 7 ref., (3) 93.
vitreous bodies, low-temperature, 7 ref., (9) 231–32.
volumeter, improved mercury balance, 6 ref., (10) 275–77.
whiteware, translucency, use of photronic cell and spectrophotometer, 3 ref., (4) 116–17.
zirconium and thorium oxides in ceramics, 109 ref., (5) 138–41.
Bingham-Green plastometer, use, (1) 16.
Bismuth molybdate in enamels, properties and behavior, (6) 162.
Bisque molds. See *Molds*.
Bisque ware. See *Dinnerware*.
Black glass. See *Glass, colored, selenium black*.
Blast-furnaces, refractories service conditions, review, tests, and bibliography, 75 references, (11) 311–30.
Blisters. See also *Enamels, defects; Glass, defects*.
carbon dioxide in, vacuum apparatus for analysis, (3) 77.
in glostware, effect of reducing gases, (4) 416.
Boric oxide–alumina, properties, cone fusion and pouring temperature, curves, (14) 393–94.
and silica as glassforming oxide, analogy between comparable binary systems, (14) 393.
Boroaluminate ($2B_2O_3 \cdot 9Al_2O_3$), crystalline compounds, electric furnace fusion, physical properties, (14) 391.
crystallographic and optical properties, petrographic and X-ray diffraction studies, (14) 391–93; B_2O_3 and SiO_2 as glassforming oxides, resemblance, (14) 393; system Al_2O_3–B_2O_3, pouring point and cone fusion curves, (14) 393–94; refractory properties vs. fusion cast mullite, (14) 394.
and jeremjevite ($BAlO_3$), relation, (14) 393; specimens in U. S., (14) 394; conversion to artificial boroaluminate, (14) 394.
and mullite, resemblance, (14) 393.
Boron oxide, B–O distances, estimated O atoms around B atoms, (3) 85.
and sodium oxide for sodium borate glass, chemical composition, light transmission, and temperature, relation, (14) 395–401.
Bottle machines, Owens suction, Hartford-Empire, I. S., and Lynch types, production-rate curves, (15) 431–32.
Bottles. See *Glass*.
Brick, water-saturated, drying behavior in contact with wet clay cylinders, (14) 422–24.
Brock creep-test apparatus for speed-effect tests on special electrical porcelain ware, (1) 25.
Bubbles in enamels. See *Enamels, defects*.
Bureau of Mines Electrotechnical Laboratory, load-test furnace, design and operation, (4) 112.

Cadmium, determination method, (5) 127.
Cadmium molybdate in enamels, properties and behavior, (6) 162.
Calcium chloride for bisque-mold treatment, effect on casting slips, yield value vs. water content, (12) 341.
Calcium hydroxide for ball-clay treatment, effect on physical properties, (12) 329, (12) 335.
Calcium molybdate, properties and behavior in enamels, (6) 161.
Calcium oxide–Al_2O_3–SiO_2, Rankin and

Calcium oxide (*continued*)
Wright equilibrium diagram modified and revised, (10) 242.
–FeO–Al_2O_3–SiO_2, quenching experiments on five joins, (10) 241; diagram, positions of five joins in regular tetrahedron, (10) 248.
Calcium silicate ($CaSiO_3$)–anorthite–FeO, compositions, primary phases, and liquidus temperatures, equilibrium diagram and table, (10) 256–59; for $CaSiO_3$–gehlenite–FeO, (10) 263–65.
Calorimeters, Globar-heated water-flow, for insulating firebrick tests vs. guarded hot plate tester, (15) 458; speed of test runs, Globar vs. Weinland testers, agreement of duplicate tester, reproducibility in laboratories, (15) 458–59.
Camera for decay patterns of vibrating glass bars, process and photo, (14) 411–12.
Carbon-element furnace for load tests on refractory brick, advantages, (4) 112.
Carbon oxide gases, effect on cast-iron enamels, (7) 177.
Casting, dewatering mechanism in clay–water system, (12) 336 37.
Casting slips, clays for, plasticity, yield points, and shrinkage, review and theories, (12) 337–39.
deflocculated, and plaster of Paris molds, effect on slip properties, (12) 344.
dewatering: and exchange process, (12) 336–44; effect on stress-strain values, (12) 340–41; mechanical dewatering of slip, (12) 342.
in gypsum and bisque $BaCO_3$-treated molds, yield value vs. water content, curves, (12) 341–43; in $CaCl_2$- and $AlCl_3$-treated bisque molds, reactions and effect, (12) 342; in $CaSO_4$ porous molds, effect, (12) 342.
in plaster, porous bisque, and $CaCl_2$- and $AlCl_3$-treated porous bisque molds, base-exchange determination, (12) 336.
torsion and stress-strain diagrams, (12) 340.
viscosity (apparent), yield point, and water content, relation, (12) 339.
Cast iron. See *Metals for enamels; Molds for glassforming.*
Catalysis, catalytic mullitization of kaolinite by metallic oxides, (1) 1.
mullite, literature review, (1) 1.
Cathodic electrolysis vs. acid pickling, effect on hydrogen absorption, (7) 207–208.
Cements, refractory, ZrO_3 and ThO_3 in, uses, review, (5) 134–35; see also *Mortars, refractory.*
Cerium molybdate in enamels, properties and behavior, (6) 162.
Cerium oxide for bleaching cobalt ground coats and as antimony substitute, (5) 143.
as glass decolorizer and ultraviolet absorber, (5) 141.
in glass as oxidizing agent and other ceramic uses, study and references, (5) 143.
as refractory material, (5) 143.
Chemical constitution of steatite ceramics: talc-kaolin mixtures, low-dielectric loss type, chemical composition and dielectric properties, relation, (15) 439; chemical analyses, compositions, and firing schedule, specific resistance and ratio of reactance to resistance or susceptance to conductance in systems MgO–Al_2O_3–SiO_2, RO–Al_2O_3–SiO_2, and MgO–CaO–Al_2O_3–SiO_2, tables and curves, (15) 440–43.
Chemical durability of glass. See *Glass, chemical durability.*
Chill cast iron. See *Molds for glassforming.*
Chinaware. See also *Dinnerware; Earthenware; Whiteware.*
fluxes, spodumene-feldspar mixes as feldspar substitute, (11) 321–26.
hotel. See also *Chinaware, vitreous, hotel.*
hotel, ink-stain resistance, test results, (3) 71.
hotel, lepidolite vs. feldspar: composition and absorption data, (4) 117; intensity of transmitted light, (4) 119; translucency of specimens, (4) 120; effect of mixtures on translucency, absorption vs. translucency, tabular data and curves, (4) 121.
hotel, nepheline syenite vs. potash feldspar in: chemical composition of fluxes, (3) 90; dry and plastic properties of test bodies, (3) 91; absorption, modulus of rupture, and thermal expansion curves, (3) 91–92.
semivitreous, deck and bung position: effect on bisque rim warpage, plate size, and bisque absorption, curves and tables, (2) 43–44.
firing data on specific car decks, effect on properties, (2) 42–43.
moisture expansion curves, (2) 45; glaze stress vs. crazing, tables, (2) 45.
spodumene-feldspar mixes as feldspar substitute: compositions, (11) 322–23; porosity, and volume shrinkage, table, (11) 323; porosity diagrams, (11) 324–25; advantages, (11) 326.
thermal expansion vs. glost thermal history, curves, (2) 44; thermal-expansion data, (2) 44.
thermal history: bisque vs. crazing resistance, (2) 41–45; glost thermal history vs. properties, (2) 46.
vitreous, cone deformation, tables, (2) 34–35.
firing data on muffle kilns and multiburner direct-fire, cone deformation and effect on physical properties, (2) 34–36; comparative data on kilns, (2) 36.
glassy phase, effect on thermal expansion vs. thermal history, (2) 38–39.
glazes for, ring test data and glaze stress data in muffle kiln, vs. multiburner kiln, (2) 39–40.
hotel body, composition and absorption, tabular data, (4) 117; intensity of transmitted light through specimens, (4) 119; light transmittance curves, (4) 122.
hotel body, spodumene-feldspar (soda and potash) mixes as feldspar substitute: chemical analyses and compositions, (11) 322–23; warpage factor, diagram of slump ring method, (11) 322; P.C.E. value and softening temperatures, (11) 322; porosity and shrinkage measurements, table and diagrams, (11) 323–25; strength, warpage, and impact resistance, table and diagram, (11) 324–25; advantages, (11) 326.
hotel body, translucency measurements, use of photronic cell and spectrophotometer, (4) 116–22.
microstructure vs. thermal history, effect of repeated firings, photomicrographs, (2) 37–38.
thermal history vs. properties, (2) 33; vs. thermal expansion, effect of repeated firings, (2) 38; glaze condition, ring test data, (2) 39.
warpage factor and slump ring for measurement, diagram, (11) 322.
Clays. See also *Kaolin; Shales.*
American, volume measurements by improved mercury balance volumeter, (10) 275.
analyses: casting as base-exchange phenomenon, (12) 336–44; effect of surface area on exchange capacity of kaolinite, (12) 344–46.
ball, base-exchange treatment: properties, (12) 327; electrodialysis treatment, process and results, (12) 328–36.
chemical composition, and miscellaneous chemical properties, (12) 328–29.
flow sheet for base-exchange tests on properties, (12) 328.
physical properties, tables, (12) 330.
potassium hydroxide treatment, effect, (12), 329, (12) 335.
sodium hydroxide, effect on plasticity and strength, (12) 328.
transverse strength of original, leached, and saturated samples, tables and curves, (12) 330, (12) 332–33, (12) 335.
treated and untreated, volume shrinkage, table and curves, (12) 330–35; heated to 1300°C., curves, (12) 334.
untreated: vs. H_2O_2-treated samples, base-exchange capacity, (12) 328; leached, saturated samples, apparent porosity, tables, (12) 330, (12) 332, (12) 335; heated at varying temperatures, curves, (12) 336.
volume determination, kerosene overflow and mercury volumeters for tests, (12) 329.
casting slip, effect of deflocculents on cation exchange, (12) 338.
clay-flint-feldspar bodies for porous earthenware, effect of flint particle size on permanent moisture and thermal expansion, (14) 413.
and clay-flint mixtures, stress-strain data, (1) 21–22.
Clays (*continued*)
clay fractions: particle size, specific surface, and exchange capacity, table, (12) 345; electrodialyzed monodisperse, with NaOH additions, viscosity relations, (12) 345.
clay minerals, fired and unfired, heat-of-wetting values, (4) 108–12.
compression tests, apparatus, and use, photo and diagram, (1) 17–19.
cracks, drying: storage of clay cylinders in contact with wet brick, method and effect, (14) 423; water content of clay cylinders vs. water of plasticity and effect of chemical additions, (14) 424.
drying behavior, tests and improvements, rate of water flow vs. evaporation, (14) 422.
drying rate, effect of ferric chloride, hydrochloric acid, and wetting agents, (14) 424.
exchange capacity, effect of surface area, (12) 344.
expansion, contraction, and strength changes during firing, test apparatus, curves, (12) 351–54.
fire clay, mullite and tridymite as equilibrium products, (6) 159.
fire clay and shales, fired, expansion, contraction, and strength changes during firing, test apparatus, curves, (12) 351–54.
fired, hot transverse strength test, formula apparatus, curves, (12) 352–54.
Florida, particle distribution of closely monodisperse systems, curves, (12) 345.
flow-point pressure and moisture content, Stull and Johnson method, (1) 17.
hydration and rehydration, literature review, (4) 109.
ionic exchange, effect on casting slips, (12) 336.
linear relation of surface area and base-exchange capacity, (12) 344.
Missouri burley and Florida kaolin, analyses and studies in system FeO–Al_2O_3–SiO_2, (6) 153.
montmorillonite, illite, and kaolinite, fired and unfired, heat-of-wetting values, studies, tables, curves, (14) 108–12.
plasticity, Mellor and Bleininger methods and Bingham-Green plastometer for, (1) 16.
properties, effect of steam and hot water with soda ash and wetting agent, tables and curves, (12) 346–51.
pugging treatments, effect of soda ash and wetting agents, (12) 347.
rehydration, Purdy and Moore studies, (4) 109.
and shales, Read mixer for, (12) 347.
shrinkage, improved mercury balance volumeter for tests, (10) 275.
specific surface, formula, (12) 346.
torsion stress, Wilson, Norton, and Graham and Sullivan studies, (1) 17.
treatment, base-exchange effect, (12) 328.
Clayware, brick, drying behavior, storage of clay cylinders in contact with water-saturated brick, test method, changes in weight of cylinders, effect of chemical additions, (14) 422–24.
clay treatments to improve physical properties, (12) 346.
cracks, drying behavior, rate of water flow vs. surface evaporation, effect of chemical additions, (14) 422.
moisture attack, heat-of-wetting values and tests, (4) 108.
plastic clay masses, stress-strain characteristics and tests, (1) 16.
plasticity, yield points, and shrinkage, review and theoretical considerations, (12) 337–39; relative properties of clay forms, (12) 338.
slip-casting molds, mechanical water removal vs. ionic exchange reaction of slip and mold, (12) 336.
Clinoenstatite as stable crystal modification of magnesium metasilicate, (15) 447.
Coal ash and refractory material, A.S.T.M. fusion tests, and preparation of cones of nonplastic material, (10) 282.
Colors. See *Decoration; Glass, colored.*
Cone fusion tests for refractories slag attack, (11) 286; cone-fusion penetration test of Schauer, (11) 286.
Consistency of refractory mortars, wet, air-setting types, modified needle Vicat apparatus for tests, description, data, and results, (15) 459–63.
vs. workability, differentiation, (15) 459.
Constitution. See *Chemical constitution.*

Copper ruby glass. See *Glass, colored, copper ruby.*
Cords in glass. See *Glass, defects, cords.*
Corundum as primary crystal phase in system Al_2O_3–SiO_2–FeO, (6) 157.
Cracks in cast-iron glassforming mc[illegible] annealing vs. spheroidizing heat-treatment of, (13) 381–88.
Crazing of glazes, autoclave test, results and glaze formula, effect of flint particle size, (14) 414–15.
of semivitreous bodies, crazing factors, autoclave test and thermal quenching, moisture expansion, and glaze compression data, (2) 45.
of semivitreous ware vs. bisque thermal history, moisture expansion curves, and glaze stress vs. crazing, tables, (2) 45.
Creep test for speed-effect tests on special electrical porcelain types, Brock apparatus, (1) 25.
Crucibles, thorium oxide in, review, (5) 138.
Cristobalite or tridymite, separation of, as primary crystal phase in system FeO–Al_2O_3–SiO_2, (6) 156.
Crystal analysis of boroaluminate, (14) 391.
Crystalline solid phases in system CaO–FeO–Al_2O_3–SiO_2, (10) 263–65; crystallization theory, (10) 272–73.
Crystal phases in system FeO–Al_2O_3–SiO_2, (6) 156–57.
Cyclic-load tests on plastic clay masses, (1) 25; for vitreous electrical porcelain bodies, (1) 25.

Decalcomania decoration and semivitreous dinnerware glazes, effect of sulfur and reducing gases, (14) 416; glaze and decoration defects, characteristics, causes, and tests, (14) 418–20.
Decarburization vs. hydrogen absorption during firing, sheet-iron enamel tests, (7) 178.
Decay vibration of glass bars. See *Glass, vibration.*
Decolorizers in glass. See *Glass, decolorizers.*
Decomposition of kaolinite, equations, (1) 1, (1) 2.
Decoration, colored, for dinnerware, effect of kiln gases, natural vs. manufactured gas, (14) 418–19.
decalcomania, defects in muffle-kiln firing, effect of kiln gases, (14) 419; effect of sulfur dioxide, firing recommendations, bibliography, (14) 419–20.
De-enameling of steel by hydrogen absorption, photomicrograph, (7) 182; see also *Metals for enamels.*
Definitions, "cordy" glass, (6) 168.
deformation temperature, (14) 405.
dielectrics, Q as ratio of reactance to resistance or susceptance to conductance, (15) 440.
fish scales, (7) 212.
plasticity, (1) 16.
porcelain vs. steatite bodies, differentiation, (15) 439.
"scale," (7) 188.
steatite bodies vs. porcelain bodies, (15) 439.
workability, Bancroft, (1) 16.
Dehydration of clays, review, (4) 109.
Dehydrogenized cast iron. See *Metals for enamels.*
Dewatering process in clay-water systems, effect of water removal by porous mold on casting slip, (12) 336–44.
Dielectric properties of steatite ceramics (kaolin-talc mixtures), chemical composition and properties, relation, (15) 439; chemical analyses, compositions, and firing schedule, specific resistance and ratio of reactance to resistance or susceptance to conductance in bodies of system MgO–Al_2O_3–SiO_2, RO–Al_2O_3–SiO_2, and MgO–BaO–Al_2O_3–SiO_2, tables and curves, (15) 440–43.
of talc-kaolin mixtures, effect of variations in talc-kaolin ratio, alkaline earth oxides, and temperature, (15) 443.
Dinnerware. See also *Chinaware; Whiteware.*
bisque ware, open-fire tunnel kiln for, effect of sulfur gases, analyses, (14) 417.
glostware, semivitreous: properties vs. glost thermal history, (2) 46; scratch resistance vs. temperature, curves, (2) 46–47.
semivitreous, glazed, and decalcomania decoration, firing of, effect of sulfur and reducing gases, (14) 416; glaze and decorating defects, characteristics, causes, and tests, (14) 418–19; firing recommendations, (14) 419–420.
Disannealing of glass. See *Annealing.*
Discoloration of glass. See *Glass, fading.*
Dolomite-lime glass. See *Glass, soda-dolomite lime-silica.*
Drying of clays for brick, rate of water flow vs. surface evaporation, (14) 422.
cracks in clays, test method, storage of clay cylinders with wet brick, method and effect, (14) 423; water content of cylinders vs. water of plasticity, (14) 424; effect of chemical additions, ferric chloride, hydrochloric acid, and wetting agents, (14) 424.
Durability of glass. See *Glass, chemical durability.*

Earthenware, porous, flint particle size, effect on permanent moisture and thermal expansion, (14) 413; talc-pyrophyllite and clay-flint-feldspar bodies, chemical composition and flint particle size, (14) 414; particle-size distribution, moisture and thermal expansion, and crazing, methods, test results, and curves, (14) 414–16.
Electrical porcelain. See *Porcelain, electrical.*
Electric load-test furnace. See *Furnaces, load-test.*
Electrocast forsterite for refractory brick, load-test data, (4) 115.
Electrodialysis for base-exchange tests on ball clays, process, results, tables, and curves, (12) 329–36.
of clay fractions, viscosity of, with NaOH additions, exchange-capacity determinations, (12) 344–46.
Electrolytes in casting slip, effect on dewatering mechanism, (12) 341.
Electrotechnical Laboratory, Bureau of Mines, load-test furnace, design and operation, (4) 112.
Elements, oxides of, as glassformers, (4) 100.
Enamels, abrasion resistance vs. firing treatment, tables, (2) 49; dye-stain method of measurement, value, (2) 50.
acid-resistance tests, American Ceramic Society Standard and Porcelain Enamel Institute tests, (2) 49.
acid-resistant vs. nonresistant, weight-loss data, (6) 166.
acid-resistant and normal, firing treatments, effect on reflectance and surface-abrasion resistance, (2) 48–49.
acid-resistant, "rod" test, (15) 465.
addition agents to reduce set and setup agents to increase set, studies, (2) 51.
antimony-bearing dry-process, firing treatment vs. physical properties, (2) 48–50.
cast iron for. See *Metals for enamels.*
clear, adherence, effect of various compounds as mill additions, (6) 161; molybdates for ground coats and color bases, empirical formulas and smelter and mill batches, (6) 162.
coatings for ground and cover coats, application weight, effect on thermal-shock resistance, (15) 463–65.
coatings, surface preoxidation as ground-coat substitute, advantages, photomicrograph, (7) 191–92.
cover-coat, white, surface oxidation and preoxidation, photomicrograph, (7) 192.
defects. See also *Metals for enamels.*
black specking on sheet-steel white cover coats, (7) 176.
blisters and opacification bubbles, photomicrograph and description, (7) 183–84.
blisters, oxide coatings vs. general blistering phenomena: effect of iron-moisture reaction, substitution of preoxidized ground-coat surfaces, (7) 191–92; hydrogen absorption during enamel firing, (7) 193; primary boiling, cause, (7) 194.
blisters: pickling acid contamination, used acid as cause of increased hydrogen absorption, (7) 205; surface impurities, effect, (7) 205–206.
blisters and pinholes, hydrogen in cast iron as cause, (7) 175–80.
blisters, "promoters in pickling" and cathodic electrolysis, effect of oxide films, impurities, and inhibitors, (7) 207–208.
blisters, scratch-type, effect of hydrogen, and other causes, (7) 180–90; see also *Enamels, defects, scratch blisters.*
boiling, primary, cause, (7) 194; see also *Enamels, defects, reboiling.*
bubble structure, thermal-shock resistance tests, (15) 465.
chips, fish scales, and shiners, artificial fish scales and chips, description and occurrence, (7) 195; progression of
Enamels, defects, chips (*continued*)
hydrogen-caused fractures, (7) 198; control and prevention, (7) 200–203.
fish scales defined, and hydrogen effect on rimming-steel stock, (7) 212.
fish scales vs. reboiling, (7) 198–99.
fractures: progression of chips → fish scales → shiners, effect of hydrogen, (7) 195–98; control and prevention, (7) 200–202.
hydrogen theory proposed, Kautz and Zapffe and Yarne discussions, (7) 203–204.
pickling acid contamination, (7) 205; see also *Metals for enamels, pickling.*
reboiling, analogy, (7) 213.
reboiling, "cluster blisters," (7) 213.
reboiling vs. fish scaling, studies, (7) 198–99.
reboiling, rimming-steel stock behavior, effect on edges and center sections, (7) 212.
"scale," definition, (7) 188.
scratch blisters, hydrogen behavior and effect: at scratched steel surface during pickling, galvanic plating (nickel dip) and enamel firing, (7) 181–83; mechanical impurities, geometrical effect, and chemical deposition of salts, (7) 184; hydrogen effect, (7) 185; surface oxidation vs. hydrogen absorption during pickling, (7) 186–87; hydrogen effect and other causes, (7) 180–90.
scratch blisters, nickel-dip effect: vs. hydrogen effusion during firing, (7) 182–83; ferrous salts deposition, hydrogen in nickel and preferential plating, and reactions during firing, (7) 188–89, (7) 209–11; photomicrographs, (7) 211.
scratch blisters, physical effect of scale on sheet steel, electrochemical action between scale and iron, and production and control of blisters, (7) 186–87.
scratch blisters over scratch and stamp marks, (7) 184–85.
dry-process, firing treatment, effect on physical properties, (2) 48.
fish scales. See *Enamels, defects.*
frit extraction for solubility test, (6) 166–67.
frits, resistance of, weight-loss vs. water extraction, (6) 166–67.
frits, zirconium oxide in, stability and solubility, (5) 136–37.
gloss, residual, relation of firing treatment to surface-abrasion resistance, (2) 49.
ground-coat vs. preoxidized surface, advantages, (7) 191.
hydrogen effect, bibliography, 35 references, (7) 215; see also *Enamels, defects; Metals for enamels.*
hydrometer readings on enamel slip, specific gravity vs. flow data, (2) 51.
kitchenware, thermal-shock resistance tests, (15) 463–66.
opacifiers, cerium oxide, review, (5) 142–43.
opacity, acid resistance, and surface-abrasion resistance, relation to firing treatment, tables, (2) 48.
pick-up rate vs. hydrometer readings, (2) 51–52.
"plate" method for thermal expansion tests on ground- and nonacid-resistant cover coats, (15) 465; "rod" method for acid-resistant cover coats, (15) 465.
porcelain, Amsler tensile testing machine for strength tests on enamel fibers, (1) 30.
porcelain frits, solubility tests, (6) 166.
porcelain, tensile strength, effect of iron oxide, (1) 29.
porcelain, vs. zinc as protective coatings for hot-water tanks, (6) 164.
reboiling. See *Enamels, defects.*
"scale," definition, (7) 188.
scratch blisters. See *Enamels, defects.*
set, effect on hydrometer readings of slip, (2) 51.
setup salts, effect on solubility, (6) 166.
sheet steel for. See *Metals for enamels.*
slips, dried, effect of water content, (7) 200.
slips: hydrometer readings, effect of "set," (2) 51; mobility and pickup process, (2) 52; specific gravity data, effect of various addition agents, (2) 51–52.
solubility, effect of setup salts, (6) 166.
thermal-shock resistance tests, (15) 463; method, (15) 464; thermal-expansion measurements and method, tables, (15) 464–65; thermal-shock failure, effect of coating thickness, curve, (15) 465; bubble structure and cover-coat expansion, photomicrographs, (15) 465–66;

Enamels, thermal-shock (*continued*)
ground- and cover-coat expansion, (15) 466.
weight-loss tests, modified Soxhlet extractor, acid-resistant vs. nonacid-resistant enamels, effect of setup salts, pressure-temperature apparatus, (6) 166.
wet-process, carbon oxide gases in metal, blistering effect, (7) 177, (7) 179.
white, in ground coats, color bases, and single-coat, single-fire application, effect of molybdates, empirical formulas, smelter and mill batches, (6) 162–63.
Equilibrium diagrams, anorthite–Al_2O_3–FeO join, compositions, primary phases and liquidus temperatures, (10) 254.
calcium oxide–Al_2O_3–SiO_2 of Rankin and Wright, modified and revised, (10) 243.
calcium oxide–FeO–Al_2O_3–SiO_2, positions of five joins within regular tetrahedron, (10) 248.
calcium oxide–FeO–SiO_2, without isotherms, fields of stability of crystalline phases in contact with liquid, (10) 242.
calcium silicate ($CaSiO_3$)–anorthite–FeO join, compositions, primary phases, and liquidus temperatures (10) 256.
calcium silicate ($CaSiO_3$)–gehlenite–FeO join, compositions, primary phases, and liquidus temperatures, (10) 263.
ferrous oxide–Al_2O_3–SiO_2, without isotherms, fields of stability of crystalline phases in contact with liquid, (10) 245.
ferrous oxide–Al_2O_3–SiO_2 system (6) 155, (10) 244; isotherm curves, (6) 155; refractive indices, (6) 158.
gehlenite–anorthite–FeO join, compositions, primary phases, and liquidus temperatures, (10) 260.
silica–anorthite–FeO join, compositions, primary phases, and liquidus temperature, (10) 252; method of plotting experimental data, (10) 249.
spodumene and potash and soda feldspar mixtures, melting diagram, (11) 322.
zirconium dioxide–MgO, melting diagram of Ebert and Cohn, (5) 132.
Equilibrium studies, calcium oxide–FeO–Al_2O_3–SiO_2, joins in quaternary system, (10) 248; diagrams and tables, (10) 249–65.
equilibrium-stress data on plastic clay bodies, evaluation, (1) 26.
equilibrium temperature in test brick, time required, (13) 390.
ferrous oxide–Al_2O_3–SiO_2, melts, treatment, (6) 153; analytical data, crystal phase, and optical data, (6) 154–55; mullite and tridymite as equilibrium products from kaolin or fire clay, (6) 159; hercynite equilibrium, (6) 159.
on glass, oxidation-reduction in, between iron and selenium in atmospheres of air, N_2, and CO, (13) 371–81.
in magnesia–Al_2O_3–SiO_2 system, portion of phase diagram and chemical composition and dielectric properties, (15) 440–41.
magnesia–silica system, phase diagram, (11) 294.
in oxide system, magnesium metasilicate modifications, literature review, (15) 443–44.
in refractories vs. slag constituents, relation, references, (11) 290.
silica–Na_2O–ZrO_2 system, properties, (5) 137.
Exchange capacity of kaolinite, effect of surface area, (12) 344; see also *Base exchange.*
Expansion, moisture, in porous earthenware bodies, effect of flint particle size, (14) 413.
moisture, of semivitreous bodies, curves and tables, (2) 45.
thermal, in porous earthenware bodies, effect of flint particle size, (13) 413.
thermal: of vitreous chinaware vs. thermal history, curves, (2) 38–39; of semivitreous chinaware, curves and tables, (2) 44–45.
thermal, of zirconia and spinel, curves, (3) 94.

Fatigue test for cast-iron glassforming molds, endurance curve, (13) 382.
Fayalite, separation as primary crystal phase in system FeO–Al_2O_3–SiO_2, (6) 156.
Feldspars, alkaline earth oxides as substitute flux for steatite bodies, (15) 441–43.
commercial, chemical analysis, formulas and method, (14) 420–22.
-flint-clay bodies for porous earthenware, effect of flint particle size on permanent moisture and thermal moisture, (14) 413.

Feldspars (*continued*)
vs. lepidolite in hotel chinaware body, composition and absorption data, (4) 117; intensity of transmitted light, (4) 119; translucency of specimens, (4) 120; effect of mixtures on translucency and absorption vs. translucency, tables and curves, (4) 121.
mineralogical composition, chemical analysis and formulas for calculation, (14) 420–22.
soda and potash, spodumene as feldspar substitute in chinaware bodies: chemical analyses and compositions, table, (11) 321; warpage factor and slump ring method, (11) 322; P.C.E. values and softening temperatures, melting diagram and table, (11) 322; porosity of semivitreous dinnerware and vitreous hotel chinaware bodies, table, (11) 323; strength, warpage, and impact resistance, effect on vitreous china, (11) 324; porosity diagrams, (11) 324–25; advantages, (11) 326.
Ferric oxide and ferrous oxide in porcelain enamel, effect on tensile strength, (1) 29.
in glass, effect on melting rate, (12) 355–56; chemical effect, (12) 357.
in soda-dolomite lime-silica glass, effect of substitution, (14) 401; chemical composition and physical properties in 10 and 12% dolomite lime glass, tables and curves, (14) 402–408.
Ferrous iron and selenium in soda-lime and potash soda-lime glasses, melted in air, N_2, and CO atmospheres, (13) 371.
Ferrous oxide–Al_2O_3–anorthite, compositions, primary phases, and liquidus temperatures, equilibrium diagram and tables, (10) 254–55; for FeO–anorthite–SiO_2, (10) 250–52; for FeO–$CaSiO_3$–anorthite, (10) 256–59; for FeO–$CaSiO_3$–gehlenite, (10) 263–65; for FeO–gehlenite–anorthite (10) 260–62.
–Al_2O_3–SiO_2, equilibrium diagrams: from Snow, (10) 244; from Schairer, stability of crystalline phases with liquids, (10) 245.
–Al_2O_3–SiO_2, equilibrium studies, (6) 151; primary crystal phases, (6) 156; hercynite in, studies, and reaction with mullite (6) 159.
–CaO–Al_2O_3–SiO_2, diagram, positions of five joins in regular tetrahedron, (10) 248.
–CaO–Al_2O_3–SiO_2, quenching experiments on five joins, (10) 241–74.
–CaO–SiO_2, limiting system, equilibrium diagram, (10) 242.
Fiber methods for tensile strength tests on glass, various methods cited, (1) 29.
Firebrick refractories. See *Refractories, firebrick.*
Fire clays. See *Clays, fire clays.*
Firing of clays and shales, expansion, contraction, and strength changes in, test apparatus, curves, results, (12) 351–54.
of dinnerware, semivitreous, effect of sulfur and reducing gases, (14) 417–18.
of dry-process enamels, firing treatment vs. physical properties, (2) 48–49.
glost, of semivitreous ware: properties vs. glost thermal history, (2) 46; scratch resistance vs. temperature, curves, (2) 46–47.
of glostware: effect of sulfur and reducing gases, (14) 416; effect of kiln gases, (14) 418.
muffle, sulfur gases in, effect on decalcomania decoration, (14) 418–19; sulfur reduction, lime compounds for absorption, (14) 419.
reducing gases, natural vs. manufactured gas, analyses and effect, (14) 416–17.
of vitreous chinaware: in muffle and multi-burner direct-fire kilns, cone deformation and effect on physical properties, (2) 33–36; comparative data on kilns, (2) 36; microstructure vs. thermal history, photomicrographs, (2) 37–38; thermal expansion vs. thermal history, (2) 38; thermal history, effect on glazes, (2) 39.
Fish scaling of enamels. See *Enamels, defects.*
Flint-clay-feldspar bodies for porous earthenware, effect of flint-particle size on permanent moisture and thermal expansion, (14) 413.
-magnesia series in system MgO–SiO_2. See *Magnesia-flint series.*
Flint glass. See *Glass, flint.*
Flow of refractory mortars, consistency, Vicat modified apparatus, test results, adaptability, results with flat-end and hemispherical-end plunger, recommendations, (15) 459–63.
Flow sheet of clay treatment, effect of base exchange, (12) 328.
Fluxes in chinaware bodies, effect of spodumene and soda and potash feldspar mixes, (11) 321–26.
Forsterite, electrocast and pressed, for refractory brick, load-test data, (4) 115.
as magnesium metasilicate modification, Allen and associates and Bowen and Posnjak studies, (15) 443.
-periclase (magnesia-flint series), micrometric analyses, (11) 307.
Frits, enamel. See *Enamels, frits.*
Fruit jars. See *Glass.*
Furnaces. See also *Firing; Kilns.*
Ajax-Northrup electric induction, for glassmelting, diagram, (13) 373.
Arsem-type, for electric load-test model, (4) 113.
blast-, refractories service conditions, review, tests, and bibliography, 75 references, (11) 311–20.
carbon-element, for refractory brick load tests, advantages, (4) 112.
electric, for boroaluminate fusion, (14) 391.
electric for MgO–SiO_2 system, studies, (11) 294–310.
electric, transverse-test, for refractories, cross section and photo, (13) 389–90.
electric tube, for glost firing, laboratory test on sulfur content of burner gases, (14) 418.
for gas analyses in glass, photo, (3) 69–70.
gas, natural vs. manufactured, sulfur and reducing gases in, effect on glazes and dinnerware decoration (14) 416.
glassmelting, for spectral transmission measurements, method and diagram, (14) 395–96.
load-test, for refractory brick, design, diagrams and photos, operating data, advantages and disadvantages, (4) 112–16.
transverse-test, for breaking strength of refractories, cross section and photo, (13) 389–90.
Fused quartz, dielectric characteristics, properties, and use, (15) 439.
Fusion test cones, A.S.T.M. procedure for refractory material and coal ash, (10) 282; method for nonplastic materials, (10) 282.

Galvanic plating (nickel dip). See *Metals for enamels, nickel dip.*
Gases, blank, deduction method, (3) 75; spread of blanks, table, (3) 75.
carbon dioxide, in blisters, analysis, vacuum apparatus, (3) 77.
carbon dioxide, effect on cast-iron enamels, (7) 177.
condensable, separation process, (3) 74.
in glass, analyses, apparatus for tests, (3) 69–73; furnace assembly, (3) 70.
in glass, gas fractions, chemical analyses, average deviations, relative volumes dissolved, tables, (3) 75–76.
in glass, seeds and blisters, analyses, data, (3) 82.
in glass, synthetic mixtures, analyses, (3) 81.
kiln, SO_2 content, determination and precautions, (14) 417–18.
natural vs. manufactured, analyses, and calculated composition of combustion products, (14) 416–17.
noncondensable, analysis, (3) 72.
reducing, in glost firing, blistering effect, (14) 416.
in seeds: test apparatus, (3) 78; CO_2, N_2, SO_2, and air, analyses and volume contraction curves, (3) 78–80; absorption of SO_2 by KMnO solution, curve, (3) 80.
in sodium salts, decomposition by vacuum heating, (3) 70.
water vapor in, determination, (3) 74.
Gehlenite ($CaAl_2O_4$)–anorthite–FeO, compositions, primary phases, and liquidus temperatures, equilibrium diagram and table, (10) 260–62; for gehlenite–$CaSiO_3$–FeO, (10) 263–65.
Geology, observations on quaternary system CaO–FeO–Al_2O_3–SiO_2, (10) 273.
Glass, acid and distilled water resistance, effect of BaO and ZnO substitutions for Na_2O, CaO·MgO, and SiO_2, (3) 61; effect of Fe_2O_3 substitutions, (14) 401.
aging, solarization, and weathering, experimental results, aging in warehouse, (2) 53–54.

Glass (*continued*)
Alexandrite, neodymium in, (5) 142.
alkali extraction, accelerated autoclave durability test, variable factors, (5) 143.
alkali extraction for weathering test on commercial glass bottles in storage, tables, (13) 361–64.
amber: water vapor as gas constituent, (3) 69; blister and seeds in, deposit in, (3) 88–89.
ampoules, soft, gases in, analysis of synthetic mixtures, (3) 81.
annealing, disannealing of glass bars, effect on sonic properties, (14) 412.
apparatus for. See *Apparatus, glass.*
arsenic in, and varying iron oxide additions, effect on fading, (4) 106.
aviation and navigation types, neodymium in, effect, (5) 142.
autoclave chemical durability test, variable factors in, (5) 143.
barium oxide as substitute for Na_2O, CaO-MgO, and SiO_2, effect on physical properties, (3) 61; chemical analyses and properties, (3) 62.
batch mix, sampling and analysis, apparatus and laboratory methods, effect of fineness, speed, and mixing time, (2) 56–59.
beryllia in, glassforming nature and properties, (4) 97–99.
black. See *Glass, colored, selenium black.*
blisters. See *Glass, defects.*
boron oxide, space model, theoretical, (14) 400.
Boston rounds, strength limitations in manufacture, (15) 427–34.
bottles, aging, weathering, and solarization, experimental studies and results, (2) 53–54; solarized and weathered samples, average internal pressure, (2) 55.
alkali extraction, effect of internal area of container, (5) 147; test temperature vs. NaOH extracted per minute, and test temperature vs. time for extraction, curves, (5) 148–49.
alkali extraction at varying relative humidity, tables, (13) 361–64.
amber: gas content, analysis, (3) 76; deposit in blister, photo, (3) 82.
A.S.T.M. hydrostatic pressure and thermal shock tests on bottles, (15) 434–35.
breakage vs. use, ratio, (2) 55.
chemical durability. See *Glass, chemical durability.*
commercial, Coca Colas, Boston rounds, and steinie beers, strength limitations in manufacture, (15) 427–34.
and jars, thermal-shock tests vs. weathering and solarization, (2) 54.
metal salts effect, table, (5) 145.
pressure test breakage vs. bottling line, A.S.T.M. breakage test, (15) 434–35; test control, production rate vs. breakage on various sizes, and mathematical calculations and definitions, (15) 436–48.
production rates of Owens suction, Hartford-Empire I.S., and Lynch machines, curves, (15) 431–32.
strength. See *Glass, chemical durability.*
weathering effect of storage conditions: effect of humidity and temperature on internal and external surfaces of capped and uncapped bottles, (13) 359–71; alkali extraction test method, tables, and visual tests, (13) 361–64; photomicrograph, (13) 365–69.
weathering vs. mechanical abuse, (2) 55.
breakage, pressure test, vs. bottling line, (15) 434; see also *Glass, chemical durability.*
cerium in, as ultraviolet absorber, (5) 141.
chemical durability, acid and water effect, BaO and ZnO substitutions for Na_2O, CaO-MgO, and SiO_2, (3) 61; effect of Fe_2O_3 substitutions, (14) 401.
American Ceramic Society method, (3) 63.
of bottles: accelerated autoclave test, variable factors, (5) 143; preparation of distilled water, effect of CO_2, metal salts, and rinsing, (5) 144–47; effect of volume of water and variations in time and temperature of heating and cooling periods, (5) 147–49.
of bottles, old vs. new, (2) 55.
of commercial flint bottles, effect of storage, and photomicrographs, (13) 365–70.
Griffith fiber method for tensile strength tests, (1) 29.
Glass, chemical durability (*continued*)
pressure test breakage, correlation with bottling line production, (15) 434.
strength, average internal pressure of solarized and weathered bottles, and ratio of breakage to use, (2) 55.
strength of bottles: thickness limitations and effect, (15) 427–28; capacity vs. average thickness and internal pressure strength, tables, (15) 428; interlocking variables, production-rate curves, pressure strength, and use of data, (15) 431–34.
chlorine in red silver types, effect, (10) 278.
Coca Colas, strength limitations in manufacture, (15) 427–34.
coloration, color changes, spectrophotometer for measurements, (14) 395.
coloration: effect of light, ultraviolet rays, sunlight, and X-ray exposure, (4) 104–105; effect of radiation exposure, (4) 107.
coloration, Se and iron in, melted in air, N_2, and CO, effect, (13) 371.
colored, copper ruby, tin compounds in, effect on solubility, (10) 280.
gold ruby: tin compounds in, effect on solubility, (10) 280; solubility curves for low-melting borax and soda-lime glasses, (10) 281.
neodymium and praseodymium oxides in, effect, (5) 142.
pigments in, MgO, $BaSO_4$, and $Ca_3(PO_4)_2$, effect of tin, (10) 281.
purple, Nd_2O_3 in, (5) 142.
purplish-blue, Alexandrite, use of Nd_2O_3, (5) 142.
red silver, use of chlorine, lead, and other halides, effect, (10) 278–79.
selenium black, base glass compositions, oxide additions, transmission curves, and Se addition, (5) 128–29.
selenium black, nickel and iron oxides vs. CoO, effect, (5) 129.
selenium and iron additions, effect of melting in air, N_2, and CO atmospheres, (13) 371.
selenium pink, effect of neodymium, (5) 142.
selenium retention, reducing agents in, effect, (5) 125; composition variations, ZnO and K_2O and added Co and Ni compounds, effect, (5) 126–27.
selenium ruby, cadmium, selenium, and sulfur in, determination methods, (5) 127.
selenium ruby composition, (5) 123; crucibles and day tank for, (5) 124; color development and oxidizing and reducing conditions, (5) 124–25.
selenium ruby, melting schedule, effect of carbon on Se retention, curves, (5) 125.
selenium ruby, oxide composition, calculated, (5) 126.
silver, red color, use of chlorine, lead, and other halides, effect, (10) 278–79.
silver, yellow color, (10) 278.
tin in, effect on metallic colors, (10) 281.
yellow, cerium oxide and TiO_2 in, (5) 141.
yellow, effect of silver compounds and halides content, (10) 278–79.
color indicator, cobalt oxide for tests on sodium borate glass, (14) 395; General Electric automatic recording photoelectric spectrophotometer for measurements, (14) 385.
commercial bottles. See *Glass, bottles.*
constitution, K_2O–B_2O_3 glass, atomic structure, X-ray diffraction data, X-ray studies, and intensity and radial distribution curves, (3) 85.
containers. See *Glass, bottles.*
cooling, arrested, for color development, (5) 126–27.
copper ruby. See *Glass, colored, copper ruby.*
cords. See *Glass, defects.*
crystalline film deposit on bottles in storage, weathering tests, effect of humidity, (13) 359.
decolorizers, cerium and neodymium oxides, review, (5) 141.
decolorizers, effect of light, X-ray studies, (4) 104.
decolorizing action of selenium and iron, effect of oxidation-reduction equilibria, (13) 371–81.
defects, blisters, CO_2 in, vacuum apparatus for analysis, (3) 77.
blisters and seeds, gas analyses, tables, (3) 82; deposit in blister in amber glass, (3) 82.
Glass, defects (*continued*)
cords, definition, (6) 168; formation condition, (6) 172.
cords, surface tension effect, nature of cords, composition of glass samples, surface tension differences and relative viscosities, (6) 168–73.
deterioration after use and abuse, (2) 53.
discoloration: heat effect, (4) 107; ultraviolet, effect of Pb or TiO_2 additions, (4) 108.
fading, by irradiation, color restoration, (4) 106.
fading: ultraviolet, sunlight and X-ray tests, (4) 104; visual observations, (4) 104–105; effect of iron oxide, manganese oxide, arsenic oxide, antimony and selenium, (4) 106–107.
seeds in, analysis, procedure, (3) 78.
seeds and blisters, gas analyses, tables, (3) 82.
seeds in, density, effect of Fe_2O_3 additions on melting and fining, curves, (12) 357.
seeds, gases in, analyses, (3) 69.
weathering vs. mechanical abuse, treatment, effect, (2) 55.
weathering, storage conditions, effect of humidity and temperature, (13) 359–69.
weathering of glass jars, thermal-shock tests, (2) 54.
density: BaO and ZnO substitutions for Na_2O, CaO-MgO, and SiO_2, effect, (3) 63; effect of Fe_2O_3 substitutions, (14) 402.
density of K_2O–B_2O_3 types, methods, measurements, and curves, (3) 88.
discoloration. See *Glass, defects.*
durability. See *Glass, chemical durability.*
elements, oxide in, as glassformers, (4) 100.
expansion coefficient: BaO and ZnO substitutions for Na_2O, CaO-MgO, and SiO_2, effect, (3) 65; effect of Fe_2O_3 substitutions, (14) 404.
extinction formula, Beer and Lambert laws, (13) 374; extinction curves for glass melted in N_2 and CO, FeO, Fe_2O_3, and aqueous selenide solutions, (13) 375–76.
fading. See *Glass, defects, fading.*
ferrous oxide in. See *Glass, soda-dolomite lime-silica.*
fiber softening point, Lillie method, (3) 63.
fibers, unannealed, thermal expansion curves, (3) 86.
flint, gas content, and CO_2 analysis of blisters, (3) 69, (3) 76–77.
flint, weathering effect of storage conditions on external and internal surfaces of capped and uncapped bottles, (13) 359; chemical composition, capacity, internal area, and storage conditions, tables, (13) 360; alkali extraction tests, method and tables, (13) 361–64; visual tests, (13) 362–63; photomicrographs, (13) 365–69.
fruit jars, thermal-shock tests after aging and weathering, (2) 53.
furnaces for glassmelting. See *Furnaces.*
gases in, test apparatus, (3) 70–73; analysis of noncondensable and condensable gases, (3) 72–74; average deviations in gas content, and relative volumes of dissolved gases, (3) 75–76.
glassforming molds, cast iron for: fatigue test, curve, (13) 381–92; cracking, accelerated test, materials, procedure, and equipment, (13) 382–83; chemical analyses of samples and cracking data, (13) 382; chill-cast iron and alloy iron and sand-cast alloy irons, microstructure, (13) 383–86; heat-treated iron, microstructure of, and crack through chill area, (13) 387; hardness gradients, (13) 388.
glassforming oxides, B_2O_3 and Na_2O for sodium borate glass, chemical composition, light transmission, and temperature, relation, (14) 395–401.
glassforming oxides (network formers): nature of Ta_2O_5, TiO_2, and BeO, (4) 97; ρ values for various oxides, (4) 98; vs. modifier, identification method, (4) 99; grouping of elements as oxide glassformers, (4) 100.
glassforming oxides, silica and boric oxide, analogy between comparable binary systems, (14) 392.
glassmelting, effect of air, N_2, and CO furnace atmospheres on oxidation-reduction equilibria between selenium and iron, (13) 371.
glassy phase, effect of firing and cooling rates, (2) 39.

Glass (*continued*)
grain size vs. density of particles, effect on batch mixes, (2) 59.
heat penetration, temperature gradients in soda-lime-silica melt with varying amounts of Fe_2O_3, curves, (12) 356.
humidity effect on commercial bottles, tests, (13) 359.
iron oxide additions, melting rate effect, table and curves, (12) 356; chemical effect, (12) 357.
iron oxide substitutions for Na_2O, CaO·MgO, and SiO_2, in soda-dolomite lime-silica glass, effect, (14) 401–408.
irradiated, fading and color restoration, (4) 106.
lead silicate, with halides and silver, effect on colors, (10) 279.
light transmission in. See *Light transmission*.
liquidus temperature: BaO and ZnO substitutions for Na_2O, CaO·MgO, and SiO_2, effect, (3) 64; effect of Fe_2O_3 substitutions, (14) 403–404.
liquidus temperature, temperature-gradient method of W. B. Silverman, (3) 62.
mechanical wear vs. mechanical strength, (2) 55.
metal salts effect, table, (5) 145.
mixers for batch mixing, types, photos, (2) 56.
molds for. See *Glass, glassforming molds*.
navigation and aviation types, neodymium in, effect, (5) 142.
neodymium oxides for coloring, effect, (5) 142.
neodymium, for windows, for use with sodium lamps, (5) 142.
Neophane (Philiphan) for aviation and navigation, (5) 142.
network formers. See *Glass, glassforming oxides*.
noble metals in, tin ion as stabilizer, (10) 278.
optical, praseodymium oxide, Nd_2O_3, and La_2O_3 in, review, (5) 142.
optical, thorium oxide content, composition, (5) 138.
oxidation-reduction equilibria in, between Se and iron melted in atmospheres of air, N_2, and CO, (13) 371.
oxide composition: calculated, for selenium ruby, (5) 126; Ni and iron oxides vs. CoO in selenium black glass, effect, (5) 129; see also *Glass, glassforming oxides*.
Pauling electrostatic valence rule, (4) 102.
potash, high content, effect on selenium ruby glass, (5) 126.
potash, melted in N_2, transmittancy curves, (13) 374.
potash-soda-lime, reactions between iron and selenium in air, N_2, and CO_2, (13) 371–81.
potassium borate (K_2O–B_2O_3), chemical analyses, (3) 84.
density and refractive index, methods, measurement, curves, (3) 88; effect of K_2O on BO_4 tetrahedra, (3) 88.
structure of B_2O_3 glass, effect of BO_4 tetrahedra formation, (3) 89.
thermal expansion, method, results, and composition curves, (3) 86–87.
viscosity of, data and curves, (3) 88–89.
X-ray diffraction data for atomic structure, (3) 83–84; X-ray studies and intensity and radial distribution curves, (3) 84–85.
powdered materials for batch mixes, advantage, (2) 56.
pressure strength of bottles, thickness limitations and effect, (15) 428, (15) 432–33; curves and logarithmic scatter plots, (15) 432–33; see also *Glass, chemical durability*.
pressure test breakage vs. bottling line, (15) 434.
Preston hydrostatic pressure machine for strength tests on bottles, (15) 434.
production rates for bottles, strength limitations, (15) 431–32.
purple. See *Glass, colored*.
Pyrex-brand capillaries, gases in, analysis of synthetic mixtures, (3) 81.
refractive index of K_2O–B_2O_3 types, methods, measurements, and curves, (3) 88.
ruby. See *copper ruby, gold ruby*, and *selenium ruby* under *Glass, colored*.
seeds. See *Glass, defects*.
selenium in, black. See *Glass, colored*.
color changes, Höfler studies, (13) 372.
fading, effect, (4) 106–107.
and iron in, decolorizing action of, oxidation-reduction equilibria between, in

Glass, selenium in (*continued*)
air, N_2, and CO atmospheres, (13) 371–81.
Pavlish and Silverthorn method for analysis, (5) 127.
pink. See *Glass, colored, selenium pink*.
polyselenide in, extinction curves, (13) 378–79; coloration, effect of half-cell reaction, (13) 379.
ruby. See *Glass, colored, selenium ruby*.
signal glass, selenium ruby base composition, (5) 125.
silicate, with halides and silver, effect on colors, table, (10) 279.
silicon in, partial formation theory, (4) 101–103.
silver. See *Glass, colored, silver*.
soda-ash, whiting, and sand in batch mix, effect of soda-ash fineness, r.p.m. of mixer, and mixing time, (2) 57.
soda-dolomite lime-silica: barium and zinc oxide substitutions, effect on physical properties, chemical composition, and physical properties, tables and curves, (3) 61–69; iron oxide substitutions in, effect, (14) 401–408.
soda-lime and potash-soda-lime, oxidation reduction equilibria in, between selenium and iron in air, N_2, and CO atmospheres, (13) 371–81.
soda-lime-silica, decolorizers in, effect of light, (4) 104.
soda-lime-silica, iron oxide additions, effect on melting rate, heat penetration, and chemical effect, (12) 356.
sodium borate, color changes, General Electric automatic recording photoelectric spectrophotometer for measurements, (14) 395.
sodium borate: structure vs. temperature, chemical composition, spectral transmission, light transmission vs. Na_2O content, and transformation temperature, (14) 395–98; B and O atoms vs. Na_2O atoms, relation, and possible B_2O_3 space model, (14) 400.
solarization and weathering, thermal-shock test results, (2) 54.
space model of boron oxide glass, theoretical, (14) 400.
spectrophotometer for spectral transmission measurements, (4) 104, (13) 374, (14) 395.
Steinie beer bottles, strength limitations, in manufacture, (15) 427–34.
storage of commercial bottles, weathering test for capped and uncapped samples, (13) 359–71.
strength. See *Glass, chemical durability*.
"striking" properties, (10) 278.
surface tension, effect on cords, (6) 168.
surface tension, Littleton fiber softening point method, (3) 63.
thermal expansion, Merritt interference method, (3) 62.
thermal-shock tests on solarized and weathered glass samples, test results, (2) 54–55.
thickness of bottles, strength limitations, (15) 427–28; weight per capacity ratio, effect, (15) 428.
thorium oxide in, composition, effect, (5) 138.
tin compounds in, effect on gold ruby color, data on solubility, (10) 281.
transformation temperature, Gooding and Turner data, curves, (14) 399.
transformation temperature of sodium borate specimens, (14) 397; spectral transmission curves at varying temperatures, (14) 396–99.
transmission curves for soda-lime and potash-soda-lime glasses melted in N_2 atmosphere, (13) 374; see also *Light transmission*.
ultraviolet discoloration, prevention by lead or titanium oxide additions, (4) 108.
vibration decay in glass bars, vs. chemical composition, vibration amplitude vs. modulus of decay, chemical composition and density of specimens, (14) 409; decay method and tone decay pattern, disannealing effect on sonic properties, (14) 410–12; modulus of decay, table and curves, (14) 412.
viscosity, BaO and ZnO substitutions for Na_2O, CaO·MgO, and SiO_2, effect, (3) 66–67; effect of Fe_2O_3 substitutions, (14) 406–407.
viscosity, Fulcher measurements, (3) 63.
viscosity, Hunter falling-sphere method, (3) 63.
viscosity, Lillie equation, (3) 89.

Glass (*continued*)
viscosity of K_2O–B_2O_3 types, methods of determination and results, curves, (3) 88–89.
water additions to batch, use and effect, (2) 59.
weathering. See *Glass, defects, weathering*.
X-ray discoloration, effect of cerium, (4) 108.
yellow. See *Glass, colored, yellow*.
zinc base, composition, effect on selenium ruby glass, (5) 126.
zinc oxide additions, effect of time and r.p.m. on degree of mixing, (2) 58.
zinc oxide in, chemical analyses and physical properties, tabular data, (3) 63.
zinc oxide as Na_2O, CaO·MgO, SiO_2 substitute, effect on density and liquidus temperature, (3) 54; expansion coefficient and deformation temperature, viscosity, and acid and water durability, (3) 65–68.
zirconium oxide in, application, review, (5) 134–35.
Glass Container Association of America, Standard Testing Procedure Committee, Preston report on strength of bottles, (15) 427; Committee members, (15) 427.
Glazes with alumina and silica of varying contents, firing effect on interfacial or glassy layer, (1) 12–15.
for bisque ware, batch contents and glaze formula, (14) 417.
blistering and bubbles, effect of sulfur in kiln gases, (14) 417–18.
cerium oxide in, effect, review, (5) 142–43.
crazing, autoclave test, results and glaze formula, (14) 414–15.
crazing factors, and tests, for semivitreous bodies, (2) 45.
crystal, at cone 4 and cones 02, 2, and 4, (1) 13–15.
crystalline materials in, at cone 4 and melted on Pt foil, tables, (1) 12.
defects, effect of air-gas ratio, (14) 418.
dinnerware, semivitreous, and decalcomania decoration, effect of sulfur and reducing gases, (14) 416; body and glaze formulas, (14) 416; defects, characteristics, cause, and laboratory tests, (14) 418; decoration defects, tests, (14) 418–19; firing recommendations, (14) 419–20.
gas-firing, effect, bibliography, (14) 420.
glaze-fit compression of nepheline syenite chinaware bodies, tables, (3) 91.
hardness, microcharacter for determination of microhardness numbers, vs. scratch hardness, (2) 47; Lyons scratch-hardness tester for scratch-resistance vs. glost-temperature tests, curves, (2) 47.
lead, glaze-body interface, compositions, tables, (1) 11–12; lead content, volatilization effect vs. refractive index values, (1) 15.
refractive index vs. firing time, curves, (1) 11.
ring-test compression data on vitreous chinaware fired in 45 positions, (2) 39; glass compression data, muffle vs. multiburner kilns, (2) 40.
scratch hardness. See *Glazes, hardness;* also *scratch hardness* under *Enamels, defects*.
for semivitreous bodies, crazing resistance vs. bisque thermal history, moisture-expansion curves, (2) 45; glaze stress vs. crazing, table, (2) 45.
solubility, vs. firing effect, curves, (1) 11.
stress condition vs. crazing, ring test and tuning fork test data, (2) 45; variations in glost firing, cone deformation and compression data, (2) 46.
texture, microstructure data, variations with different glost thermal treatment, (2) 46–47.
thermal history, effect, (2) 39.
zirconium compounds in, application, review, (5) 135–36.
zirconium oxide in, stability and solubility, (5) 136–37.
Glostware. See *Dinnerware; Firing*.
Gold ruby glass. See *Glass, colored, gold ruby*.
Graphite for spiral heating element in electric load-test furnace, (4) 113; advantages, (4) 116.
Gypsum, consistency test, modified Vicat needle, description and photo, (15) 460.
Gypsum molds. See *Molds*.

Halides in red silver glasses, effect, (10) 278; silver carbonate in, effect on colors of silicate glasses, table, (10) 279.

Hardness in chill- and sand-cast blocks, and curves, (13) 386.
of glazes, microhardness numbers vs. scratch hardness, relation to glost temperatures, (2) 46–47.
Lyon scratch-hardness tester, (2) 47.
Harrison dye-stain method for abrasion resistance, value, (2) 50.
Heat flow, lateral and vertical, in insulating firebrick tests, formulas, and effect of variables, (15) 456.
Heatshock ware. See *Vitreous heatshock ware.*
Heat-of-wetting values of clayware, tests, (4) 108.
Hercynite, separation of, as primary crystal phase in $FeO–Al_2O_3–SiO_2$, (6) 157.
Hommel viscometer for enamel slip control, (15) 459–60.
Hotel chinaware bodies. See *Chinaware.*
Hot-water tanks, coatings for, zinc vs. porcelain enamel, tests, (6) 164–68.
Humidity and other weathering effects on commercial glass bottles in storage, (13) 359.
Hunter multipurpose reflectometer for reflectance tests and gloss measurements, (2) 49.
Hydration of clays. See *Clays.*
Hydrofluoric acid method for mullite determination, process, effect of different oxides, X-ray values compared, (1) 4–5; accuracy, (1) 10.
Hydrogen in cast iron, effect of firing above 725°C., (7) 175; decarburization vs. hydrogen absorption during firing, (7) 178.
in cast iron for wet-process enamels as cause of blisters, and pinholes, (7) 175–80.
Hydrogen ion value of ball clays, calomel and quinhydrone electrodes for determination, (12) 327; base-exchange capacity, organic matter in, hydroxide treatment of H clays, (12) 328; pH values, chemical properties, tabl , (12) 329.
Hydrometer for specific gravity tests on enamel slip, (2) 51.
Hydrostatic pressure machine, Preston, for strength tests on glass bottles, test procedure, (15) 434–35.
Hydrous magnesium metasilicate (talc or soapstone) for steatite bodies, constitution, literature review and studies, (15) 443.
Hyvac and metal diffusion pump (shell pump) for gas analyses, (3) 71.

Illite, description, and heat-of-wetting values of autoclaved and unautoclaved samples, tables and curves, (4) 110–11.
Inhibitors, effect on relation of diffused hydrogen to temperature, (7) 207–209.
Insulators for high-frequency application, steatite bodies for, review, test studies, and optical properties, (15) 443; see also *Steatite bodies.*
Ionic radii of Si^{4+} and O^{--}, (4) 101.
Iron. See *Metals for enamels; Molds for glassforming.*
Iron oxide in arsenic-containing glass, effect on fading, (4) 106.
in glass, effect on melting rate, (12) 355–56; chemical effect, (12) 357.
in porcelain enamel, effect on tensile strength, (1) 29.
in soda-dolomite lime-silica glass, effect of substitution, (14) 401–408.

Jeremjevite, $BAlO_3$, vs. artificial boroaluminate, $2B_2O_3·9Al_2O_3$, and glass, conversion, (14) 394; specimens in U.S., (14) 394.

Kaolin. See also *Clays; Kaolinite.*
dehydration, review, (4) 109.
Florida, and Mo. burley clay, analyses and studies in system $FeO–Al_2O_3–SiO_2$, (6) 153.
-talc body mixtures (steatite ceramics), low dielectric-loss: chemical composition and dielectric properties, relation, (15) 439; chemical analyses, compositions, and firing schedule, specific resistance and ratio of reactance to resistance or susceptance to conductance in bodies of $MgO–Al_2O_3–SiO_2$, $RO–Al_2O_3–SiO_2$, and $MgO–BaO–Al_2O_3–SiO_2$, tables and curves, (14) 440–43.
Kaolinite, decomposition, equations, (1) 2; hydrofluoric acid method, effect of oxides on mullite yield, (1) 5.
description and heat-of-wetting values of autoclaved and unautoclaved samples, tables and curves, (4) 111.
Kaolinite (*continued*)
electrodialyzed fractions, with NaOH additions, viscosity relations, curves, (12) 344–45.
exchange capacity, effect of surface area, (12) 344; specific surface vs. exchange capacity, curve, (12) 346.
Kiln gases. See *Gases.*
Kilns. See also *Firing; Furnaces.*
muffle and multiburner direct-fire types: for firing vitreous bodies and ware, cone deformation data and effect on physical properties, (2) 33–36; comparative data, (2) 36; glaze compression data, (2) 40.
tunnel, open-fire, for bisque ware, effect of sulfur gases, analyses, (14) 417.
Kitchenware, enameled, thermal-shock resistance, tests, (15) 463–66.
Kyanite, pressed, for refractory brick, load-test data, (4) 115.

Lead glazes. See *Glazes.*
Lead molybdate in enamels, properties and behavior, (6) 163.
Lead silicate glass. See *Glass, lead silicate.*
Lepidolite vs. feldspar in hotel chinaware body: composition and absorption data, (4) 117; intensity of transmitted light, (4) 119; translucency of specimens, (4) 120; effect of mixtures on translucency and absorption vs. translucency, tables and curves, (4) 121.
Light transmission, intensity, through vitreous hotel chinaware body, tables, (4) 119; curves, (4) 122.
in neodymium glasses, (5) 142.
in selenium black glass, curves, (5) 128.
in soda-lime and potash-soda-lime glasses, effect of iron and Se melted in N_2 atmosphere, curves, (13) 374.
in soda-lime-silica glass, fading and discoloration tests, (4) 104–107.
in sodium borate glasses, effect of temperature, method, test-furnace data and curves, (14) 395–99.
Limiting systems. See *Systems.*
Lithium molybdate in enamels, properties and behavior, (6) 161.
Load test for plastic clay bodies, effect of cyclic loading, curves, (1) 25.
for refractories, methods and furnace, (4) 112–14.
Lyon scratch-hardness tester for glaze scratch resistance vs. glost temperature, curves, (2) 47.

Magnesia, characteristics and review, (3) 93.
–$FeO–SiO_2$ system, electric-furnace study, vs. Schairer thermal study, agreement, (11) 310.
-flint series, chemical analysis and specific gravity of fused products, curves, (11) 297–98.
forsterite-periclase, micrometric analyses, (11) 307.
furnace charges, calculated final composition, (11) 295.
vs. olivine-magnesite-quartz series, fusion compositions, calculated and analyzed, comparison, (11) 298; grain size vs. texture and grain size of periclase and wüstite, (11) 307–308; see also *Olivine-magnesite-quartz series.*
petrographic data, (11) 299; megascopic description of melts, (11) 300–306; effect of impurities on optical properties, (11) 309.
–silica system: electric furnace study, (11) 294; phase diagram of Bowen and Andersen, revised by Greig, (11) 294; studies of magnesia-flint melts and olivine-magnesite-quartz melts, (11) 295; ratio vs. melt composition, curves, (11) 298.
–zirconia spinel, thermal expansion, density, and microstructure studies, (3) 93.
Magnesio-wüstite, grain-size study as function of composition in $MgO–Mg_2SiO_4$ system, (11) 308.
Magnesium carbonate in steatite bodies, dielectric properties, composition and data on specific resistance and ratio of reactance to resistance or susceptance to conductance, tables and curves, (15) 442.
Magnesium hydroxide for ball-clay treatment, effect on physical properties, (12) 329, (12) 335.
Magnesium metasilicates. See also *Clinoenstatite; Forsterite; Soapstone; Steatite; Talc*
Magnesium metasilicates (*continued*)
classification and literature review, (15) 443; Thilo and Rogge modifications, (15) 444.
crystal modifications, protoenstatite and clinoenstatite, (15) 447.
Magnesium oxide–$Al_2O_3–SiO_2$ system, portion of phase equilibrium diagram, chemical composition vs. dielectric properties, (15) 440–41.
–ZrO_2 and $MgO–ZrO_2–TiO_2$, survey of systems, characteristics, and uses, (5) 132–33; $MgO–ZrO_2$, melting diagram, (5) 132.
Manganese oxide in soda-lime-silica glass, effect on fading, curves and discussion, (4) 106–107.
Melting diagrams. See *Equilibrium diagrams.*
Mercury balance volumeter. See *Volumeters.*
Metallic oxides for catalytic mullitization of kaolinite, (1) 1.
Metals, iron, for glassforming molds. See *Molds for glassforming.*
iron and steel, refining, importance of $FeO–Al_2O_3–SiO_2$, (6) 151.
Metals for enamels, cast-iron defects, effect of firing above 725°C., (17) 175; hydrogen condition and decarburization vs. hydrogen absorption during firing, (7) 177–79; see also *Enamels, defects.*
cast iron and sheet steel, hydrogen treatment vs. dehydrogenization, fired at 730°–840°C., photomicrographs, (7) 176–77; hydrogen-containing vs. hydrogen-free specimens, photomicrographs, (7) 178–79.
dehydrogenized cast iron, blister-free, photomicrographs, (7) 176–77.
fracture-type defects: effect of hydrogen, (7) 195–98; control and prevention, 200–202.
hydrogen absorption, cold-worked metal vs. scratch blisters, effect of rolling direction, validity of mechanical causes, (7) 185–86.
hydrogen theory proposed, Kautz and Zapffe and Yarne theories, (7) 204.
impurities (geometrical), sharp vs. blunt scratch marks, and chemical deposition of salts, effect on scratch blistering, (7) 184.
iron foil, hydrogen isothermal evolution, curves, (7) 213.
iron-moisture reaction, effect on blistering, (7) 191.
nickel dip, effect of Ni thickness, (7) 188–89; effect of acid concentration, (7) 208–209.
nickel dip, effect on scratch blisters, ferrous salts deposition, hydrogen in nickel and preferential plating, and gas-liberating reactions at scratch, (7) 188–89.
nickel dip, vs. hydrogen effusion during firing, effect on scratch blistering, (7) 182–83.
oxidation, preoxidized surface, substitution for ground-coat enamel, advantages, (7) 191.
pickling-acid contamination, used acid as cause of increased hydrogen absorption, surface impurities, effect, (7) 205–206.
pickling, inhibitors, effect on relation of diffused hydrogen to temperature, (7) 207–209.
pickling, "promoters," and cathodic electrolysis, effect of oxide films, impurities, and inhibitors, and effect on absorption, (7) 207–208.
reboiling analogy and hydrogen effects, (7) 213.
rimming steel, hydrogen in, chemical nature of steel and effect on fish scaling, (7) 212.
sheet steel: hydrogen behavior at scratched steel surface, effect of cold-working and scale during pickling, (7) 181–82; effect of galvanic plating (nickel dip), and behavior during firing, (7) 183.
hydrogen-containing and hydrogen-free, effect on ground and cover coats, photomicrographs, (7) 178.
physical effect of scale, electrochemical action between scale and iron, and production and control of scratch blisters, (7) 189.
in pickling acid, hydrogen bubbles at cold-worked scratch marks and sheared edges, (7) 178.
surface oxidation vs. hydrogen absorption during pickling, development of scratch blisters during firing, (7) 186.

Metals for enamels, sheet steels (*continued*)
steel, de-enameling by hydrogen absorption, (7) 182.
steel, hydrogen in, effect of water content of dry enamel slip, (7) 200.
steel, oxide coatings vs. general blistering phenomena: effect of iron-moisture reaction, substitution of preoxidized ground coats, (7) 191–92; hydrogen absorption during enamel firing and primary boiling, cause, (7) 193–94.
steel, surface oxidation vs. defects in enamel coatings, (7) 191.
Metal salts in water, effect on glass bottles, tables and discussion, (5) 145–46.
"Metatalk." See *Talc.*
Microcharacter for glass-hardness tests, (2) 47.
Micrometers, Wentworth recording, for analyses of forsterite-periclase and olivine-magnesite-quartz series, tables, (11) 307.
Microstructure of cast iron for glassforming molds, modification by heat-treatment, photomicrographs, (13) 384–87.
Minerals in feldspar, calculation by chemical analysis, formulas and method, (14) 420–22; see also *Clays, clay minerals.*
Mixing apparatus for glass batches, types, photos, (2) 56.
Read mixer for pugging clay, (12) 347.
Modulus of decay of glass bars. See *Glass, vibration.*
Moisture in clays, heat-of-wetting values, studies, (4) 108; see also *Expansion.*
Molds, glassforming: cast iron for, fatigue test, accelerated cracking test, chemical analyses of samples, and cracking data, (13) 381–83; chill-cast and alloy iron and sand-cast alloy irons, microstructure, (13) 383–86; heat-treated iron, microstructure crack through chill area, hardness gradients, curves, (13) 387–88.
gypsum and bisque, yield value vs. water content of casting slips, curves, (12) 343.
plaster of Paris ($CaSO_4$) and deflocculated slips, effect on slip casting, reactions, (12) 339, (12) 344.
plaster, porous bisque, and $CaCl_2$- and $AlCl_3$-treated porous bisque molds for casting slips, base-exchange studies, (12) 336.
Molybdates, compounds of, $(NH_4O_2)MoO_4$, Na_2MoO_4, K_2MoO_4, $LiMoO_4$, $BaMoO_4$, $PbMoO_4$, $ZnMoO_4$, $CdMoO_4$, and $Ce(MoO_4)_2$, properties, adherence, and opacity of, as mill additions in clear enamels, (6) 161.
soluble and insoluble, in enamels, effect on adherence, (6) 160; properties, behavior, and effect of compounds as mill additions, (6) 161; empirical formulas and smelter batches for clear and white enamels for ground coats and color bases, (6) 162–63.
Monazite, zirconia as by-product, (5) 130.
Montmorillonite, description, heat-of-wetting values of autoclaved and unautoclaved samples, tables and curves, (4) 110–11.
Mortars, refractory: consistency of wet, air-setting types, tests: flow trough, range of flow, Hommel viscometer, (15) 459–60; modified Vicat apparatus, description, photo, results, (15) 460–62; mortar consistencies with hemispherical- and flat-end plungers, (15) 462; adoption of modified Vicat apparatus, (15) 463.
refractory, consistency vs. workability, differentiation, (15) 459.
Muffle gases. See *Gases.*
Mullite and boroaluminate, resemblance, (14) 393; comparison of fusion cast bodies, (14) 394.
catalysis, literature review, formation and structure, preparation and composition of samples, (1) 1–3.
chemical vs. X-ray method, (1) 9.
crystallization in system $FeO–Al_2O_3–SiO_2$, (6) 153; as primary crystal phase, (6) 156–57.
hydrofluoric acid determination, method, chemical analysis, effect of oxides on mullite yield from kaolinite, solubility rate, tables and curve, (1) 4–5.
microphotometer curve for analysis, (1) 5.
with oxide additions, MgO, Li_2O, and TiO_2, effect, photomicrographs, (1) 6–8.
oxide concentration, effect on percentage yield, table, (1) 5; microscopic tests and ratio of intensity of mullite to ZnO lines, (1) 7–9.
Mullite (*continued*)
pseudomorphic effect of MgO, photomicrographs, (1) 6–7.
pure, solubility, determination, (1) 4.
separation as primary crystal phase in $FeO–Al_2O_3–SiO_2$, (6) 156–57.
X-ray quantitative determination, (1) 4; tables, (1) 8–9.
Mullite electrical porcelain. See *Porcelain, electrical.*

National defense, neodymium glass for windows, (5) 142.
Neodymium as glass decolorizer, (5) 141.
Neophane (Philiphan) glass, for aviation and navigation, (5) 142.
Nepheline syenite vs. potash feldspar in hotel chinaware bodies: flux content, chemical composition, (3) 90; absorption, modulus of rupture, and dry and plastic properties, tables, (3) 91; pitch frequency (cycles) (3) 92; thermal expansion curves, (3) 92.
Network formers. See *Glass, glassforming oxides.*
New York shales. See *Shales.*
Nickel dip (galvanic plating). See *Metals for enamels, nickel dip.*
Nomograph, formulas and alignment chart for volume determination, (10) 277.
Nonplastic materials for fusion test cones, preparation, (10) 282.

Olivine-magnesite-quartz series, chemical analysis and specific gravity of fused products, specific gravity curves, (11) 297–98.
-magnesite-quartz series, vs. magnesia-flint series: fusion compositions, comparison of calculated and analyzed bodies, (11) 298; comparison-microscope study of grain size and texture, (11) 307.
-magnesite-quartz series, petrographic data, grain size and texture, micrometric analyses, and photomicrographs, (11) 305–307; periclase and magnesio-wüstite grain size as function of composition, curves, (11) 308.
Olivines, electrical fusion, effect, (11) 309.
Opacifiers, cerium oxide in, review, (5) 142–43.
in frits and glazes, ZrO_2 solubility, rules governing, (5) 137.
zirconium compounds in, history and types, (5) 135–36.
Opacity of enamels, dry-process, effect of firing treatment, (2) 49.
Optical glass. See *Glass, optical.*
Optical properties of magnesite-flint series, effect of impurities, (11) 309.
Oxidation-reduction equilibria in glass between Se and iron melted in atmospheres of air, N_2, and CO, (13) 371.
of steel surfaces for enameling, relation to defects in enamel coatings, (7) 191.
Oxides, glassforming (network formers), nature of Ta_2O_5, TiO_2, and BeO, and oxide ρ value, (4) 97–98; network formers vs. modifiers, identification method, (4) 99; elements as oxide glassformers, table, (4) 100.
glassforming, silica and boric oxide as, and analogy between comparable binary systems, (14) 393; B_2O_3 and Na_2O, for sodium borate glass, effect on glass structure, (14) 395.
metallic: catalytic mullitization of kaolinite, (1) 1; in mullite, concentration, effect on temperature vs. percentage of mullite yield, curves, (1) 6.
refractory, from ZrO_2-containing elements, (5) 133.

Particle size of flint in talc-pyrophyllite and clay-flint-feldspar bodies, effect on moisture and thermal expansion, (14) 413–16.
of kaolinite, monodisperse fractions, calculated and observed values, vs. specific surface and exchange capacity, (12) 345.
Periclase-forsterite (magnesia-flint series), micrometric analyses, (11) 307.
grain size as function of composition in $MgO–Mg_2SiO_4$ system, curves, (11) 308.
Petrology, observations on quaternary system $CaO–FeO–Al_2O_3–SiO_2$, (10) 273.
Phase diagrams. See *Equilibrium diagrams.*
Photography, miniature camera for decay patterns of vibrating glass bars, process and photo, (14) 411–412.
Photronic cell and spectrophotometer for translucency measurements on whiteware, photos and description, and summary of use, (4) 116–22.
Pickling and pickling solutions. See *Metals for enamels.*
Pigments, MgO, $BaSO_4$, and $Ca_3(PO_4)_2$, in gold ruby glasses, effect of tin compounds, (10) 281.
Pitch frequency (cycles) in nepheline syenite hotel chinaware bodies, tables and curves, (3) 91–92.
Plaster of Paris ($CaSO_4$) for molds and deflocculated slips, effect on casting process, (12) 336.
Plastic bodies, flow characteristics: Bleininger method, (1) 16; Emley test apparatus, (1) 17.
slip planes, development, (1) 25; slickensides on specimen surfaces, (1) 25.
Plastic clay masses, stress-strain characteristics, (1) 16; test methods, (1) 19.
Plasticity of clays, review, and viscosity and workability defined, (1) 16.
and strength of American and English ball clays, effect of KOH and NaOH treatment, (12) 327, (12) 336.
Plastograph, Thiess, for plastic mixtures, (1) 17.
"Plate" method for thermal-expansion measurements on ground-coat and nonacid-resistant cover-coat enamels, (15) 465; see also *"Rod" method.*
Plate tester for thermal conductivity tests on firebrick, description and photos, (15) 452–53.
Plungers, hemispherical-end and flat-end types, Vicat consistency results, (15) 462.
Porcelain. See also *Chinaware; Dinnerware, Whitewares.*
electrical: high mullite and steatite types, body composition data, (1) 18; stress equilibrium vs. moisture content, curves, (1) 21–22.
electrical vitreous, aging effect on plasticity and workability, (1) 23.
creep-test apparatus for tests on speed effect, and cyclic loading test, (1) 25.
heatshock ware: body composition, (1) 18; equilibrium stress vs. moisture content curves, (1) 21.
stress and strain tabular data, (1) 26.
vs. steatite bodies, differentiation, (15) 439; see also *Steatite bodies.*
stress-strain vs. moisture content, curves, (1) 18; log equilibrium stress vs. moisture content, (1) 22.
translucency measurements with photronic cell and spectrophotometer, (4) 116–22.
Porcelain enamel. See *Enamels.*
Porous earthenware bodies. See *Earthenware bodies.*
Potash feldspar vs. nepheline syenite in hotel chinaware bodies, (3) 90–93.
Potash-soda-lime glass. See *Glass, potash.*
Potassium borate glass. See *Glass, potassium borate.*
Potassium hydroxide for ball-clay treatment, effect on physical properties, (12) 329, (12) 335.
Potassium molybdate in enamels, properties and behavior, (6) 161.
Pottery, firing, effect of sulfur and reducing gases, (14) 416; glaze defects, characteristics cause and laboratory test, (14) 418; decoration defects, characteristics, causes, and tests, (14) 418–19; firing recommendations, (14) 419–20; see also *Earthenware.*
Power loss in low dielectric loss bodies, formula, (15) 439.
Praseodymium oxide in optical glass, effect, (5) 142.
Protoenstatite as unstable crystal modification of magnesium metasilicate, (15) 447.
Pugging of clays, Read mixer and various treatments, (12) 347–48.
of shales, effect of treatments on physical properties, tables and curves, (12) 347–50.
Pyrometric cone equivalent, cone deformation data on vitreous china bodies and ware, (2) 34–35.
Pyrometric cones, refractory and coal-ash, preparation, A.S.T.M. procedures, C24–35 and D271–40, (10) 282; preparation from nonplastic material, (10) 282.
Pyrophyllite-talc body, effect of flint particle size, thermal expansion and rate-of-change curves, (14) 415.
heat-treatment studies, effect on properties, (2) 41–46.

Quaternary systems. See *Systems.*

Q meter for dielectric loss measurements, (15) 440.

Rare earths as oxidizing agents, cerium oxide and neodymium oxide, (5) 141; see also *Cerium oxide* and *Neodymium oxide*.
source and uses, (5) 141.
Reboiling of enamels. See *Enamels, defects*.
Reducing gases. See *Gases*.
Reduction-oxidation equilibria in glass between Se and iron melted in air, N_2, and CO atmospheres, (13) 371.
Reflectance of antimony-bearing, dry-process enamels, effect of firing treatment, (2) 49.
Refractories, alkali analysis for slag-attack tests, (11) 287.
alumina-silica, ferrous oxide attack, value of equilibrium studies in system FeO–Al_2O_3–SiO_2, (6) 159.
blast-furnace, abrasion effect on lining wear, (11) 315–16; references, (11) 320.
alkali attack, cause and effect, (11) 313–15; references, (11) 320.
carbon and alkali action combined as cause of disintegration, (11) 317.
disintegration by carbon deposition, photo, (11) 312–13.
hearth brick samples, analyses and photos, (11) 313.
linings, chemical analysis of typical samples, (11) 312.
service conditions, (11) 311–16; bibliography, 75 references, (11) 318–20.
slag attack in bosh and upper hearth sections, (11) 315.
in U.S. vs. Great Britain, (11) 312.
boroaluminate fusions, physical properties and uses, comparison with cast fusion mullite, (14) 394.
carbon deposition as cause of disintegration, (11) 312; photo, (11) 313.
cerium oxide in, use, (5) 142–43.
and coal-ash test cones, preparation of nonplastic materials, (10) 282.
cone-fusion test for slag attack, (11) 286; references, (11) 290.
corrosive fluids attack, immersion tests for, (11) 284, (11) 289.
crucibles, thorium oxide for, review, (5) 138.
disintegration by carbon and alkali action, (11) 317; references, (11) 318–30.
electrocast and pressed forsterite, commercial electrocast, pressed kyanite and commercial magnesia, silica and chrome types, load-test furnace data, (4) 115.
equilibria relation of slag constituents vs. refractory, references, (11) 290.
firebrick. See *Refractories, insulating firebrick*.
fuel-oil ash attack, test, (11) 285.
fuels, coal, effect on slag attack, tests, (11) 285.
furnace for slag tests, types, (11) 285, (11) 289.
furnace for transverse strength tests, cross section and photo, (13) 389–90.
high-temperature, effect of MgO–ZrO_2, (5) 132.
immersion tests for corrosive fluid attack, (11) 284.
insulating firebrick: heat-flow measurements, lateral flow, (15) 456; variables effect, calorimeter to guard balance, room vs. calorimeter temperatures, temperature rise in calorimeter, sample thickness precision, precision measurements for calorimeter-temperature rise, and stray e.m.f. from power line, (15) 456–57.
insulating firebrick, pore structure, effect on thermal conductivity of variations in water flow through calorimeter, curves and photomicrograph, (15) 457–58.
literature review, blast-furnace disintegration: early studies, (11) 318; by CO, (11) 319; alkali action, abrasion, and miscellaneous, (11) 320.
load-test furnaces for brick tests, description, photos, and tables, advantages and disadvantages, (4) 112–16.
load-test methods, manual and recording, for linear changes, (4) 114.
magnesia–silica system, electric furnace study, (11) 294–310.
modulus of rupture, breaking mechanism, formula and diagram, (13) 389.
mullite. See also *Mullite*.
mullite: catalytic mullitization of kaolinite by metallic oxide, (1) 1; mullite formation, importance, (1) 1.
mullite, fusion-cast, vs. boroaluminate fusion, (14) 394.
Refractories *(continued)*
nonplastic materials, silica and alumina, preparation of fusion test cones, (10) 282.
particle-size measurements, references, (11) 289.
petrographic studies for slag tests, (11) 287.
porosity determinations, references, (11) 289.
pyrochemical studies, references, (11) 290.
for pyrometric test cones, fusion procedure, A.S.T.M. methods, (10) 282.
reactivity in, acidic or basic, references, (11) 290.
silicon carbide, self-bonded, calibration curves for load-test furnace, (4) 115.
slag attack: in bosh and upper hearth sections, (11) 315.
slag attack: measurement by chemical, physical, petrographic, and miscellaneous methods, (11) 287; outline, (11) 290.
slag penetration, physical measurements, (11) 287.
slag tests, cone fusion and crucible penetration tests, (11) 286, (11) 289.
immersion in corrosive fluids, gases, or vapors, (11) 284, (11) 289.
impingement method, (11) 285, (11) 289.
slag on brick surface, (11) 283, (11) 289.
literature review, 1932–1940, 166 references, (11) 290–94.
strength test, transverse test furnace, (13) 389; breaking mechanism for modulus of rupture tests, formula, (13) 389; test method, furnace control, and temperature equilibrium in test brick, (13) 389–90.
super-, zirconium oxide and ThO_2 in, uses, review, (5) 134–35.
thermal conductivity measurements: apparatus: review of 1936 test apparatus, diagrams, (15) 451; heating, water calorimeter, and thermocouple systems, photographs and diagrams, (15) 452–56; Globar water calorimeter vs. plate tester, curves, (15) 452; effect of contact pressure with calorimeter supported by springs, curves, (15) 455; lateral flow tests and curves, (15) 456; variables in heat flow, effect, curves, (15) 456–57; insulating and dense firebrick samples, conductivity curves and pore structure, (15) 457–58.
zirconium and thorium oxides in, characteristics, uses, review, (5) 132–34.
Refractory mortars. See *Mortars*.
Refractory oxides from ZrO_2-containing elements, (5) 133; order of ionic radius, (5) 133.
Rehydration of clays, review, (4) 100.
Resistance. See *Dielectric properties*.
ρ values of Si^{4+} and O^{--}, (4) 101.
Rimming steel, enameling stock. See *Metals for enamels*.
Ring test for vitreous chinaware, firing data, (2) 39.
"Rod" method for thermal-expansion measurements, on acid-resistant cover-coat enamels, (15) 465; see also *"Plate" method*.
Ruby glass. See *copper ruby, gold ruby,* and *selenium ruby* under *Glass, colored*.
Rutile (TiO_2), characteristic properties, (5) 132.

Sand-cast iron. See *Molds for glassforming*.
Sanitary ware, commercial body, casting slips for, stress-strain data and curve, (12) 340.
Scratch blisters in enamels. See *Enamels, defects*.
Scratch hardness. See *Hardness*.
Seeds in glass. See *Glass, defects, seeds*.
Selenium in glass. See *Glass, selenium;* also *selenium black, selenium pink,* and *selenium ruby* under *Glass, colored*.
Semivitreous chinaware bodies. See *Chinaware, semivitreous*.
Set of enamels. See *Enamels, set*.
Shales. See also *Clays; Kaolin*.
New York, physical properties, effect of steam and hot water with soda ash and wetting agents, tables and curves, (12) 346–49.
Read mixer for, (12) 347.
red-firing, expansion, contraction, and strength changes during firing, (12) 351.
Sheet steel for enamels. See *Metals for enamels*.
Signal glass. See *Glass, signal*.
Silica–Al_2O_3–CaO, Rankin and Wright equilibrium diagram revised, (10) 243.
–anorthite–FeO, composition, primary phases, and liquidus temperatures, equilibrium diagram and table, (10) 250–52.
Silica *(continued)*
and boric oxide as glassforming oxides, analogy between comparable binary systems, (14) 392.
–CaO–FeO–Al_2O_3: quenching experiments on five joins, (10) 241–74; equilibrium diagram, positions of five joins in regular tetrahedron, (10) 248.
–CaO–FeO, limiting system, equilibrium diagram, (10) 242.
–FeO–Al_2O_3, Snow equilibrium diagram, (10) 244; Schairer diagram, stability of crystalline phases with liquid, (10) 245.
–FeO–Al_2O_3 system, equilibrium studies, (6) 151.
iron oxide (Fe_2O_3) substitutions in glass, effect on physical properties, (14) 401–408.
–magnesia system, electric-furnace study, (11) 294–310; see also references under *Magnesia-flint series* and *Olivine-magnesite-quartz series*.
–MgO–Al_2O_3 system, portion of phase equilibrium diagram, chemical composition vs. dielectric properties, (15) 440–41.
–MgO–FeO system, electric-furnace study, vs. Schairer thermal study, agreement, (11) 310.
–Na_2O–ZrO_2, properties of compounds, application, (5) 136.
Silica-dolomite-soda glass. See *Glass, soda-dolomite lime-silica*.
Silicate glasses. See *Glass, silicate*.
Silicates, zirconium, properties, tabular data, (5) 138.
Silicon in synthetic crystal, six-fold coordination, theory, (4) 101.
Sillimanite, structure, Taylor theory, (1) 3.
Silver glass. See *Glass, colored, silver*.
Slag attack, measurement, chemical, physical, petrographic and miscellaneous methods, (11) 287; outline, (11) 290.
Slag tests, cone fusion, and cone fusion with crucible penetration, (11) 286, (11) 289.
immersion in corrosive fluids, gases, or vapors, (11) 284, (11) 289.
impingement method, (11) 285, (11) 289.
literature review, 1932–1940, 166 references, (11) 290–94.
mathematical measurement, erosion and flow as functions of slag viscosity and refractory solubility in slag, (11) 286.
slag on original surface of test brick, (11), 283, (11) 289.
Slickensides on plastic clay body surfaces, photo, (1) 25.
Slip planes in plastic clay bodies, (1) 25.
Slips, casting. See *Casting slips*.
Soapstone and talc, microscopic studies, Pulfrich and Krause and Leroux studies, (15) 444.
Soda-dolomite lime-silica glass. See *Glass, soda-dolomite lime-silica*.
Soda-lime glass. See *Glass, soda-lime*.
Sodium borate glass. See *Glass, sodium borate*.
Sodium hydroxide for ball-clay treatment, effect on physical properties, (12) 329, (12) 335.
Sodium molybdate, properties and behavior in enamels, (6) 161.
Sodium oxide in sodium-borate glasses, varying amounts of, effect on spectral transmission, transformation temperatures, and physical properties, (14) 395.
–zirconium oxide–silica, properties of compounds, application, (5) 136.
Sodium salts, decomposition by vacuum heating, table, (3) 70.
Solarization tests on glass bottles and jars, and results, (2) 54.
Sonic properties of glass. See *Glass, vibration*.
Soxhlet extractor test, modified for porcelain enamel, process, (6) 166.
Spectral transmission. See *Transmission*.
Spectrophotometers, automatic photoelectric for measuring color changes in sodium borate glass, (14) 395.
electric automatic recording photoelectric type for spectral transmission of glass, (4) 104.
and electrometer, for spectral transmission measurements on soda-lime and potash-soda-lime glasses, (13) 374.
for translucency measurements on hotel chinaware body, photo and description, (4) 118–19; summary of use, (4) 122.
Spheroidizing vs. annealing heat-treatment for chill-cast and sand-cast irons for glassforming molds, microstructure and hard-

Spheroidizing (*continued*)
ness gradients, photomicrographs and curves, (13) 381–88.
Spinel–zirconia, ZrO_2–$MgAl_2O_4$, thermal expansion, density, and microstructure, data, (3) 93.
Spodumene and feldspar (soda and potash) mixes as feldspar substitute in china bodies: chemical analyses and composition, table, (11) 321; P.C.E. values and softening temperatures, melting diagram and table, (11) 322; warpage factor, slump ring method, (11) 322; porosity and shrinkage of semivitreous dinnerware and vitreous hotel china bodies, table, (11) 323; strength, warpage, and impact resistance, effect on vitreous bodies, (11) 324; porosity diagrams, (11) 324–25; advantages, (11) 326.
Steatite, constitution, literature review, (15) 443.
Steatite bodies vs. porcelain bodies, differentiation, (15) 439.
as insulators for high-frequency application, (15) 443.
steatite electrical porcelain, body composition, (1) 18; log stress equilibrium vs. moisture content, curve, (1) 22.
test studies: composition, (15) 445; X-ray patterns, (15) 446, (12) 449–50; heat-treatment, water absorption, and crystal size, relation, curves, (15) 447; microstructure of test bodies, (15) 447–48.
Steatite ceramics, fluxes in, alkaline earth oxides and alkaline earth carbonates as feldspar substitute, (15) 441–42.
low dielectric loss type, chemical composition and dielectric properties, relation, (15) 439; talc and kaolin, chemical analyses, compositions, and firing schedule, (15) 439–40; specific resistance and ratio of reactance to resistance or susceptance to conductance of bodies of MgO–Al_2O_3–SiO_2, RO–Al_2O_3–SiO_2, and MgO–BaO–Al_2O_3–SiO_2, tables and curves, (15) 440–43.
talc-kaolin ratio, alkaline oxides, temperature, effect of variations, (15) 443.
Steel, rimming steel. See *Metals for enamels*.
Stokes' law vs. observed values of particle size of clays, (12) 345.
Stoneware, chemical, body composition, (1) 18; log equilibrium stress vs. moisture content, (1) 21.
Strain in plastic clay masses, creep-test apparatus, (1) 25.
Strength of refractories, transverse test furnace and process, (13) 389–90.
tensile, of glass: fiber method of Schwalbe, Badger, and Silverman, and Smekal method for fracture of glass fibers, (1) 29; see also *Glass, chemical durability*.
tensile, Griffith method, (1) 29.
tensile, of porcelain enamel, effect of iron oxide, (1) 29.
Stress, equilibrium stress data on plastic clay bodies, (1) 26.
in plastic clay masses, clay-compression apparatus, (1) 17–18; strain-rate equations, (1) 18.
Stress-strain data on dark special ball clay, clay flint-mixture, and vitreous electrical porcelain body, (1) 26.
on plastic clay masses, (1) 16; stress-rate effect on yield-point stress, Norton cited, (1) 24.
Sulfur, determination method, (5) 127.
in kiln gases, determination and effect, (14) 417; in bisque ware firing, (14) 418; effect on decalcomania decoration, (14) 419.
Surfaces, specific surface, formula, (12) 346.
Systems. See also *Equilibrium diagrams; Equilibrium studies*.
alumina–boric oxide, cone fusion, pouring temperature, and blistering temperature, curves, (1) 393–94.
calcium oxide–FeO–Al_2O_3–SiO_2, crystalline solid phases, (10) 263–65; crystallization theory, (10) 272.
ferric oxide as liquid phase content, (10) 246.
geology and petrology applications to study, (10) 273.
glasses, refractive indices, method of measurement, (10) 246; tables, (10) 250–65.
melting points, temperatures of completion, tables, (10) 250–65.
microscopic reaults, tables, (10) 250–65.
quenching experiments on five joins, (10) 244–74.

Systems (*continued*)
solid and liquid phases, tables, (10) 250–65.
tie lines and composition planes, (10) 268.
univariant lines, ternary and invariant points in limiting systems and quaternary invariant points, diagram, tables, maximum and minimum points, (10) 265–68.
clay–water and clay OH–Na, effect of yield value of casting slip, (12) 341–44.
ferrous oxide–Al_2O_3–SiO_2, equilibrium, (6) 151; composition melting data and primary crystal phases, (6) 156–57; composition triangles and equilibrium products, (6) 158–59; quenching experiments, (6) 155–59; refractories application, (6) 159; photomicrographs, (6) 155.
limiting, CaO–FeO–SiO_2, CaO–Al_2O_3–SiO_2, FeO–Al_2O_3–SiO_2, and CaO–FeO–Al_2O_3, data and equilibrium diagrams, (10) 242–44.
magnesia–Al_2O_3–SiO_2, portion of phase diagram and chemical composition and dielectric properties, (15) 440–41; MgO–BaO–Al_2O_3–SiO_2, effect of MgO and BaO as flux in steatite bodies, (15) 442–43.
–FeO–SiO_2, electric-furnace study of iron-poor section, vs. Schairer thermal study, (11) 310.
–silica, electric-furnace study: phase diagram, (11) 294; magnesia-flint and olivine-magnesite-quartz series studies, chemical analyses of fusions, furnace charges, and fused products, tables, (11) 295–97; density, melt composition, P.C.E., and mineralogical and petrographic examinations, tables and curves, (11) 297–99.
–ZrO_2, Ebert and Cohn phase relationship and diagram, (5) 132.
–ZrO_2–TiO_2, review of studies, (5) 132.
silica–Na_2O–ZrO_2, d'Ans and Löffler studies and table of properties of two ternary compounds, (5) 136.
soda-dolomite lime–silica, liquidus temperature, effect of Fe_2O_3 substitutions for SiO_2, curves, (14) 403–404.
sodium oxide–CaO·MgO–SiO_2, BaO and ZnO substitutions in glass, effect on expansion coefficient, (3) 65; effect of Fe_2O_3 substitutions, (14) 404.
titania–ZrO_2, review of studies, (5) 132.
zirconia-containing, elements forming refractory oxides, (5) 133.
zirconia–spinel (ZrO_2–$MgAl_2O_4$), thermal expansion, density, and microstructure, (3) 93.

Tableware. See *Chinaware; Dinnerware; Porcelain*.
Talc, experimental studies, process, physical properties, and crystal modifications, (15) 445–49.
kaolin, and feldspar, firing tests, Krause and Jäkel studies, (15) 444.
"metatalk," Thilo modifications, (15) 444; "protoenstatite" of Büssem, (15) 444.
and soapstone, Pulfrich microscopic studies, (15) 444.
thermal decomposition, and conversion, Ewell, Bunting, and Geller studies, (15) 444.
Talc bodies, zircon in, effect, (5) 133.
Talc-kaolin body (steatite ceramics), low dielectric loss type, chemical composition and dielectric properties, relation, (15) 439; chemical analyses, compositions, and firing schedule, (15) 440; specific resistance and ratio of reactance to resistance or susceptance to conductance in bodies of MgO–Al_2O_3–SiO_2, RO–Al_2O_3–SiO_2, and MgO–CaO–Al_2O_3–SiO_2, tables and curves, (15) 440–43.
mixtures, effect on dielectric properties of variations in talc-kaolin ratio, alkaline earth oxides, and temperature, (15) 443.
Talc-pyrophyllite body, effect of flint particle size, thermal expansion and rate-of-change curves, (14) 415.
heat-treatment studies, effect on properties, (2) 41–46.
Tanks, hot-water, protective coatings, zinc vs. porcelain enamel, analyses and tests, (6) 164.
Tantala in glass, glassforming nature, (4) 97.
Temperature, deformation temperature defined, (14) 405.
Tensile strength. See *Strength*.
Thermal conductivity tests for refractories. See *Refractories, thermal conductivity*.
Thermal expansion. See *Expansion*.
Thermal shock. See *Enamels, thermal-shock resistance; Glass, thermal-shock tests*.
Thermal treatments for china bodies and ware, effect on properties, (2) 33.
Thiess Plastograph for plastic clay masses study, (1) 17.
Thorium, thoria, and thorite, characteristics, (5) 138.
Thorium oxide, application, review, characteristics, (5) 138.
Tin compounds in gold ruby glass, effect on glass solubility, (10) 280.
Titania in glass, glassforming nature, (4) 97.
Titanium dioxide–ZrO_2 and TiO_2–MgO–ZrO_2, survey of system, characteristics, and uses, (5) 132–33.
Toepler automatic pump, circuit for operation, photo, (3) 71.
Tone decay of glass bars. See *Glass, vibration decay*.
Torsion-stress of clays, Wilson, Norton, and Graham and Sullivan methods, (1) 17.
Translucency, light transmittance through chinaware bodies, curves, (4) 122.
of whiteware: photronic cell and spectrophotometer for measurement, (4) 116–22; vs. thickness, formula and curves, (4) 119.
Transmission of light. See *Light transmission*.
Transverse test furnace for refractories, test breaking mechanism, formula, and heating chamber, (13) 389; furnace control and temperature equilibrium in test brick, (13) 390.
Tuning-fork test for glazes, compression data and stress curves, (2) 45–46.

Ultraviolet absorption of cerium glasses, review, (5) 141.

Vacuum apparatus for gas analyses in glass, photos and use, (3) 69–76.
Vernadsky equations for decomposition of kaolinite, (1) 2.
Vibration of glass bars, (14) 409; vibration decay vs. chemical composition, test method, (14) 412.
Vicat apparatus, modified, for tests on refractory mortars, description, photo, test results, (15) 460–62; Vicat consistencies with hemispherical- and flat-end plungers, (15) 462; recommendations, (15) 463.
Viscometers, Hommel, description and use, (15) 459–60.
Viscosity vs. plasticity, definitions, (1) 16.
Vitreous chinaware bodies. See *Chinaware*.
Vitreous electrical porcelain. See *Porcelain, electrical*.
Vitreous heatshock ware, body composition, (1) 18; equilibrium stress vs. moisture content, curves, (1) 21; see also *Porcelain, electrical*.
Vitreous ware and semivitreous ware, special types, composition data for stress-strain studies, (1) 18; stress vs. moisture content, curves, (1) 20–23.
Volume measurements, nomograph formula and alignment chart for plastic, dried, and fired samples, (10) 277.
Westman mercury balance and formula, (10) 275.
Volumeters, Goodner mercury displacement vs. improved type, (10) 275.
kerosene overflow type for plastic clay bars, and mercury type for dried and heated bars, (12) 329.
mercury balance, improved: description and photo, (10) 275–76; submersion arm diagram, submersion force equation, accuracy, (10) 276; advantages and disadvantages, (10) 276.
Volumetric methods of Wheeler, Kuechler, Spiers, and Westman, review, (10) 275.

Weathering of commercial glass containers, effect of storage conditions, humidity, temperature, and of capped and uncapped bottles, (13) 359–71.
tests on bottles and fruit jars, and results, (2) 54.
Whiteware. See also *Chinaware; Dinnerware; Earthenware; Porcelain*.
absorption and translucency curves for lepidolite and feldspar mixtures, (4) 121.
clay-flint-feldspar body, flint particle size vs. thermal expansion, curves, effect, (14) 416.
clays for, English and American ball, base-exchange tests, properties and results, (12) 327–36.

Whiteware (*continued*)
moisture expansion and crazing resistance, effect of flint particle size, tables, (14) 415.
plastic clay bodies, Emley test apparatus, (1) 17.
talc-pyrophyllite body, effect of flint particle size, thermal expansion and rate-of-change curves, (14) 415.
translucency, measurements with photronic cell and spectrophotometer, (4) 116–22.
zirconium oxide in, uses, review, (5) 133–34.

X-ray method for mullite determination, process, (1) 4; analyses, tabular data, (1) 8–9; chemical vs. X-ray method, (1) 9.
X-ray studies, boroaluminate, powder diffraction data, (14) 392.
glass, decolorizers in, effect of light, (4) 104.
glass: X-ray diffraction data for atomic determination of K_2O-B_2O_3 types, (3) 83; intensity and radial distribution curves, (3) 85; conclusions, (3) 88.
Zinc coating for hot-water tanks, vs. porcelain enamel, analysis and tests, (6) 164.
Zinc molybdate in enamels, effect, properties, and behavior, (6) 162.
Zinc oxide in glass. See *Glass, zinc oxide.*
Zircon, Washburn and Libman melting diagram cited, (5) 150.
Zirconia, characteristics and review, (3) 93; transformation on cooling vs. molecular composition and effect on length, curve and table, (3) 94; specific volume vs. composition, curve, (3) 95.
and spinel, thermal expansion, curves, (3) 94; structure, photomicrograph, (3) 95.
Zirconia–magnesia spinel system, thermal expansion, density, and microstructure, studies, (3) 93.
–spinel system, thermal-expansion measurements, effect on stable compounds and solid solutions, (3) 95.
Zirconium, elemental, sources, characteristics and uses, (5) 129–30.
Zirconium boride, characteristics, McKenna studies, (5) 133.
Zirconium carbide, characteristics and uses (5) 133.
Zirconium compounds, properties and studies of ZrO_2 systems, (5) 129–41; refractive indices, comparison, (5) 137.
Zirconium oxide, bibliography, 85 references, (5) 139–41.
elemental, and ZrO_2 minerals, uses, (5) 130–31; properties, expansion curves, history, (5) 131–32.
in enamel frits and glazes, stability and solubility, (5) 136–37.
–MgO, TiO_2–ZrO_2, MgO–ZrO_2–TiO_2, and other systems containing ZrO_2, survey, characteristics, review, (5) 132–33.
as opacifier in frits and glazes, solubility of, rules governing, (5) 137.
for refractories, characteristics and uses, (5) 132–34.
vs. silica glass, melting point, (5) 131.
stability, limits in several ternary fields (Löffler), (5) 137.
Zirconium silicates, properties, tables, (5) 138

FOOTNOTE CITATIONS INDEX TO THE JOURNAL*

Volume 25, 1942

The reference number in parentheses refers to the *monthly* issue of *The Journal;* the number following is the *page* number (the issue numbers are (1) through (16) for 1942).

Abbott, G. H., investigations and modern ideas on enamel control, (7) 215.
Allen, E. T., White, W. P., Wright, F. E., and Larsen, E. S., diopside, relation to calcium and magnesium metasilicates, (15) 443.
Allen, E. T., Wright, F. E., and Clement, J. K., minerals of composition $MgSiO_3$, case of tetramorphism, (15) 443.
Allen, E. T., and Zies, E. G., contribution to methods of glass analysis with special reference to boric acid and two oxides of arsenic, (3) 69.
American Ceramic Society, Committee on Chemical Durability of Glass, report, (3) 63, (6) 166; Standards Report, (3) 90, (9) 232, (14) 414.
American Chemical Society, specifications recommended by Committee on Analytical Reagents, (13) 373.
American Society for Testing Materials, Comm. C-8 on Refractories, report, (11) 290; designation C16-39T, (4) 112; designation C135-38T, (11) 297; hydrostatic pressure test on glass containers, C147-39T, (15) 434; hydrostatic pressure test on glass containers, revised, C147-40T, (2) 55, (15) 434; report of Comm. E-1 on manual of presentation of data, 1933, (15) 463; tentative method of testing fire clay and alumina-diaspore refractories under load at high temperatures, (13) 389; tentative method of thermal shock test on glass containers, C149-40T, (2) 54, (15) 435; tentative test for slagging action of refractory materials, C17-17T, (11) 290.
Andersen, Olaf, magnesia refractories in basic open-hearth steel furnaces, (11) 308; system anorthite–forsterite–silica, (10) 248.
Andersen, O., and Bowen, N. L., binary system MgO–SiO_2, (15) 443.
Andrews, A. I., enamels, (1) 29.
Andrews, A. I., and Coffeen, W. W., comparison of tensile strengths of sheet-iron ground-coat enamel glasses, (1) 29.
Andrews, A. I., and Gates, R. W., solubility of ZrO_2 opacifier in enamel glasses, (5) 138.
Andrews, A. I., and Hertzell, E. A., effect of furnace gases on quality of enamels for sheet steels, (14) 419.
Ao, Takeo, studies of thermal and chemical changes of Kato kaolin, (1) 1.
A. P., carbon brick, (11) 320.[43]
Arbogast, Philip, patent on glassblowing apparatus, (15) 427.
Arndt, E., and Puetter, K. E., importance of lanthanum, (5) 143.
Arnold, H., production of highly refractory ware, (5) 138.
Arsem, W. C., electric vacuum furnace, (4) 113.
Audley, J. A., use of ZrO_2 as refractory material, (5) 139.
Austin, J. B., physics and chemistry of firing ceramic ware, (2) 40; symposium on thermal insulating materials, (15) 451
Austin, J. B., and Day, M. J., chemical equilibrium and control of furnace atmospheres, review of equilibrium data, (11) 320.[55]
Austin, J. B., and Pierce, R. H. H., description of thermal conductivity apparatus, (15) 451; reliability of measurements of thermal conductivity, (15) 451.
Austin, M. M., granular carbon resistor furnace, (4) 112.

Babcock, C. L., surface-tension measurements on molten glass by modified dipping cylinder method, (6) 169.
Badger, A. E., Parmelee, C. W., and Williams, A. E., surface tension of various molten glass, (6) 169.
Bailey, E. G., action of slag from fuel in boiler furnaces, (11) 290.
Bailey, James, on chemical durability, (2) 55.
Bair, G. J., constitution of lead oxide-silica glasses, I–II, (3) 86.
Bancroft, W. D., applied colloid chemistry, (1) 16.
Bardenheuer, P., and Thanheiser, G., investigations on pickling low carbon steel sheet, (7) 215.
Barker, G. J., and Truog, Emil, improvements of stiff-mud clays through pH control, (12) 346.
Barrett, E. P., and Taylor, J. A., method for studying flow characteristics of glasses and slags at elevated temperatures, (11) 290.
Barrett, L. R., rehydration of fired brick clays, (4) 109.
Barton, L. E., composition of matter and method of producing, (5) 139.
Bartsch, Otto, action of sodium sulfate on refractory materials, (11) 290; determination of slag attack by crucible method, (11) 290.
Baudewyns, J., attack of refractory materials used in glassmaking, (11) 290.
Bauer, A., zircons of low density, (5) 139.
Baukloh, W., and Retzlaff, W., diffusion of hydrogen through steel during electrolytic pickling, (7) 215.
Baukloh, W., and Zimmerman, G., diffusion of hydrogen through steel during electrolytic pickling, (7) 215.
Bayer, R., preparation of containers from ZrO_2, (5) 139.
Beattie, C. L., failure of blast-furnace linings, (11) 320.[70]
Becker, C. A., chemical and physical investigation on beryllium glasses, (4) 100.
Beljankin, D., classification of mullite, (1) 3.
Bell, W. C., evaluation of glaze-fit test methods, (9) 232.
Benedicks, C., allotropy in general and that of iron in particular, (3) 96.
Benner, R. C., and Baumann, H. N., Jr., refractory material, (14) 391.
Berg, H. A., blast-furnace developments in 1928, (11) 319.[33]
Berry, E. R., clear, fused quartz made in electric furnace, (11) 298.
Betz, G. C., zircon as ceramic material, (5) 139.
Biltz, W., and Lemke, A., γ-Al_2O_3 and spinels, (1) 2.
Biscoe, J., X-ray study of soda-lime-silica glass, (4) 102.
Biscoe, J., Druesne, M. A. A., and Warren B. E., X-ray study of potash-silica glass, (4) 102.
Biscoe, J., and Warren, B. E., X-ray diffraction study of soda-boric oxide glass, (3) 84, (14) 395.
Blacet, F. E., and Leighton, R. A., microanalysis of gases, (3) 77.
Blacet, F. E., and Volman, D. V., microanalysis of gases, nitrous oxide and methane, IV, (3) 77.
Blakely, A. M., life history of glaze, maturing of whiteware glaze and measurements of stress in cooling glaze, I–II, (1) 11.
Bleininger, A. V., process of forming ceramic products, (12) 337.
Bleininger, A. V., and Ross, D. W., flow of clay under pressure, (1) 16, (12) 340.
Boehm, J., recalescence of some metal oxides, (5) 139.
Bogoroditskii, N. P., and Fridberg, I. D., dielectric losses at high frequencies, (15) 441.
Bole, G. A., mechanism of plasticity from colloid standpoint, (1) 16, (9) 227.
Booze, M. C., fire-clay brick for open hearth, (11) 290; refractories for blast furnaces and coke ovens, (11) 320.[67]
Booze, M. C., and Flint, F. C., checker-brick for resisting alkaline slags, (11) 290.
Booze, M. C., and Klein, A. A., rapid means for determination of quartz content of feldspars, (14) 421.
Bouma, F. J., Neophane glass (Philiphan), (5) 142.
Bowen, N. L., certain singular points on crystallization curves of solid solutions, (10) 272; crystallization of haplobasaltic,

* Superscript numbers occurring with page number indicates a *Bibliography reference number:* these are used only when an alphabetical sequence in a bibliography has not been followed.

haplodioritic, and related magmas, (10) 272; ternary system diopside–forsterite–silica, (10) 272.
Bowen, N. L., and Andersen, O., binary system MgO–SiO_2, (11) 294.
Bowen, N. L., and Greig, J. W., system Al_2O_3–SiO_2, (1) 3, (6) 152, (10) 244.
Bowen, N. L., and Posnjak, E., magnesian amphibole from dry melt, correction, (15) 443.
Bowen, N. L., and Schairer, J. F., crystallization equilibrium in nepheline–albite–silica mixtures with fayalite, (10) 241, (10) 246; system FeO–SiO_2, (6) 152, (10) 241, 243–44, 246, 253, 265, and 274; system MgO–FeO–SiO_2, (10) 241, (11) 294; system albite–fayalite, (10) 241.
Bowen, N. L., Schairer, J. F., and Posnjak, E., system CaO–FeO–SiO_2, (6) 151, (10) 241, 244, 246, 256, 262, 265, 266, 270, 272, and 274; system Ca_2SiO_4–Fe_2SiO_4, (6) 155, (10) 241.
Bowen, N. L., Schairer, J. F., and Willems, H. W. v., properties of glass cited by G. W. Morey, (4) 103.
Bowes, U. E., communication on production rate of bottles, (15) 428.
Bowmaker, E. J. C., method of testing probable durability of tank blocks, (11) 290.
Boyd, J. E., pyrometric properties of spodumene-feldspar mixtures, (11) 321.
Bradshaw, L., and Emery, W., comparative tests of machine-made and hand-made brick, (11) 320.[46]
Bragg, W. L., atomic structure of minerals, (4) 99, (4) 103, (6) 151.
Brennan, J. J., effect of coal ash on refractories, (11) 290.
Brode, W. R., absorption spectra of cobaltous compounds, alkali oxide-boric oxide glasses, IV, (14) 399.
Brongniart, A., Traité des Arts Céramique, (12) 336.
Brown, G. H., method of testing corrosive action of slags on firebrick, (11) 290.
Bruckner, W. H., Kovac, L. R., and Wilder, A. B., metallurgical study of cast-iron glass molds, (13) 382.
Bryson, F. F. S., distribution of temperature and block corrosion in glass tank furnaces, (12) 355.
Budnikov (Budnikoff), P. P., destruction of grog brick by carbon monoxide, (11) 319[38]; determining slag resistance of refractories, (11) 290; increasing chemical resistance of refractories for glass tanks, (1) 1; investigation of properties of kaolin fired to different temperatures, (1) 2; testing stability against slag, (11) 290.
Budnikov, P. P., and Hisch, B. A., mullitization of refractory grog material, (1) 1.
Budnikov, P. P., and Zhikharevich, S. A., choice of chemically resistant refractory materials for sodium sulfide furnaces, (11) 290.
Burch, O. G., and Babcock, C. L., effect of glass color on setting rates in manufacture of glass bottles, (12) 355.
Büssem, W., Schusterius, C., and Stuckardt, K., constitution of steatite, glass phase, II, (15) 444; X-ray investigations of binary systems, TiO_2–MgO, ZrO_2–MgO, ZrO_2–TiO_2, (5) 139.

Campbell, N. R., method for microanalysis of gases by Pirani gauge, (3) 77.
Campbell, R. M., promotion of interfacial reactions to counteract crazing, (1) 11.
Chamot, E. M., and Mason, C. W., handbook of chemical microscopy, (3) 81.
Charrin, V., synthetic superrefractories, (5) 139.
Chesters, J. H., and Howie, T. W., fire-clay brick for iron- and steel-works, (11) 290.
Chesters, J. H., and Lee, L., slag resistance of steelworks refractories, (11) 290.
Chesters, J. H., and Lynam, T. R., chrome-magnesite brick for open-hearth furnaces, (11) 290.
Chesters, J. H., and Parmelee, C. W., measurement of reaction rates at high temperatures, (12) 351.
Chipman, John, and Shadburn, Marshall, equilibrium $FeO+H_2=Fe+H_2O$ up to melting point of iron, (10) 253.
Chudoba, K., green color of zircon, (5) 139; hardness of zircon, (5) 139.
Chudoba, K., and Stackelberg, M. v., density and structure of zircon, II, (5) 139.
Clark, G. L., and Reynolds, D. H., chemistry of ZrO_2, X-ray diffraction studies, (5) 139; quantitative analysis of mine dusts, X-ray diffraction method, (1) 4.
Clements, F., blast-furnace practice, (11) 319[34]; modern British furnaces, (11) 320.[46]
Clevenger, C. B., rapid and convenient method for preparation of conductivity water, (5) 144.
Clews, F. H., Chadeyron, A., and Green, A. T., Action of alkalis on refractory materials: action of potassium chloride vapor on refractory material at 1000°C. in presence of water vapor and air, IV, (11) 290.
Clews, F. H., Green, A., and Green, A. T., action of alkalis on refractory materials: action of potash vapor on refractory materials at 900° and 1000°C., I, (11) 290, (11) 320[31]; action of potassium chloride vapor on refractories materials at 1000°C., II, (11) 290; volatilization from alkali-impregnated refractory materials at 1000° and 1100°C., III, (11) 290.
Clews, F. H., and Green, A. T., action of alkalis on refractory materials: further observations on action of potassium chloride vapor on refractory materials, at 1000°C., V, (11) 290–91; summary, I–IX, (11) 291, (11) 320[31]; permeability of refractory materials to gases, (11) 320; significance of permeability to gases in relation to texture and industrial usage of refractory materials, (11) 319.[38]
Clews, F. H., Richardson, H. M., Chadeyron, A., and Green, A. T., action of vapors of potash-silica glass on refractory materials at 1200°C., VI, (11) 291.
Clews, F. H., Richardson, H. M., and Green, A. T., action of alkalis on refractory materials: aspects of action of alkali chloride vapors on refractory materials at 1000°C., VIII, (11) 291; experiments on action of vapor from sodium aluminate and sodium carbonate at various temperatures, IX, (11) 291; examination of reactions on NaCl vapor with refractory materials at 1000°C., and conditions leading to volatilization of brick constituents, X, (11) 291, (11) 320[31]; experiments on alterations in strength when refractory materials are exposed to KCl vapor at 1000°C., XI, (11) 291, (11) 320.[31]
Coad-Pryor, E. A., notes on pot attack, (11) 291.
Cobb, J. W., and Committee, standardization of tests for refractory materials, (11) 291.
Coggeshall, A., and Bleininger, A. V., convenient carbon-resistance furnace, (4) 112.
Cohn, W. M., crystal modification of zirconia, clear fused zirconia produced in sun furnace, (5) 139; expansion behavior of differently prepared zirconium dioxides in temperature area 0°–1400°C., (3) 93, (5) 139.
Cohn, W. M., and Tolksdorf, S., dependence of structure of zirconia on previous heat-treatment, (3) 93.
Cole, S. S., and Taylor, N. W., system Na_2O–B_2O_3, I, (14) 391.
Comings, E. W., and Sherwood, T. K., drying of solids: moisture movement by capillarity in drying granular materials, VII, (14) 422.
Commons, C. H., Jr., effect of Zircopax (zirconium silicate) on abrasion resistance and various properties of several glazes, (5) 139; recent developments in zirconium glazes and effect of various materials on results, (5) 139.
Comstock, G. F., experiments with zircon and zirconia refractories, (5) 139.
Cone, C., heat transfer in glass tanks, (12) 355.
Cooke, R. D., effect of muffle atmosphere on firing enamels, (7) 215; manufacture of enameled ware, (7) 215.
Cooper, H. S., enamel composition, (5) 142.
Cowdrey, I. H., and Adams, R. G., materials testing, (12) 340.
Cox, G. L., effect of temperature on corrosion of zinc, (6) 164.
Cronshaw, H. B., standardization of refractory materials in iron and steel industries, (11) 291.
Crook, W. J., series iron oxides-silica, (1) 274.
Crookes, W., coloration of glass by natural solar and other radiations, (4) 104; preparation of eye-preserving glass for spectacles, (5) 141.
Cross, A. H. B., and Rees, W. J., further investigation of basic refractories for steelmelting furnaces, I, (11) 291.
Cross, C. L., color of glass in ultraviolet light, (4) 107.
Čtyroký, V., glasses colored with neodymium oxide and vanadium oxide, (5) 142; importance of rare earths for glass industry, (5) 142.

Dale, A. J., testing refractory materials for resistance to slag corrosion and erosion, (11) 291.
Dalton, R. H., extraction and analysis of gases from glass, (3) 69; gases in glass, (3) 69.
Danielson, R. R., and Sweely, B. T., relation between composition and properties of enamels for sheet steel, (15) 463.
D'Ans, J., and Löffler, J., studies on system Na_2O–SiO_2–ZrO_2, (5) 138.
Davey, W. P., structure of zirconia, (5) 139.
Dear, P. S., soda-ash foundry-slag attack on refractory lining of teapot-type reservoir ladle, (11) 291.
Deneuville, opacification of enamels by zirconium oxides, (5) 139.
Deutsche Ton- und Steinzeug-Werke A.-G., mullite, (1) 1.
Diepschlag, E., and Feist, K., disintegration of blast-furnace refractories by carbon monoxide, (11) 319.[38]
Dietzel, A., strains in glazes as influenced by reactions between glaze and body, (1) 11; theory of decolorizing with selenium, (13) 372.
Dietzel, A., and Meures, K., reactions important for adherence when firing ground coats containing no adhering-promoting oxides, (9) 217.
Dimbleby, V., English, S., Firth, E. M., Hodkin, F. W., and Turner, W. E. S., transparent zirconia-containing glasses, (5) 139.
Dimbleby, Violet, Gill, H. S. Y., and Turner, W. E. S., effect of storage on chemical durability of glass containers, (13) 359.
Dimbleby, Violet, and Turner, W. E. S., effect of humidity on weathering of bottle glasses, (13) 359; relation between chemical composition and resistance of glasses to action of chemical reagents, I, (5) 139.
Dodd, A. E., action of slags on refractories and methods of testing, (11) 291.
Dodd, A. E., and Green, A. T., refractories in production of steel by basic open-hearth process, casting pit refractories, II, (11) 291.
Donoho, C. K., and MacKenzie, J. T., effect of fluxes on cupola linings, (11) 291.
Dornte, R. W., and Ferguson, C. V., solubility of nitrogen and oxygen in liquid sulfur dioxide, (3) 79.
Drosbach, P., decolorization of glass with rare earths, (5) 141.
Dutton, C. A., and Wagner, B. F., zirconium oxide in glasses and enamels, II, (5) 139.

Ebelman, J. J., syntheses of artificial crystals, (14) 391.
Eberlin, L. W., optical glass, (5) 139; rare earth borate compositions, (5) 142.
Ebert, F., and Cohn, E., phase diagram MgO–ZrO_2, (5) 139.
Ebright, H. E., McIntyre, G. H., and Irwin, J. T., study of furnace atmospheres and temperature gradients and their effect on porcelain enameling, (14) 420.
Eckert, F., peculiar case of color change and luminescence in glass, (4) 105.
Eitel, W., sillimanite-mullite problems, (1) 3.
Eitel, W., and Lange, B., determining radiating power of glass, (12) 355.
Eitel, W., and Skaliks, W., Doppelcarbonate der Alkalien und Erdalkalien, (4) 98.
Ellis, S. B., and Keil, S. J., purification of water and pH value, (5) 144.
Emley, W. E., instrument for measuring plasticity, (1) 17.
Emmel, K., enameling cast iron, (7) 215.
Emmons, R. C., double-dispersion method of mineral determination, (9) 217.
Endell, K., slagging process of refractory brick, (11) 291.
Endell, K., Fehling, R., and Kley R., influence of fluidity, hydrodynamic characteristics and solvent action of slag on destruction of refractories at high temperatures, (11) 291.

Endell, K., and Wens, C., relation between attack on fire clay and density and fluidity of glasses and slags at high temperatures, (11) 291; temperature-viscosity relation of coal slags, methods of investigation and results, I, (11) 291.

English, S., natural sillimanite as glass refractory material, (11) 291.

English, S., Howes, H. W., Turner, W. E. S., and Winks, F., influence of iron oxide on properties of glass, (12) 355.

Enss, J., analysis of gases in glass bubbles, (3) 77.

Esmé, A., thorium oxide, high-quality refractory, (5) 139; irconium compounds and their relation in the refractory and ceramic industry, (5) 139.

Esse, effect of frost and humidity on resistance to pressure of paving brick, (4) 110.

Evans, U. R., report on corrosion research work at Cambridge University interrupted by outbreak of war, (7) 215.

Ewell, R. H., Bunting, E. N., and Geller, R. F., thermal decomposition of talc, (15) 444.

Ewell, R. H., and Insley, Herbert, hydrothermal synthesis of kaolinite, dickite, beidellite, and nontronite, (4) 109, (12) 335.

Faber, A., extraction of sulfur dioxide from flame gases by glasses and glazes, (14) 420.

Fabianic, W. L., observations on slagging of glass-furnace checkers, (11) 291.

Fairchild, C. O., and Peters, M. F., characteristics of pyrometric cones, (4) 113; patent citation, (5) 139.

Faulkner, L. R., slagging action of fuel-oil ash, (11) 291.

Fehling, R. H., erosion of refractories by coal slag, (11) 291.

Fellows, R. L., and Howe, E. E., effect of mill additions on thermal expansion of sheet-iron ground coats, (15) 463.

Ferguson, R. F., discussion on "slag tests and action of slag on silica, magnesite, chrome, diaspore, and fire-clay refractories," by R. M. Howe, S. M. Phelps, and R. F. Ferguson, (11) 291; review of literature on laboratory slag test for refractories, (11) 291.

Fessler, A. H., and Navratiel, Hans, effect of different fluxing oxides on constitution of porcelain, (1) 7.

Fettke, C. R., magnesite refractories cited by J. S. McDowell and R. M. Howe, (11) 308.

Fettke, C. R., and Stewart, W. E., slagging action of western Pa. coals on different types of refractories in small pulverized coal installation, (11) 291.

Fieldner, A. C., annual report of research and technological work on coal, fiscal year, 1938, studies of slag-forming and ash-fusion properties, (11) 291.

Finck, J. L., on conductivity, (15) 451.

Firmstone, F., alteration of firebrick by furnace gases, (11) 318.[9]

Firth, E. M., Hodkin, F. W., Muirhead, C. M., Parkin, M., and Turner, W. E. S., study of effects of chlorides on melting and working properties of potash-lead oxide-silica glasses, (10) 278.

Firth, E. M., Hodkin, F. W., Turner, D., and Turner, W. E. S., corrosion of fire clay by alkali-lead oxide glasses, (11) 291.

Firth, E. M., Hodkin, F. W., and Turner, W. E. S., effect of saltcake in soda-lime batches in corroding fire-clay refractory materials, (11) 291; production of opalescence by chlorides in potash-lead oxide-silica glasses, (10) 278.

Fisher, H. D., looking for a brick, (11) 291.

Fisher, R. A., statistical methods for research workers, (15) 437.

Fisk, H. G., and McCaughey, W. J., equilibrium studies in systems containing magnesium oxide, iron oxide, and magnesium aluminate, (11) 308.

Fleiger, A. G., use of palladium tube in gas analysis, (3) 75.

Foote Mineral Co. Research Department, resistance of Zirkite to slag corrosion, (5) 139.

Ford, K. L., weathering of glass containers, (13) 359.

Ford, W. E., Dana's textbook of mineralogy, (6) 155.

Forgue, S. V., and Loomis, G. A., modulus of elasticity of dinnerware bodies by the sonic-vibration method, (3) 90, (14) 411.

Foshag, W. F., problems in study of meteorites, (11) 310.

Fraas, Foster, and Ralston, O. C., beneficiation of spodumene by decrepitation, (11) 321.

Freed, M. L., study of mullite refractories formed by calcining cyanite (kyanite), industrial application, (11) 291.

Fritz, E. H., and Harrison, H. C., effect of thermal history on physical properties of electrical porcelain, (2) 38.

Fulcher, G. S., analysis of recent measurements of viscosity of glasses, II, (3) 63.

Furnas, C. C., kinetics of some reactions of interest to ceramists, disintegration of blast-furnace linings due to carbon deposition, (11) 319.[42]

Geer, W. C., crystallization in 3-component systems, (10) 272.

Gehlhoff, G., Schneeklоth, W., and Thomas, M., currents and temperatures in glass tanks, I, (12) 355.

Geisinger, E. G., and Berlinghof, K., effect of furnace gases on glass enamels, (14) 418.

Geller, R. F., effect of repeated heatings on mechanical strength of high-tension insulator porcelains, (2) 40; laboratory testing of aluminous refractories, (11) 291; testing fire-clay brick with coal-fired boiler setting, (11) 291.

Geller, R. F., and Creamer, A. S., effect of feldspar in pottery bodies, (4) 117.

George, H., and Lambert, R., dissociation of zircon, (5) 139.

German Standard Slag Test, D. I. M., 1069, (11) 291.

Gilard, P., tests for slagging of refractory materials, (11) 291.

Gilard, P., and Dubrul, L., bases physico-chimiques de l'industrie du verre, (4) 100; calculating coefficient of expansion of silicate glasses, (4) 100; calculation of physical properties of glass, index of refraction, III, (4) 100, (9) 217.

Gilard, P., and Lecrenier, A., influence of various radiations on color of glasses, (4) 107.

Gill, J. H., tests on mullite refractories, (11) 291.

Gillett, H. W., features of ductile zirconium and titanium, (5) 139.

Giusca, D., crystal chemistry of simple rare earth silicates, (5) 143.

Goldman, F. H., hydrofluosilicic acid method for determination of quartz, (14) 420.

Goldschmidt, V. M., geochemical distribution laws of elements: researches on structure and properties of crystals, VIII, (4) 101, (5) 139.

Golovatnii, R. N., effect of chemical composition of refractories on separation of C according to reaction $2CO \rightleftarrows CO_2 + C$, (11) 319.[43]

Golovatnii, R. N., and Smolyanitzkii, I. A., changes in chemical composition of refractories for blast-furnace use during service, (11) 319.[44]

Gooding, E. J., decolorizing of glass, review, (13) 371.

Gooding, E. J., and Murgatroyd, J. B., investigation of selenium decolorizing, (4) 107, (13) 371.

Gooding, E. J., and Turner, W. E. S., study of series of glasses containing sodium oxide, boric oxide, and silica, (3) 87, (14) 397.

Goodner, E. F., mercury volumeter, (1) 275.

Gould, R. E., Toole, M. G., and Nelson, M. S., electric kilns and furnaces, (9) 239.

Grady, R. F., comments on diffusion combustion, (14) 420.

Graham, R. P., and Sullivan, J. D., critical study of methods of determining exchangeable bases in clays, (12) 338; improved machine shows different forms of failure in clay bodies in torsion, (1) 17; workability of clays, (1) 17.

Granger, M. A., zirconia, (5) 139.

Green, H., further development of plastometer, practical application to research and routine problems, (1) 16.

Green, A. T., Hugill, W., and Ellerton, H., blast-furnace linings, preliminary results of examination of brick taken from furnaces off for relining, (11) 319.[47]

Greig, J. W., immiscibility in silicate melts, (10) 244, (10) 253, (11) 294; liquid immiscibility in system $FeO-Fe_2O_3-Al_2O_3-SiO_2$, (10) 253.

Griffith, A. A., phenomena of rupture and flow in solids, (1) 29.

Grim, R. E., relation of composition to properties of clays, (12) 344, (12) 351.

Gruner, M. L., studies of blast-furnace phenomena, (11) 318.[1]

Guestrow Co. (Chem. Fabrik), preparing opacified glasses and enamels characterized by use of ZrO_2 and substances carrying ZrO_2 as opacifier, (5) 139.

Hägg, G., vitreous state, (4) 97.

Haff, R. S., Dear, P. S., and Whittemore, J. W., corrosion of refractories by soda-ash foundry slag, (11) 291.

Hahner, Clarence, Voigt, G. Q., and Finn, A. N., gases in optical and other glasses, (3) 69.

Hall, F. P., casting of clayware, résumé, (12) 337.

Hall, F. P., and Insley, H., compilation of phase-rule diagrams of interest to ceramist and silicate technologist, (15) 440.

Halle, R., Preston, R., and Turner, W. E. S., distribution of temperature in molten masses of colored and colorless glasses, (12) 355.

Hanawalt, J. D., Rinn, H. W., and Frevel, L. K., chemical analysis of X-ray diffraction, classification and use of X-ray diffraction and X-ray diffraction pattern, (1) 10.

Hancock, W. C., and King, W. E., note on abrasion of fire-clay materials, (11) 320.[48]

Hankinson, J. E., boiler-furnace refractories, discussion by E. B. Powell, (11) 291.

Hansen, J. E., and Irwin, J. T., nickel dip in enameling practice, (7) 215.

Haraldson, H., Beitrage zur Kenntnis der Thermischen Umbildung des Talks (contribution on status of thermal decomposition of talc), (15) 444.

Harbert, C. J., less familiar elements in ceramic pigments, (5) 139.

Hare, W. A., and Solér, Gilbert, deoxidation type inclusions in alloy steels, (6) 158.

Harkort, H., effect of particle size of quartz on properties of whiteware bodies, (14) 413.

Harman, C. G., and Frealini, Felix, properties of kaolinite as function of particle size, (12) 344.

Harrison, W. N., Shelton, S. M., and Wadleigh, W. H., strength and Young's modulus of some ground-coat enamels for sheet iron, (1) 29.

Hartmann, F. (Fritz), action of alkalis on refractory brick, (11) 291; destruction of blast-furnace linings (11) 319[45]; method for quantitative determination of action of slag and flue dust on refractory brick, (11) 291; viscosity of Siemens-Martin slag, (11) 291; viscosity of slags, application to slagging of refractory brick, (11) 291–92.

Hartmann, M. L., and Hougen, O. A., physical characteristics of refractories: spalling losses and cold and hot abrasion tests, I–II, (11) 320.[57]

Hartmann, M. L., Westmont, O. B., and Weinland, C. E., thermal conductivity apparatus, (15) 451.

Hartshorn, L., critical résumé of work on dielectrics, (15) 439.

Hassel, O., crystal chemistry, (4) 98.

Hauser, E. A., colloid chemistry in ceramics, (9) 223, (12) 339.

Hauser, E. A., and Hirshon, S., behavior of colloidal suspension with electrolytes, (9) 224, (12) 339.

Hauser, E. A., and Johnson, A. L., plasticity of clays, (12) 338.

Hay, R., White, James, and Caulfield, T. H., ternary system $FeO-Al_2O_3-SiO_2$, (6) 152, (10) 244.

Hay, R. A., McIntosh, B., Rait, J. R., and White, J., slag systems, $FeO-Al_2O_3$ and $FeO-MnO-Al_2O_3$, (11) 292.

Hebestreit, O., dependence of slagging of firebrick on flux content and porosity, (11) 292.

Heilman, R. H., thermal conductivity apparatus, (15) 451.

Heilman, R. H., and Bradley, R. S., thermal conductivity apparatus, (15) 451.

Heindl, R. A., thermal expansion of refractories to 1800°C., (5) 139.

Hendricks, S. B., and Jefferson, M. E., structure of kaolin and talc-pyrophyllite hydrates, bearing on water sorption of clays, (9) 224.

Hepplewhite, J. W., effect of ZrO_2 and TiO_2 on resistance to crazing of typical glaze for semivitreous dinnerware, (5) 139.

Heraeus, W. C., Co., process for melting silica glass from rock crystal, (5) 139.

Herrmann, W., zircon blocks for metallurgical furnaces, (5) 139.
Herty, C. H., physical chemistry of steel-making, (6) 152.
Herty, C. H., Jr., slag viscosity control, (11) 292.
Hessinger, F., methods of testing tank brick, (11) 292.
Heuer, R. P., prevention of disintegration of blast-furnace linings, discussion, (11) 319[35]; petrographic, fusion, and slag studies of magnesite refractories in rotary kiln service (11) 292.
Hewitt, L. C., fusion points of firebrick coal-ash mixtures, (11) 292.
Hibbott, H. W., and Rees, W. J., influence of cyanogen on reduction of carbon monoxide in contact with refractory materials, (11) 319.[44]
Hidnert, Peter, and Sweeney, W. T., thermal expansion of magnesium and some of its alloys, (3) 90, (9) 232.
Higgins, W. W., and Deringer, W. A., investigation of fish-scale phenomena, (7) 215.
Hillringhaus and Heilmann, ZrO_2 as enamel opacifier, (5) 139.
Hilpert, S., and Dieckmann, T., iron carbides, catalytic action on decomposition of carbon monoxide, (11) 319.[12]
Hind, S. R., study of factors involved in slip casting, (12) 337.
Hirsch, H., slag action on refractory linings, (11) 292.
Hirsch, M., attack on firebrick by slagging, (11) 292.
Hixon, A. W., and Leudeke, V. D., wall friction in liquid agitation systems, (11) 292.
Hoar, T. P., study of cathodic reactions in metallic corrosion, (7) 215.
Hoch, E. T., power losses in insulating materials, (15) 439.
Höfler, W., verhalten das Selen im Glase (behavior of selenium in glass), (13) 372.
Höfler, W., and Dietzel, A., Anlaufen der Seleneisengläser und seine Bedeutung für die Entfärbung mit Selen (warming in of selenium-iron glasses and significance in decolorizing with Se), (13) 372; Verfärbung von Selengläsern im Kühlofen (selenium glass in annealing oven), (13) 372.
Hoffman, H. O., and Hayward, C. R., metallurgy of copper, smelting in blast furnace, (11) 320.[68]
Hoffmann, J., chemical changes caused in glasses by light and heat, (4) 107.
Hohl, G. M., brick column lifts furnace top, (11) 318.[7]
Holgersson, Sven, röntgenographic examinations of minerals of spinel group and of synthesized substances of spinel type, (5) 153.
Holland, A. J., and Preston, Eric, microscopic examination and identification of crystalline products in commercial glasses, (3) 83.
Holland, A. J., and Turner, W. E. S., investigation into variation with temperature on spectral transmission of glasses: transmission in visual spectral region from 20° to softening point, I, (14) 399.
Holmquist, P. J., precipitation of carbon on blast-furnace brick, (11) 319.[27]
Holscher, H. H., expansion of ceramic bodies caused by liquid and vapor penetration, (14) 413.
Hommel, O., art of making enamelware, (7) 215.
Horak, William, and Sharp, D. E., influence of ZrO_2 on elasticity of soda-lime glasses, (5) 139.
Horning, R. A., thesis on rehydration of surface clays, (4) 109.
Houldsworth, H. S., properties of clay-sillimanite mixtures, (11) 292.
Houwink, R., elasticity, plasticity, and structure of matter, (9) 227.
Howard, F. C., carbon deposition near furnace top, (11) 319.[21]
Howe, E. E., some sheet-iron enamel defects traceable to base metal or metal-forming operation, (7) 215.
Howe, R. M., blast-furnace refractories, (11) 320[61]; blast-furnace refractories, appendix, (11) 319[12]; disintegration of blast-furnace linings, discussion, (11) 319[18]; how slag temperatures affect brick, (11) 292; study of slag test, (11) 292; testing refractories, (11) 292; tests in vogue for refractories, (11) 292.
Howe, R. M., Phelps, S. M., and Ferguson, R. F., action of slag on silica, magnesite, chrome, diaspore, and fire-clay refractories, (11) 292.
Hubbard, D. E., and Rees, W. J., dissociation of carbon monoxide in contact with refractory materials, (11) 319.[38]
Hugill, W., Ainsworth, R. L., and Green, A. T., action of slags on refractories: observations on corrosive action of lime on aluminous, fire-clay, and silica brick, II, (11) 292.
Hugill, W., Ellerton, H., and Green, A. T., action of carbon monoxide on refractory materials: experiments on disintegration of fire-clay products by carbon monoxide, I, (11) 319[37]; further experiments on disintegration of fire-clay products by carbon monoxide, II, (11) 319[37]; experiments (*a*) with laboratory-prepared specimens and (*b*) influence of reheating disintegrable products, III, (11) 319[37]; deposition of carbon on certain ferruginous substances, IV, (11) 319.[37]
Hugill, W., and Green, A. T., action of slags on refractory materials: application to study of action of $CaO–Al_2O_3–SiO_2$ slags on refractory materials, I, (11) 292.
Hunt, W. F., improved Wentworth recording micrometer, (11) 307.
Hunter, R. G., application of Stokes' law in determination of absolute viscosity of glass, (3) 63, (6) 169.
Hursh, R. K., laboratory slagging test for boiler-furnace refractories, FSP 51–44, (11) 292; laboratory slagging test furnace with rotating burner, (11) 292.
Hursh, R. K., and Welliver, W. E., viscosity-temperature characteristics of coal-ash slags, (11) 292.
Hurst, T. L., slag action of alkalis on refractories, (11) 320.[49]
Hustin, R., fractional fusion of refractories, (11) 292.
Hutchison, Clark, effect of various factors on abrasive resistance of porcelain enamels, (2) 48.
Hyslop, J. F., chemical activity of refractories, (11) 292.
Hyslop, J. F., and Biggs, H. C., corrosion of refractories, quantitative durability test, (11) 292; slag and spalling tests on firebrick, (11) 292.
Hyslop, J. F., Gumm, R., and Biggs, H., corrosion and erosion phenomena, bearing on macrostructure of refractories, (11) 292.
Hyslop, J. F., and Rooksby, H. P., effect of heat on crystalline breakup of kaolin, (1) 3; further note on crystalline breakup of kaolin, (1) 3.

Illgren, F., influence of blast-furnace dust on cone-fusion point of clay materials with various alumina contents, (11) 292.
Insley, H., microstructure of earthenware, (1) 11; notes on behavior of refractories in glassmelting furnaces, (11) 292; quantitative microscopic analysis of commercial feldspar, (14) 421.

Jaeckel, Georg, Entfarben des Glases (decolorization of glasses), (13) 371.
Jänecke, Ernst, Mineralogie und Phasenlehre, (10) 247.
Jebsen-Marwedel, Hans, glastechnische Fabrikationsfehler (technology of defects in glass manufacture), (3) 69; influence of surface tension in glassmelting processes, (6) 168; influence of surface tension of slag glass from refractory material on tendency to form nodes and cords, II, (11) 292; local reactions of slag with furnace refractories, (11) 292.
Jenckel, E., temperature of transformation intervals of glasses formed from B_2O_3 with Na_2O and BaO, (3) 87.
Jette, E. R., and Foote, Frank, study of homogeneity limits of wüstite (FeO) by X-ray methods, (10) 253, (10) 265.
Johnson, A. L., stresses in porcelain glazes, (1) 11.
Johnson, A. L., and Norton, F. H., fundamental study of clay, preparation of purified kaolinite suspension, I, (12) 341, (12) 344; fundamental study of clay, mechanism of deflocculation in clay–water system, II, (9) 224, (12) 338.
Johnson, R. L., corrosive action of frits on refractories, (11) 292.
Jordan, L., Peterson, A. A., and Phelps, L. H., refractories for melting pure metals, Fe, Ni, Pt, (5) 139.
Jung, H., chemicophysical processes during dehydration and rehydration of kaolin crystals, (4) 109.

Kanolt, C. W., melting points of refractory materials, (4) 113, (10) 254.
Karmaus, H. J., latest technical developments in enamel industry, (5) 139.
Kautz, Karl, further data on enamel adherence, (7) 215; molybdenum in enamels, adherence produced with molybdenum compounds, I, (6) 160.
Kenney, J. F., mathematics of statistics, (13) 363.
Keppeler, G., further contributions to knowledge of clays, (1) 2.
Kerstan, W., formation of fish scales in enamels, (7) 215.
King, B. W., Jr., and Andrews, A. I., development of opacity in ZrO_2 enamels, (5) 139; solubility of ZrO_2 in $Na_2O–B_2O_3$ glasses, (5) 139.
Kinney, C. L., steel-mill pouring pit refractories, IV, (11) 292.
Kinney, S. P., and Guernsey, E. W., occurrence, distribution, and significance of alkali cyanides in iron-blast furnace, (11) 320.[68]
Kinzie, C. J., coherent porous Zr silicates, (5) 139; double silicates of Zr and methods of making, (5) 139; opaque vitreous enamel, (5) 139; physical tests for vitreous enamels, (15) 463; zirconium oxide compound, method of making, (5) 139; zirconium oxide opacifier, method of making, (5) 139; zirconium oxide vitreous enamel opacifier, (5) 139.
Kinzie, C. J., and Commons, C. H., effect of ZrO_2 in glasses, glazes, and enamels, (5) 139.
Kinzie, C. J., and Hake, D. S., preparation of zirconium oxycarbide and silicon carbide, (5) 140.
Kitaigorodskii, I. I., and Solomin, N. W., rate of setting of glass during working, (12) 355.
Klein, A. A., time and temperature of burning as factors influencing constitution of microstructure of porcelain body, (2) 40.
Klemm, A., and Berger, E., change in transmission of glasses with temperature below and above transformation point, (14) 399; kinetics of photochemical change in glasses by ultraviolet irradiation and regeneration by reheating, (4) 108.
Klever, E., new investigations on dehydration of kaolin and bearing on mullite question, (1) 3.
Klinefelter, T. A., and Meyer, W. W., properties of American kaolins and comparison with English china clays, (12) 327.
Klinefelter, T. A., Meyer, W. W., and Vachuska, E. J., some properties of English china clays, (12) 327.
Klinefelter, T. A., and Rexford, E. P., action of slags on firebrick and boiler-furnace settings, (11) 292.
Knopf, Adolph, determination of quartz in dusts, (14) 420.
Koenig, C. J., fundamental properties of nepheline syenite, (9) 231; nepheline syenite in ceramic ware, (3) 90, (14) 414; use of nepheline syenite in sanitary ware, (14) 410.
Koeppel, C., feuerfester Baustoffe, (1) 2.
Körber, F., and Ploum, H., absorption of hydrogen by iron during treatment in acid and hydrogen content of iron, (7) 215.
Kohl, Hans, opacifiers, economical use, (5) 141; red and yellow pigments in ceramics, yellow colors with special reference to ivory porcelain, II, (5) 141; thermal expansion and other physical properties of fine porcelain as affected by composition and firing temperature, (2) 40.
Kohlmeyer, F. A., selection of firebrick by comparative tests with detailed description of method to measure temporary expansion or contraction of firebrick at various temperatures, (11) 292.
Kollbohn, L., experience with slagging (boiler) furnace in Germany, (11) 292.
Kolthoff, I. M., and Sandell, E. B., textbook of quantitative inorganic analysis, (3) 84.
Kondo, S., and Suzuki, S., physical properties of talc and talc porcelain by particular method, (15) 441.
Kordes, E., Ermittelung von Atomabständen aus der Lichbrechung, II, (4) 101; Ionenradien und periodisches System, (4) 101; Physikalisch-Chemische Unter-

suchungen über Feinbau von Gläsern, III, (4) 98.
Kraner, H. M., development of slagging test for refractories, (11) 292; microstructure of electrical porcelain glazes, (1) 11.
Krause, O., critical remarks on "studies on dehydration of kaolin in connection with mullite question," (1) 2.
Krause, O., and Jäkel, E., ceramic firing: steatite, data and methods used, effect of firing conditions on structural changes, effect of firing on sintering process, effect of firing on properties of steatite, summary and conclusions, VII–XI, (15) 444.
Krause, O., and Leroux, A., ceramic magnesium silicate, vitrification behavior and constitution of ceramic bodies, II, (15) 444.
Krause, O., and Wohner, H., reactions on firing kaolins, (1) 2.
Kreidl, L., clouding agent for producing clouding effects in white enamels and process, (5) 140; enameling composition, (5) 140; manufacture of white enamel, glass, (5) 140; opaquing agents for production of white enamels, (5) 140; process of manufacturing opaquing agents for white enamel, (5) 140; process of producing filler for white enamel, (5) 140; white enamel, (5) 140.
Kreidl, N. J., and Weyl, W. A., phosphates in ceramic ware, phosphates in glasses, IV, (4) 99.
Krumbein, W. C., thin-section mechanical analysis of indurated sediments, (11) 308.
Kühl, C., Rudow, H., and Weyl, W., oxydations- und reductions-gleichgewichte in Farbengläsern (oxidation and reduction equilibria in colored glasses), (13) 371.

Lai, C. F., and Silverman, Alexander, beryllium glass, (4) 100.
Lambe, C. M., Jr., control of clays containing varying quantities of adsorbed salts, (12) 338.
Lambie, J. M., and Ross, D. W., mold for casting clay blocks and method of molding, (12) 337.
Lampman, C. M., effect of different bodies on some wetting and flow characteristics of glazes, (1) 11; flow of glazes on horizontal and inclined surfaces, (1) 11.
Landrum, R. D., comparison of ten white enamels for sheet steel, (15) 463.
Lange, L. A., fundamentals of enameling clays, (7) 215.
Langmuir, Irving, chemically active modification of hydrogen, (3) 77.
Larsen, E. S., and Berman, H., microscopic determination of nonopaque minerals, (11) 298.
Law, F., electrical measurements, (15) 440.
Lea, F. M., and Parker, T. W., investigations of portion of quaternary system CaO–Al_2O_3–SiO_2–Fe_2O_3, quaternary system CaO–$2CaO \cdot SiO_2$–$5CaO \cdot 3Al_2O_3$–$4CaO \cdot Al_2O_3 \cdot Fe_2O_3$, (10) 247, (10) 248.
LeChatelier, H., Konstitution der Thone, (1) 2.
Lemburg, J., formation and inversions in silicates, (4) 109.
Letort Y., mechanism of corrosion of refractory cupola linings, (11) 292.
Levi, G. R., and Peyronel, G., crystallographic structure of isomorphous group $(Si^{4+}, Ti^{4+}, Zr^{4+}, Sn^{4+}, Hf^{(4+)})P_2O_7$, (4) 102.
Lillie, H. R., viscosity of glass between strain point and melting temperature, (3) 63, (3) 89.
Limbor, destructive action of blast-furnace gases, (11) 318.[3]
Linck, G., mineralogical constitution of clays, (4) 109.
Lindgren, R. A., refractories for iron-blast furnaces, (11) 319.[44]
Line, W. R., and Arradine, P. W., determination of quartz in presence of silicates, (14) 420.
Lintz, E. H., use of talc and pyrophyllite in semivitreous dinnerware bodies, (14) 413.
Litinsky, L., development of refractories containing magnesia, (11) 292.
Littleton, J. T., effect of heat-treatment on physical properties of glass, (2) 40; method for measuring softening temperature of glasses, (3) 63; physical processes occurring in melting and cooling of glass, (2) 40.
Löffler, J., selenium pink as a glass color and modification by rare earths, (5) 142; use of zirconium compounds in glazes, (5) 140.
Long, B., prevention of color development in glasses by exposure to sunlight, (4) 108; Roentgen-ray apparatus, (5) 142.
Long, Bernard, glass and process of making, (5) 140; propriétés physiques et la fusion du verre, (4) 104.
Loux, J. H., effect on furnace refractories of protective gases for high-carbon steels, (11) 320.[51]
Lozinskii, N. M., and Ter-Mikaelyantz, E. I., influence of carbon monoxide on grog materials, (11) 319.[38]
Lurman, F. W., preservation of refractories in blast furnace, (11) 318.[6]
Lyle, A. K., and Sharp, D. E., observations on chemical durability of glass, (5) 148.

Macey, H. H., and Clews, F. H., measurement of apparent porosity, (11) 292.
Malinovszky, A., Panton, H. D., Staley, H. F., and Knight, F. P., Jr., free quartz in feldspar, discussion, (14) 421.
Mallard, E., crystal studies, (14) 391.
Martin, W. G., method of enameling, (7) 215.
Matzen, H. B., and Parmelee, C. E., air conditioning in ceramics, (12) 337.
Mayer, M., and Havas, B., coefficient of expansion of enamels in relation to chemical composition, (4) 100.
McBain, J. W., and Ferguson, John, nature of influence of humidity changes on composition of building materials, (4) 110.
McCaffery, R. S., Oesterle, J. F., and Schapiro, Leo, compositions of blast-furnace slags, (10) 247.
McCauley, G. V., fundamentals of heat flow in molten glass and in walls for use against glass, (12) 355.
McDougal, T. G., Pessler, A. H., and Bartlett, H. B., ceramic bodies for spark-plug insulators, (5) 140.
McDowell, J. S., and Howe, R. M., basic refractories, for open hearth, (11) 292; cite magnesite refractories by C.R. Fettke, (11) 308.
McDowell, S. J., ceramic body, method of making, (15) 441.
McDowell, S. J., and Lee, H. C., petrographic study of slags from boiler furnaces, (11) 292.
McIntosh, A. B., Rait, J. R., and Hay, R., binary system FeO–Al_2O_3, (6) 152, (10) 254.
McIntyre, G. H., physical testing of porcelain enameled hollow ware, (15) 463.
McIntyre, G. H., and Bozsin, M., rapid determination of quartz in feldspar, (14) 421.
McKay, R. J., and Worthington, R., corrosion resistance of metals and alloys, (6) 164.
McKenna, P. M., tantalum carbide, relation to other hard refractory compounds, (5) 140.
McLain, W. R., blast-furnace refractories, present application and possible future development, (11) 320.[73]
McMahon, J. F., improved Goodner mercury volumeter, (10) 275.
McMahon, J. F., and Fossaceca, S. A., influence of zircon, talc, and feldspar mixtures on properties of whiteware bodies, (5) 140.
McMullen, J. C., new slag test furnace, (11) 292.
McMurdie, H. F., and Insley, Herbert, quaternary system CaO–MgO–$2CaO \cdot SiO_2$–$5CaO \cdot Al_2O_3$, (10) 248.
McRitchie, F. H., cone deformation study of high flux area in nepheline syenite–flint–kaolin system, (9) 231.
McVay, T. N., identification of crystalline substances by petrographic microscope, (11) 292.
McVay, T. N., and Hursh, R. K., effects of coal ash on refractories, (11) 292.
McVay, T. N., and Thompson, C. L., X-ray investigation of effect of heat on china clays, (1) 3.
Mellor, J. W., action of flue dust on firebrick, (11) 292; behavior of glazes in glost oven, (1) 11; comprehensive treatise on inorganic and theoretical chemistry, Vols. V, IX, and XII, (14) 391, (4) 98, and (11) 319[31]; crazing and peeling of glazes, (1) 11, (2) 46; plasticity of clay, (1) 16; sulfuring and feathering of glazes, II, (14) 420.
Mellor, J. W., and Emery, W., corrosive action of flue dust on firebrick, (11) 293.
Mellor, J. W., and Green, A. T., refractory materials, (11) 293.
Mellor, J. W., and Holdcroft, A. D., chemical constitution of kaolinite molecule, (1) 2, (4) 109.
Melzer, recent experience with cerium oxide in enamel industry, (5) 143.
Menke, P. O., blast-furnace lining failures caused by zinc, (11) 320[64]; disintegration of blast-furnace linings, 319.[35]
Merritt, G. E., interference method of measuring thermal expansion, (3) 62.
Merwin, B. W., cerium oxide and rare earth oxide mixture in glaze, (5) 143.
Merwin, H. E., and Andersen, Olaf, properties of glass cited by G. W. Morey, (4) 103.
Meyer, H. C., zirconia, (5) 140; zirconium, (5) 140.
Meyer, W. W., and Klinefelter, T. A., substitution of domestic for imported clays in whiteware bodies, (12) 327.
Miehr, W., standards for testing probable behavior of tank blocks, (11) 293.
Miehr, W., Kratzert, J., and Immke, H., resistance to action of slags by refractory materials, (11) 293.
Mikesch, Rudolf, and Salmang, Hermann, investigations on slagging of refractory materials, slagging of magnesite, III, (11) 293.
Mitra, H. K., and Silverman, Alexander, prevention of disintegration of blast-furnace linings, (11) 319.[33]
Moissan, H., and Lengefeld, new zirconium carbide, (5) 140.
Mond, L., and Quincke, F., volatile compound of iron and carbonic oxide, (11) 318.[6]
Moore, C. E., plasticity of clay, (4) 109.
Moore, G. A., and Smith, D. P., occlusion and evolution of hydrogen by pure iron, (7) 215.
Morey, G. W., optical glass, (4) 98, (5) 140, (5) 142; properties of glass, (3) 69, (4) 98, (4) 103; cites P. Weiller, H. E. Merwin and Olaf Andersen, and N. L. Bowen, J. F. Schairer, and H. W. v. Willems, (4) 103.
Morey, G. W., Kracek, F. C., and Bowen, N. L., ternary system K_2O–CaO–SiO_2, (10) 268.
Moriyasu, S., comparison of glass and crystal with resistivity, (15) 441; electrical resistance of magnesia–alumina–silica–alkali system, (15) 441; electrical resistance of talc–kaolin system, (15) 441.
Morse, P. M., vibration and sound, (14) 409.

Nakai, Toshio, and Fukami, Yoshio, systems composed of silica, alumina, and magnesia, I, (1) 1.
Navias, Louis, welded zigzag windings and refractory shapes for high-temperature furnaces, (4) 112.
Navias, Louis, and Davey, W. P., differentiation between mullite and sillimanite by X-ray diffraction pattern, (1) 7.
Navias, Louis, and Gallup, J., selenium dioxide as constituent of glasses, (4) 100.
Nefedieva, O. V., and Pacukov, N. B., laboratory tests of chemical activity of ashes of solid fuels in relation to refractories, (11) 293.
Nelson, M. S., and Wilson, Hewitt, multiple-tunnel kilns, (9) 240.
Nesbitt, C. E., disintegration of firebrick linings in iron-blast furnaces, (11) 319.[41]
Nesbitt, C. E., and Bell, M. L., firebrick disintegration, (11) 319[37]; practical methods for testing refractory firebrick, (11) 293; practical methods for testing refractory firebrick, hot and cold abrasion tests, (11) 320.
Neville, R. P., preparation of platinum and platinum rhodium alloy for thermocouples, (5) 140.
Nicholls, P., determination of thermal conductivity of refractories, (15) 451.
Nicholson, C. M., developing Canada's nepheline syenite, (3) 90.
Niedringhaus, F. G., and Niedringhaus, W. F., improvement in manufacture of enameled ironware, (7) 215.
Noll, W., synthesis of montmorillonite, (4) 109.
Norman, James, and Gieseke, E. W., beneficiation of spodumene by froth flotation, (11) 321.
Norton, C. L., Jr., refractory, (1) 1.
Norton, F. H., critical study of differential thermal method for identification of clay minerals, (12) 345; effect of grain sizing on shrinkage and porosity of Georgia kaolin refractories, (3) 93; instrument for measuring workability of clays, (1) 17, (12) 339; measuring viscosity of glass, (3) 89; quantitative

laboratory slag test, (11) 293; thermal expansion of refractories, (3) 93.
Norton, F. H., and Demetrios, G., art and science in sculpture, (12) 340.
Norton, F. H., and Speil, S., fractionation of clay into closely monodispersed systems, (12) 345; measurement of particle sizes in clays, (12) 345.

Obst, W., cites Melzer in "recent experience with cerium oxide in the enamel industry," (5) 143.
O'Harra, B. M., and Darby, W. J., disintegration of refractory brick by carbon monoxide, (11) 319 [16]
Olson, L. C., and Bray, R. H., determination of organic base-exchange capacity of soils, (12) 328.
Orlowski, H. J., and Koenig, C. J., thermal expansion of silicate fluxes in crystalline and glassy states, (3) 90, (9) 231.
Ortman, F. B., composition of kiln gases, effect on terra cotta glazes and colors, (14) 418.
Orton, Edward, Jr., and Krehbiel, J. F., convenient platinum-wound resistance furnace, (4) 112.
Osann, B., action of destructive influence on refractory brickwork in iron mills, (11) 318.[8]
Osborn, E. F., system $CaSiO_3$–diopside–anorthite, (10) 248, (10) 256.
Osborn, E. F., and Schairer, J. F., ternary system pseudowollastonite–akermanite–gehlenite, (10) 248, 263, 268, and 272.
Ostrankov, M. Y., temperature of formation of globules of primary blast-furnace slags, (11) 293.
Owens-Illinois Glass Co. Research Laboratory, effect of barium oxide and zinc oxide on properties of soda-dolomite lime-silica glass, (14) 401.

Paquet, M., applications of cerium, zirconium and titanium compounds to production of enamels on metals and ceramic ware, (5) 142.
Parmelee, C. W., and Horak, William, microstructure of raw lead mat glazes, (1) 11.
Parmelee, C. W. and Ketchum, P. W., investigation of translucency of porcelains, (4) 116.
Parmelee, C. W., and Morgan, W. R., effect of fineness of flint on vitrification of a ceramic body, (14) 415.
Partridge, J. H., and Biggs, H. C., glass-house refractories, study of corrosion-resisting properties, (11) 293.
Partridge, J. H., and Lait, J. R., manufacture of refractory articles from pure oxides of high melting points, (5) 140.
Patterson, W. E., practical tests on refractory mixes, (11) 293.
Pattinson, John, carbon and other deposits from gases of blast furnaces in Cleveland (11) 318.[3]
Pauling, Linus, nature of chemical bond and structure of molecules and crystals, (4) 97, (4) 101, (9) 226.
Pavlish, A. E., and Silverthorn, R. W., analysis of selenium in glass, (5) 127, (13) 373.
Peck, A. B., effect of time and temperature on microstructure of porcelain, (2) 40.
Pendergast, W. L., electric furnace for determination of pyrometric cone equivalents, (4) 112; electric furnace for softening point determinations, (4) 112.
Peters, blast furnace, (11) 320.[40]
Peters, M. F., carborundum brick, (11) 293.
Petersen, C. A., thermal conductivity apparatus, (15) 451.
Phelps, S. M., action of gas atmospheres on refractory materials, (11) 319[39]; disintegration of clay refractories in iron blast furnaces, discussion, (11) 319.[19]
Phillips, J. G., improving properties of clays and shales, (14) 422.
Pines, Y. B., X-ray method for quantitative determination of crystals in refractory materials, (1) 4.
Pirani, Marcello, refractory glass, (5) 140, (5) 141.
Pirani, M., and Partridge, J. H., vitreous body, (5) 140, (5) 141.
Podszus, E., melting ZrO_2 and making zirconia ware, (5) 140; plasticity, I, (5) 140.
Pole, G. R., calcium oxide-chromium oxide-zirconium oxide refractory, (5) 140; calcium oxide-zirconium oxide, refractory, (5) 140.
Pole, G. R., and Moore, D. G., testing refractories against corrosive action of electric-furnace phosphate slags, (11) 293.
Pollard, R. E., and Porter, W. C., surface treatment of steel prior to painting, (7) 215.
Porcelain Enamel Institute, standard acid-resistance test, (2) 49; test for resistance of porcelain enamels to surface abrasion, (2) 49.
Powell, E. B., boiler-furnace refractories, (11) 293.
Prescott, C. H., Jr., and Morrison, James, apparatus for microanalysis of gas, (3) 71.
Pressler, E. E., and Shearer, W. L., properties of potters' flints and effect on whiteware bodies, (14) 413.
Preston, Eric, zirconium oxide as a constituent of glass, (5) 140.
Preston, F. W., behavior and misbehavior of glass in tanks, (12) 355; bottle breakage, causes and types of fractures, (2) 54; resistance of bottles to abuse, (15) 433.
Pukall, K., rapid test of resistance of refractories to carbon monoxide, (11) 319.[45]
Pulfrich, M., optical investigations of magnesium silicate bodies, (15) 444.
Purdy, R. C., and Moore, J. K., pyrochemical and physical behavior of clays, (4) 109.
Przibram, K., discoloration and luminescence by Becquerel rays, (4) 108.

Rammler, E., experience with slagging (boiler) furnace in Czechoslovakia, (11) 293.
Rankin, G. A., and Wright, F. E., ternary system CaO–Al_2O_3–SiO_2, (10) 244, (12) 254, (12) 272.
Rea, R. F., cone fusion study of mixtures of zirconium silicate, silica, and alumina, (5) 140.
Reagan, W. J., open-hearth slag control, (11) 293.
Rees, W. J., blast-furnace linings, (11) 319[22]; slag resistance, (11) 293.
Rees, W. J., and Chesters, J. H., preliminary investigation of magnesia-zircon series, (5) 140.
Renaux, thesis, (5) 140.
Rencker, E., dilatometric study of some ternary glasses, (4) 99; étude dilatometrique de quelques verres ternaires silice-soude-glucine, (4) 99.
Rhode, I., contributions to knowledge of physicochemical changes in firing crystalline kaolin, (1) 2.
Rider, J. F., cathode-ray tube at work, (14) 410.
Rieke, R., and Schade. W., determination of mullite content in porcelain by chemical means, relation between determined mullite content and properties of porcelain, (1) 2.
Rieke, R., and Ungewiss, A., ceramic and dielectric properties of TiO_2–MgO–ZrO bodies, (5) 140.
Rieke, Reinhold, Beobachtungen über der Glühverlust von Kaolinen und Tonen, (1) 2.
Rigg, G., refractory materials, (11) 293.
Rinne, F., Röntgenographische Diagnostik beim Brennen von Kalkstein, Dolomit, Kaolin, und Glimmer, VII, (1) 3.
Robertson, Campbell, ceramic colors, (5) 140.
Robertson, D. W., lead titanate, (4) 98.
Robson, J. T., rapid firing of semiporcelain, (2) 40.
Rochow, W. F., refractories and their applications, (11) 293.
Rochow, W. F., and McDowell, J. S., choosing refractories for superstructure and regenerators of modern glass tanks: refractories and insulating materials, I, (11) 293; refractories in glass house, II, (11) 293.
Rodd, E. H., zirconia as a refractory, (5) 140.
Rodebush, W. H., introductory physical chemistry, (6) 172.
Roehm, V. J., notes on operation of direct-fire tunnel kiln, (14) 420.
Roeser, W. F., Caldwell, F. R., and Wensel, H. T., freezing point of platinum, (5) 140.
Roetheli, B. E., Cox, G. L., and Littreal, W. B., effect of pH on corrosion products and corrosion rate of zinc in oxygenated aqueous solutions, (6) 164.
Roller, P. S., plastic flow of dispersions and new approach to study of plasticity, (1) 17.
Roller, P. S., Rittenberg, D., and Gabriel, A., preparation of laboratory refractory crucibles, (5) 140.
Rooksby, H. P., and Partridge, J. H., X-ray study of natural and artificial mullites, (10) 265.
Rose, C. L., proposed method for studying attack of molten slags and glasses on refractory materials, (11) 293.
Rosenberg, J. E., and Naylor, W. E., method and apparatus for studying physical properties of viscous liquids, (2) 51.
Rosenhain, Walter, phenomena of pot attack, (11) 293.
Rosenhauer, K., and Weidert, F., spectral absorption of neodymium glasses, (5) 142.
Rosin, J., reagent chemicals and standards, (3) 84.
Rosin, P., and Fehling, R., temperature-viscosity relationships of coal slags, conclusions for firing techniques, II, (11) 293.
Ross, L. P., failure of blast-furnace stock line brick, (11) 319.[14]
Ruff, O., and Ebert, F., ceramics of highly refractory materials, forms of zirconium dioxide, I, (5) 140; structure of zirconia, (3) 93.
Ruff, O., and Lauschke, G., manufacture of zirconia ware, (5) 140.
Ruff, O., and Moczala, Josef, plastic materials from ZrO_2, (5) 140.
Rulla, N. V., viscosity of blast-furnace slags, (11) 293.
Ryde, J. W., and Huddart, R., analysis of bubbles in glass, (3) 77.
Ryschkewitsch, E., new ceramic products from pure oxides for chemical purposes, (5) 140.

Sachs, S., testing attack of slag, (11) 293.
Salgado, M. L. M., and Chapman, G. W., simple electrodialysis cell for routine determination of exchangeable bases in soils, (12) 328.
Salmang, Hermann (H.), investigation of slagging of refractory material, (11) 293; physikalischen und chemischen Grundlagen der Keramik (physical and chemical principles of ceramics, (1) 2, (11) 293.
Salmang, H., and Becker, Alfred, gases in glass, I–III, (3) 69.
Salmang, Hermann, and Hebestreit, Otto, dependence of scorifying grog blocks on flux content and porosity, V, (11) 293.
Salmang, Hermann, and Kaltenbach, Joseph, researches on scorification of refractory materials, power of corrosion and constitution of smeltery slag, VI, (11) 293.
Salmang, Hermann, and Schick, Friedrich, investigations of corrosion of refractory materials: influence of chemical composition of slags, II, (11) 293; scorification of refractory materials, III–IV, (11) 293.
Samsoën, M. O., anomaly in expansion of glass B_2O_3, (3) 87.
Sanoskop G. m. b. H., ultraviolet-absorbing glasses, (5) 141.
Sasse, Heinrich, cracked cooking utensils, (15) 463.
Saunders, J. B., improved interferometric procedure with application to expansion measurements, (2) 39.
Saunders, J. B., and Tool, A. Q., effect of heat-treatment on expansivity of Pyrex-brand glass, (2) 39.
Schaal, R. B., and Fuller, D. H., mechanics of blackspeck formation in enamel from reboiling of ground coat, discussion, (7) 215.
Schachtschabel, P., dehydration and rehydration of kaolin, (4) 109.
Schaefer, C., and Rosemann, J., influence of Neophane glass on visibility of interference patterns in white light, (5) 142.
Schaefer, J., determining resistance of refractories to action of slag, (11) 293.
Schaefer, J., and Baumhauer, F., influence of slag on refractory block, (11) 293.
Schauer, T., slag penetration in refractory block, (11) 293.
Schenk, R., and Heller, W., experimental studies on processes in blast furnace, (11) 319.[11]
Schilling, H., gaseous inclusions in glass in form of seeds and bubbles and their qualitative estimation, (3) 77.
Schmid, B. C., Finn, A. N., and Young, J. C., thermal expansions of some soda-lime-silica glasses as function of composition, (4) 99.
Schramm, E., symposium on glazes, problems in whiteware glazes, (1) 11.
Schreinemakers, F. A. H., Mischkristalle in System dreier Stoffe, III, (10) 268, (10) 272.

Schuen, W., vitrified brick and salt glaze, (5) 143.

Schulz, E. H., studying and testing refractory materials for metallurgical industry in Germany, (11) 293.

Schulz, W., opacification by zirconium and cerium oxide, (5) 140.

Schurecht, H. G., effect of electrolytes on properties of clays, (12) 346; reactions of slag with refractories, surface reactions, I, (11) 293; use of electrolytes in purification and preparation of clays, (12) 349.

Schurecht, H. G., and Lampman, C. M., drying properties of clays, effect of small imposed loads on rate of drying of clays, (14) 422.

Schurecht, H. G., and Pole, G. R., effect of water in expanding ceramic bodies of different compositions, (14) 413; methods of measuring strains between glazes and ceramic bodies, (3) 90, (9) 232.

Schwalbe, F. G., depth of heat penetration in molten glass with luminous and nonluminous flames, (12) 355.

Schwalbe, W. L., Badger, A. E., and Silverman, W. B., tensile tests of glasses, (1) 29.

Searle, A. B., refractory materials for blast-furnaces, I–III, (11) 320.[71]

Shands, E. H., thermal-shock test for porcelain enamel, (15) 463.

Shaw, J. B., Bair, G. J., and Shaw, M. C., progress report on development of abrasion test for refractories at high temperatures, (11) 320.[69]

Shelton, G. R., and Meyer, W. W., nature of glass phase in heated clay materials, effect of rate of heating on glass phase and physical properties of whiteware bodies, II, (2) 38.

Shepherd, E. S., analysis of gases obtained from volcanoes and from rocks, (3) 72.

Sherman, R. A., study of refractories service conditions in boiler furnaces, (11) 293.

Shewart, W. A., economic control of quality of manufactured product, (15) 437.

Silverman, Alexander, effect of isomorphous substances on glass, (4) 99.

Silverman, W. B., effect of alumina on devitrification of soda-lime-silica glasses, (3) 63; effect of alumina on expansion and deformation temperatures of soda-lime-silica glasses, (3) 62.

Simpson, H. E., classified review of refractory slag tests, (11) 293; investigation of action of coal-ash slags on firebrick by microscopic methods, (11) 293.

Škola, V, combined testing methods, (11) 293; methods for producing refractory ZrO_2 ware, (5) 140.

Skoloff, A. M., Frage des molekularen Zerfalles des Kaolinits im Anfangsstadium des Glühens, (1) 2.

Slater, A. C., zirconia deposits of Brazil, (5) 140.

Smekal, A., breaking of glass, (1) 29.

Smith, P. L., chipping resistance of enamels, (1) 29.

Snow, R. B., equilibrium in system FeO–Al_2O_3–SiO_2, (10) 244.

Société Anon. des Manufactures des Glaces & Produits Chemiques de St. Gobain, Chauney & Cirey, preparation of crystallized zirconia by fusing, cooling, and grinding resulting mass and treating with HF, (5) 140.

Sortwell, H. H., American and English ball clays, (12) 327.

Sosman, R. B., properties of silica, (11) 295.

Spangenberg, K., phases developed in firing kaolin, (1) 2.

Spell, S., effect of adsorbed electrolytes on properties of monodisperse clay–water systems, (12) 338, (12) 344.

Spencer-Strong, G. H., and King, R. M., mechanics of enamel adherence, equilibrium studies of systems of enamel glass and cobalt, nickel, and iron oxides, (9) 219.

Spiers, C. H., direct-reading volumenometer for determining real volume and specific gravity of porous bodies, (10) 275.

Springer, L., decolorizing glass without decolorizing agents, (4) 104.

Stackelberg, M. v., and Chudoba, K., density and structure of zircon, I, (5) 139.

Staley, H. F., study of relation between fusibility and heat range in glazes, (1) 12.

Starkie, D., and Turner, W. E. S., ultraviolet light-transmitting glasses, (4) 107.

Starostin, F. D., determination of resistance of silica brick to slag, (11) 293.

Steatit-Magnesia Akt.-Ges., ceramic material, (15) 441.

Steger, W., comparative tests on whiteware glazes, effect of sulfur dioxide on whiteware glazes containing lead and boron, (14) 420; translucency of porcelain, (4) 117.

Stewart, W. E., slag attack on refractory brick, (11) 293.

Stoecker, J., and Rein, A., developments in blast-furnace lining, (11) 319.[66]

Stone, G. C., discussion on refractory firebrick, (11) 293.

Stout, Wilber, relations between manufacture and properties of refractory clayware, (11) 293.

Streletz, V. M., cracks in blast-furnace refractories, (11) 320.[73]

Ströble, W., effect of light filters, especially of neodymium-containing glasses on color sensation, (5) 142.

Stromberg, B. W., furnace-testing refractories for slag erosion, (11) 293.

Stuckert, L., expansion of enamels, (15) 463.

Stull, R. T., and Johnson, P. V., relation between moisture content and flow-point pressure of plastic clay, (1) 17, (12) 340.

Sullivan, J. D., communication on copper calorimeter and guard ring for thermal conductivity tests, (15) 454.

Sun, K.-H., and Silverman, Alexander, additive factors for calculating coefficient of thermal expansion of glass from its composition, (4) 99; tantalum glass, K_2O–Ta_2O_5–SiO_2 series, (4) 98.

Swanger, W. H., melting, mechanical working, and physical properties of rhodium, (15) 140.

Swanger, W. H., and Caldwell, F. R., special refractories for use at high temperatures, (5) 140.

Sweely, B. T., relation of composition of thermal shock and properties in steel enamels, (15) 463.

Sweetser, R. H., blast-furnace practice, (11) 320.[74]

Swett, G. W., construction of alignment charts, (10) 277.

Tammann, G., glasses as supercooled liquids, (1) 11.

Tammann, G., and Pape, W., silica studies, loss of water of kaolin and behavior in solid condition toward carbonates and oxides of alkaline earths, I, (1) 2.

Taylor, W. C., glass composition, (10) 279; new method of producing colored glass, (10) 278; phase equilibria studies on mixtures of compounds $4CaO·Al_2O_3$–Fe_2O_3–$2CaO·Fe_2O_3$–$K_2O·Al_2O_3$, (11) 294.

Taylor, W. C., and Smith, R. D., solubility characteristics of glasses of basically different composition, (6) 167.

Taylor, W. H., structure of sillimanite and related minerals, (1) 3.

Tetrick, J. D., case history of scratch blisters, (7) 215; opacity development in cover enamels for sheet steel, (2) 48.

Thiel, A., and Schulte, E., binary equilibrium systems with solid CO_2, (3) 74.

Thiess, L. E., method of recording plastic properties of porcelain bodies, (1) 17.

Thilo, F., chemical investigations of silicates, magnesium metasilicate formed in thermal decomposition of talc, VII, (15) 444.

Thilo, E., and Rogge, G., chemical investigation of silicates, thermal transformation of anthophyllite, polymorphism of Mg metasilicate and mechanism of transformation of anthophyllite and talc on heating, VIII, (15) 444.

Thomas, C. W., discussion on "testing refractory materials" by J. W. Mellor, (11) 294.

Thomas, F., Siloxide, superior substitute of silica glass, (5) 140.

Thompson, H. V., dissociation of salt, (11) 294.

Thompson, J. G., and Mallet, M. W., preparation of crucibles from special refractories by slip casting, (5) 140.

Thurnauer, H., cordierite gives low expansion in ceramic bodies, (5) 140.

Thurnauer, H., and Badger, A. E., dielectric loss of glass at high frequencies, (15) 440.

Tillyer, E. D., optics and the glass industry, (4) 99.

Tillyer, E. D., Moulton, H. R., and Gunn, T. M., glass composition, (4) 99.

Tives, T. H., ceramic firing, (2) 40.

Toole, M. G., and Nelson, M. S., heat balance on pilot kiln, VI, (9) 239.

Toulouse, J. H., problems in handling glass containers for milk, (2) 55.

Trinks, W., economy and capacity of glass tanks, effect of flame luminosity and other variables, (12) 355.

Troost, L., zirconium carbide, (5) 140.

Turner, Donald, and Turner, W. E. S., observations on corrosion of fire-clay materials by alkali salts, (11) 294.

Turner, W. E. S., and Associates, basis of standard test for chemical durability of glass bottles, (5) 147, (13) 359; constitution of glass (editor), (1) 11.

Turner, W. E. S., and Winks, F., study of casing of colorless by cobalt blue glass, question of setting rate, II, (12) 355.

Twells, Robert, and Lin, C. C., effect of substituting Al_2O_3 and ZrO_2 for free SiO_2 in electroporcelain, (5) 140.

Tyson, H. D., brick mason and blast furnace, II, (11) 320.[72]

Unger, J. S., blast-furnace refractories by R. M. Howe, discussion, (11) 320.[69]

Upton, L. O., light-sensitive glass and application for ultraviolet measurements, (4) 104.

Van Nieuwenburg, C. J., and Pieters, H. A., studies on hydrated aluminum silicates, rehydration of metakaolin and synthesis of kaolin, I, (4) 109.

Vereinigte Stahlwerke A.-G., refractory materials, (11) 319.[65]

Vernadsky, W., behavior of kaolin on heating, (1) 2.

Vernon, W. H. J., Wormwell, F., and Nurse, T. J., thickness of air-formed oxide films on iron, (7) 215.

Vickers, A. E. J., and Bell, R. A., apparatus for investigating corrosive action of slags on refractory materials, (11) 294.

Vielhaber, L., determining physical properties of enamels, (15) 463.

Wadsworth, M. E., lithological studies, (11) 310.

Warren, B. E., summary of work on atomic arrangement in glass, (14) 395; X-ray diffraction study of structure of glass, (4) 101, (13) 379.

Warren, B. E., and Biscoe, J., Fourier analysis of X-ray patterns of soda-silica glass, (3) 85, (4) 102; structure of silica glass by X-ray diffraction study, (4) 102.

Warren, B. E., Krutter, H., and Morningstar, O., Fourier analysis of X-ray patterns of vitreous SiO_2 and B_2O_3, (3) 83, (4) 102.

Wartenberg, H. v., and Eckhardt, K., fusion-point diagrams of highly refractory oxides, systems with CeO_2, VII, (5) 143.

Wartenberg, H. v., and Gurr, W., melting diagrams of superrefractory oxides, II, (5) 140; melting points of refractory oxide systems, III, (3) 95.

Washburn, E. W., and Bunting, E. N., Na_2O–TiO_2 system, (4) 98.

Washburn, E. W., and Libman, E. E., approximate determination of melting diagram of system ZrO_2–SiO_2, (5) 141.

Watkins, E. H., why a variation as small as 3% of silicon oxide content in feldspar will cause a wide variation in workability of porcelain enamel, (14) 421.

Watts, A. P., determination of effect on wall-tile glazes of direct firing with gas, (14) 420; effect of furnace atmospheres on quality of certain types of glazes, (14) 417.

Watts, A. S., data on influence of firing time on properties of some whiteware bodies, (2) 40.

Weber, E., liquefaction of clays by alkalis and use of fluid clay casting in ceramic industry, (12) 337.

Wedekind, E., preparation of zirconia, (5) 141.

Weidert, F., absorption spectrum of didymium glasses with various compositions of base glass, (5) 142.

Weidert, F., and Löffler, Hans, neodymium glasses in navigation and aviation, (5) 142.

Weiller, P., properties of glass cited by G. W. Morey, (4) 103.

Weinland, C. E., conductivity apparatus, (15) 451; method of measuring thermal conductivity at furnace temperatures, (14) 458.

Weiss, L., ZrO_2 as enamel opacifier, (5) 139.

Weiss, L., and Lehmann, R., zirconium oxide, (5) 141.

Wensel, H. T., Roeser, W. F., Barbow, L. E., and Caldwell, F. R., Waidner-Burgess standard of light, (5) 141.

West, C. D., immersion liquids of high refractive index, (6) 155.
Westman, A. E. R., capillary suction of ceramic materials, (14) 422; mercury balance, (10) 275.
Wetherill, W. H., and Furnas, C. C., rate of reduction of iron ores with carbon monoxide, effect of particle size, gas velocity, and gas composition, (11) 319.[49]
Weyl, W., chemistry of colored glass, (4) 107, (13) 380, (14) 395; contribution to fluorescence of glasses, (10) 278; thermal history of glassy phase and effect on physical properties, (2) 39.
Weyl, W. A., and Pincus, A. G., role of gases in glass, oxygen, carbon dioxide evolution and method of following reactions in batch, water, and miscellaneous gases, I–IV, (3) 69.
Wheeler, R. S., and Kuechler, A. H., new mercury volumeter, (10) 275.
Whittaker, H., effect of particle size on plasticity of kaolinite, (9) 226, (12) 345.
Wilkes, G. B., description of Heilman furnace, (15) 451; thermal conductivity of refractories, (15) 451.
Wilson, E. O., plasticity of finely ground minerals with water, (1) 17, (9) 227.
Wilson, Hewitt, ceramics, clay technology, (1) 16.
Wilson, Hewitt, Sims, C. E., and Schroeder, F. W., artificial sillimanite as refractory, II, (11) 294.
Wilson, Hewitt, and Skinner, K. G., review of four years research on refractory properties of Pacific-Northwest olivine, (11) 294.
Wilson, L. M., effect of salty coal on refractory materials, (11) 294.
Winchell, A. N., microscopic characters of artificial minerals, (6) 154; spinel group, (6) 153.
Wiss, J. E., Camp, T. P., and Ladoo, R. B., gypsum plaster in ceramic industry, (12) 337.
Woodhouse, W., Hugill, W., and Green, A. T., blast-furnace linings, investigation of linings of three blown-out furnaces, IV, (11) 319–20.[48]
Wooten, L. A., microgas-analysis metaods, application to research, (3) 77.

Yoshioka, Tosaku, and Isomatsu, Minezo, study of mullite, I, (1) 1.

Zachariasen, W. H., atomic arrangement in glass, (4) 97, (4) 103, (13) 379, (14) 395.
Zapffe, C. A., cause of defects in enamel fired on cast iron above 725°C., I, (7) 215.
Zapffe, C. A., and Faust, C. L., metallurgical aspects of hydrogen in electroplating, (7) 217.
Zapffe, C. A., and Sims, C. E., cause of pinholes and related defects in enamel coatings on cast iron, (7) 215; defects in weld metal and hydrogen in steel, (7) 215; further considerations of hydrogen as cause of enamel defects, (7) 215; hydrogen embrittlement, internal stress, and defects in steel, (7) 215; relation of defects in enamel coatings to hydrogen in steel, (7) 215.
Zapffe, C. A., and Yarne, J. L., chips, fish scales, and shiners, IV, (7) 215; relation of surface oxidation to enamel coatings on steel, III, (7) 215; scratch blisters, II, (7) 215.
Zhirnova, N. A., fusibility diagram of system ZrO_2–MgO, (5) 141.
Zimmerman, F., experimental studies on processes in blast furnace, carbon monoxide, I, (11) 319.[19]
Zschimmer, E., decolorization and discoloring of glass, (4) 107.
Zwetsch, A., X-ray examination of ceramics, (1) 3.

INDEXES FOR CERAMIC ABSTRACTS

Volume 21, 1942

Will be published in the December 15, 1942, issue of *Ceramic Abstracts* and *The Bulletin*

***Ceramic Abstracts* of January through April were published with the *Journal* and May through November with *The Bulletin*. The paging, however, is consecutive and these issues may be bound as usual.**

TWENTY-FIFTH JOURNAL VOLUME

Four Hundred and Eighty-Six Pages

Carefully Edited

Thoroughly Indexed

Research Reports

Vast Store of Knowledge

The compilation and printing costs of this material are insignificant compared to its value to those who study it

---

THE AMERICAN CERAMIC SOCIETY

Formal and Effective Collaboration

Financed by Persons and Corporations

Achieves Advancement of Ceramic Art, Science, and Technology

By Committees, Meetings, and Publications

Personal Membership	**$12.50**
Corporation Membership	**25.00 (minimum)**

SCHICKELGRUBER—A MUD SCAR

That is the Hitlerism We Are Fighting

We Need To Gear Our Efforts

To Make Our Ceramic Products Effective

Aid in Removing This Mud Scar

As Listed in *Modern Industry,* October, 1942, Issue

Ceramic centrifugal pump impellers take 2500 r.p.m.

Ceramic tanks, pipes, and pumps withstand any corrosive liquid or gas except hydrofluoric acid and hot caustic alkalis

Ceramic gas burners for industrial furnaces stand up to tests that break down brass and alloy steel

Ceramic vessels repeatedly withstand thermal shock from icewater to live steam and back again

Ceramic surfaces take abrasion abuse to such an extent that coal chutes are made of porcelain enamel and sandblast nozzles are lined with special ceramic insets

Ceramic products meet severe service requirements as good heat insulators and as excellent electrical insulators

Join in this Cooperative Effort

THE AMERICAN CERAMIC SOCIETY, Inc.

Vol. 25, No. 16, pp. 457-[illegible] (1942)

THE JOURNAL OF THE AMERICAN CERAMIC SOCIETY, DECEMBER 1, 1942 Vol. 25, No. 16, pp. 457–463 (1942)